



### Main

|                           |                       |
|---------------------------|-----------------------|
| Range                     | Acti 9                |
| Product name              | Acti 9 iPC            |
| Product or component type | Modular socket-outlet |
| Device short name         | IPC                   |
| Poles description         | 2P + E                |
| Outlet standard           | French                |

### Complementary

|                                |                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------|
| [In] rated current             | 16 A                                                                                                                 |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz                                                                                                    |
| Mounting mode                  | Fixed                                                                                                                |
| Mounting support               | Symmetrical DIN rail                                                                                                 |
| 9 mm pitches                   | 5                                                                                                                    |
| Height                         | 84 Mm                                                                                                                |
| Width                          | 45 Mm                                                                                                                |
| Depth                          | 60 Mm                                                                                                                |
| Net weight                     | 98 G                                                                                                                 |
| Colour                         | White                                                                                                                |
| Connections - terminals        | Tunnel type terminal1 cable(s) 6 mm <sup>2</sup> flexible<br>Tunnel type terminal1 cable(s) 10 mm <sup>2</sup> rigid |
| Wire stripping length          | 13 Mm                                                                                                                |
| Tightening torque              | 1.2 N.M                                                                                                              |

### Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| Standards                             | IEC 60884-1<br>NF C 15-100<br>NF C 61-314                                        |
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
| IK degree of protection               | IK03                                                                             |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                                      |
| Relative humidity                     | 95 % at 55 °C                                                                    |
| Ambient air temperature for operation | -25...70 °C                                                                      |
| Ambient air temperature for storage   | -40...80 °C                                                                      |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 101.9 G  |
| Package 1 Height             | 4.5 Cm   |
| Package 1 width              | 6.5 Cm   |
| Package 1 Length             | 8.5 Cm   |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 5        |
| Package 2 Weight             | 568 G    |
| Package 2 Height             | 7.2 Cm   |
| Package 2 width              | 9 Cm     |
| Package 2 Length             | 23.8 Cm  |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 75       |
| Package 3 Weight             | 9.007 Kg |
| Package 3 Height             | 30 Cm    |
| Package 3 width              | 30 Cm    |
| Package 3 Length             | 40 Cm    |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**