



Description		Item No.	
Fieldbus Couplers	Fieldbus Coupler PROFIBUS DP; 2nd generation; 12 MBd; extreme	750-333/040-000	352
	Fieldbus Coupler ETHERNET; 3rd generation; extreme	750-352/040-000	353
	Fieldbus Coupler CANopen; D-Sub; extreme	750-338/040-000	354
Digital Input Modules	8-Channel Digital Input; 24 VDC; 3 ms; 2-wire connection; extreme	750-1415/040-000	355
	8-Channel Digital Input; 24 VDC; 3 ms; extreme	750-430/040-000	355
	16-Channel Digital Input; 24 VDC; 3 ms; extreme	750-1405/040-000	356
	8-Channel Digital Input; 24 VDC; 0.2 ms; 2-wire connection; extreme	750-1416/040-000	357
	8-Channel Digital Input; 24 VDC; 0.2 ms; extreme	750-431/040-000	357
	2-Channel Digital Input; 60 VDC; 3 ms; extreme	750-429/040-001	358
	2-Channel Digital Input; 110 VDC; 3 ms; extreme	750-427/040-000	358
	2-Channel Digital Input; 220 VDC; 3 ms; extreme	750-407/040-000	359
Digital Output Modules	2-Channel Digital Output; 24 VDC; 2.0 A; Diagnostics; extreme	750-508/040-000	360
	8-Channel Digital Output; 24 VDC; 0.5 A; Diagnostics; extreme	750-537/040-000	360
	8-Channel Digital Output; 24 VDC; 0.5 A; 2-wire connection; extreme	750-1515/040-000	361
	2-Channel Relay Output; 250 VAC; 1 A; Relay with 2 changeover contacts; extreme	750-517/040-000	362
Analog Input Modules	4-Channel Analog Input; 0 ... 20 mA; single-ended; extreme	750-453/040-000	363
	4-Channel Analog Input; 4 ... 20 mA; single-ended; extreme	750-455/040-000	363
	2-Channel Analog Input; 4 ... 20 mA; Differential input; NAMUR NE 43; extreme	750-492/040-001	364
	4-Channel Analog Input; 0 ... 10 VDC; single-ended; extreme	750-468/040-000	365
	4-Channel Analog Input; ±10 VDC; single-ended; extreme	750-457/040-000	365
	2-Channel Analog Input; 0 ... 30 VDC; Differential input; extreme	750-483/040-000	366
	2/4-Channel Analog Input; Resistance measurement; adjustable; extreme	750-464/040-000	367
	2-Channel Analog Input; Thermocouple; adjustable; extreme	750-469/040-000	367
	3-Phase Power Measurement; 690 VAC 1 A; extreme	750-495/040-000	368
	3-Phase Power Measurement; 690 VAC 5 A; extreme	750-495/040-001	368
	3-Phase Power Measurement; 690 VAC Rogowski coils; extreme	750-495/040-002	368
Analog Output Modules	2-Channel Analog Output; 0/4 ... 20 mA; 16 bits; 6 ... 18 VDC; extreme	750-563/040-000	369
	4-Channel Analog Output; ±10 VDC; extreme	750-557/040-000	370
	4-Channel Analog Output; 0 ... 10 VDC; extreme	750-559/040-000	370
Function/Technology Modules	Counter; adjustable; extreme	750-404/040-003	371
	SSI Transmitter Interface; adjustable; extreme	750-630/040-001	372
	Incremental Encoder Interface; 24 VDC; Differential input; 32 bits; extreme	750-637/040-001	373
Communication Modules	Serial Interface RS-232/485; extreme	750-652/040-000	374
	CAN Gateway; extreme	750-658/040-000	375
Supply/Segment Modules	Power Supply; 24 VDC; extreme	750-602/040-000	376
	Power Supply; 24 VDC; Fuse holder; extreme	750-601/040-000	376
	Power Supply; 24 VDC; Fuse holder; Diagnostics; extreme	750-610/040-000	377
	Power Supply; 0 ... 230 VAC/DC; extreme	750-612/040-000	377
	System Power Supply; 24 VDC; extreme	750-613/040-000	377
	Potential Distribution; 16x 24 V; extreme	750-1605/040-000	378
	Potential Distribution; 16x 0 V; extreme	750-1606/040-000	378
	Potential Distribution; 0 ... 230 VAC/DC; extreme	750-614/040-000	379
	Field Supply Filter (Surge); 24 VDC; Higher isolation; extreme	750-624/040-000	380
	Field Supply Filter (Surge); 24 VDC; Higher isolation; without power jumper contacts; extreme	750-624/040-001	380
	Supply Filter; 24 VDC; Higher isolation; extreme	750-626/040-000	381
	Distance Module; extreme	750-616/040-000	382
	End Module; extreme	750-600/040-000	383
	Power Supply; 24 VDC; extreme; for intrinsically safe XTR modules	750-606/040-000	385
	8-Channel Digital Input; NAMUR; intrinsically safe; extreme	750-439/040-000	386
	2-Channel Digital Output; 24 VDC; intrinsically safe; extreme	750-535/040-000	387
	4-Channel Analog Input; 0/4 ... 20 mA; intrinsically safe; extreme	750-486/040-000	388
Intrinsically Safe XTR Modules	2-Channel Analog Input; 4 ... 20 mA HART; intrinsically safe; extreme	750-484/040-000	389
	2-Channel Analog Input; Resistance measurement; intrinsically safe; extreme	750-481/040-000	390
	2-Channel Analog Output; 0 ... 20 mA; intrinsically safe; extreme	750-585/040-000	391
	Up/Down Counter; intrinsically safe; extreme	750-633/040-000	392