

Eaton 5E UPS

- 1 USB port
- 2 Panel for batteries replacement
- 3 IEC320 10A socket



- 4 6 IEC 10A sockets
- 5 Internet/Tel/Fax protection

Eaton 5E 1100i USB

TECHNICAL SPECIFICATIONS	500	650	650 USB	850 USB	1100 USB	1500 USB	2000 USB
Rating (VA/W)	500 VA / 300 W	650 VA / 360 W	650 VA / 360 W	850 VA / 480 W	1100 VA / 660 W	1500 VA / 900 W	2000 VA / 1200 W
Format	Tower						
Electrical Characteristics							
Technology	Line-Interactive						
Input voltage range without using batteries	170V - 264V	170V - 264V	170V - 280V	170V - 280V	170V - 280V	170V - 280V	170V - 280V
Output voltage	230V						
Data line surge protection (Internet/Tel/Fax)	No	No	Yes	Yes	Yes	Yes	Yes
Connections							
Input	1 IEC C14 (10A)						
Outputs	4 IEC C13 (10A)	IEC models: 4 IEC C13 (10A) DIN models: 1 Schuko (DIN) + 2 IEC C13 (10A)			6 IEC C13 (10A)	6 IEC C13 (10A)	6 IEC C13 (10A)
Batteries							
Typical backup times for 1 PC*	7 min	16 min	16 min	20 min	45 min	50 min	50 min
Typical backup times for 2 PC*	-	6 min	6 min	8 min	20 min	26 min	26 min
Typical backup times for 3 PC*	-	-	-	-	7 min	10 min	10 min
Typical backup times for 4 PC*	-	-	-	-	-	-	5 min
Battery management	Permanent battery recharge, cold start						
Power Management							
Communication ports	No	No	1 USB port	1 USB port	1 USB port	1 USB port	1 USB port
Eaton UPS Companion software	No	No	Yes (available on www.eaton.eu/powerquality)				
Operating conditions, Standards and Approvals							
Operating temperature	0 to 40°						
Noise level	<40dB	<40dB	<40dB	<40dB	<45dB	<45dB	<45dB
Safety	IEC/EN 62040-1						
EMC, Performance	IEC/EN 62040-2						
Approvals	CE, CB report (TUV)						
Dimensions D x H x W / Weight							
Dimensions	288 x 148 x 100mm	288 x 148 x 100mm	288 x 148 x 100mm	288 x 148 x 100mm	330 x 180 x 133mm	330 x 180 x 133mm	330 x 180 x 133mm
Weight	3.66kg	4.6kg	4.64kg	5.16kg	9.22	10.46	10.46
Customer Service & Support							
Warranty	2 years						

* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

Part Numbers	500	650	650 USB	850 USB	1100 USB	1500 USB	2000 USB
IEC outlets	5E500i	5E650i	5E650iUSB	5E850iUSB	5E1100iUSB	5E1500iUSB	5E2000iUSB
Schuko outlets (DIN)	-	5E650iDIN	5E650iUSBDIN	5E850iUSBDIN	-	-	-

In the interests of continuous product improvement, all specifications are subject to change without notice.

