

Zelio Time - Timing Relays

Modular relays with solid state or relay output, width 17.5 mm/0.689 in.

Solid state output

- ☐ Multifunction, dual function, or single function
- ☐ Multi-range (7 selectable ranges)
- ☐ Multivoltage
- ☐ Solid state output: 0.7 A
- ☐ Screw terminals



RE17LAMW



RE17LLBM

Relay output, 1 CO contact

- ☐ Dual function or single function
- ☐ Multi-range (7 selectable ranges)
- ☐ Multivoltage
- ☐ 1 relay output: 8 A
- ☐ Screw and spring terminals
- ☐ State indication by 1 LED
- ☐ Option of supplying a load in parallel
- ☐ 3-wire sensor control option



RE17RAMU



RE17RMMWS

2 C/O contacts

- ☐ Multifunction
- ☐ Multiple timing ranges
- ☐ Multivoltage
- ☐ 2 relay outputs: 8 A - 250 V
- ☐ Screw terminals
- ☐ State indication by LED
- ☐ Option of supplying a load in parallel
- ☐ 3-wire sensor control option



REN22R2MMW

Modular relays with solid state output 0.7 A

Single function

Timing ranges	Functions	Voltages V	Reference	Weight kg/lb
7 selectable timing ranges 1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A	≈ 24...240	RE17LAMW	0.060/ 0.132
	H	≈ 24...240	RE17LHBM	0.060/ 0.132
	C	≈ 24...240	RE17LCBM	0.060/ 0.132

Dual function

7 selectable timing ranges 1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	L, Li	≈ 24...240	RE17LLBM	0.060/ 0.132
--	-------	------------	----------	-----------------

Multifunction

7 selectable timing ranges 1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A, At, B, C, H, Ht, D, Di, Ac, Bw	≈ 24...240	RE17LMBM	0.060/ 0.132
--	-----------------------------------	------------	----------	-----------------

Modular relays with relay output, 1 CO contact

Single function

Timing ranges	Functions	Voltages V	Reference	Weight kg/lb
1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	B	≈ 24/≈ 24...240	RE17RBMU	0.070/ 0.154
	C	≈ 24/≈ 24...240	RE17RCMU	0.070/ 0.154

Dual function

1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A, At	≈ 24/≈ 24...240	RE17RAMU	0.070/ 0.154
	H, Ht	≈ 24/≈ 24...240	RE17RHMU	0.070/ 0.154
	L, Li	≈ 24/≈ 24...240	RE17RLMU	0.070/ 0.154
		≈ 12	RE17RLJU	0.070/ 0.154

Multifunction

1 s, 10 s, 1 min, 10 min, 1 h, 10 h, 100 h	A, At, B, C, H, Ht, D, Di, Ac, Bw	≈ 12	RE17RMJU	0.070/ 0.154
		≈ 24/≈ 24...240	RE17RMMU	0.070/ 0.154
		≈ 12...240	RE17RMMW	0.070/ 0.154
			RE17RMMWS (1)	0.070/ 0.154
1 s, 10 s, 1 min, 10 min, 1 h, 10 h	Ad, Ah, N, O, P, Pt, Ti, Tt, W	≈ 24/≈ 24...240	RE17RMXMU	0.070/ 0.154
		≈ 24/≈ 24...240	RE17RMEMU	0.070/ 0.154

NFC Timing relays with relay output

Multifunction

Timing ranges	Functions	No. of relay outputs	Voltages V	Reference	Weight kg/lb
0.1 s to 999 h	A, Ac, Ad, Ah, Ak, At, B, Bw, C, D, Di, Dt, Di, H, Ht, L, Li, Lt, Lit, N, O, P, Pt, Qt, Qtt, Ti, Tt, W	2	≈ 24...240	REN22R2MMW	0.0904/ 0.1993

(1) Connection by spring terminals.