


ISFT100N


Devices and accessories

ISFT100N 3P fixed front-connected

Basic device for mounting on a backplate	
Connection via 2.5 to 50 mm ² cable connectors	LV480750




Basic device for mounting on busbars	
Hook-on connection to 60 mm busbars	Upstream distribution
	Downstream distribution
	LV480751
	LV480752




Accessories


DIN rail fixing kit	LV480753
---------------------	----------



Support profile laterally attachable	Set of 2	LV480754
--------------------------------------	----------	----------




Terminal shield	Set of 2	LV480756
-----------------	----------	----------




Electrical auxiliaries

Auxiliary changeover contact NO + NC	LV480755
--------------------------------------	----------



ISFT100 3P fixed front-connected

Basic device for mounting on a backplate




Connection via 1.5 to 50 mm² cable connectors

LV480800


Accessories

Mounting accessories



Accessory for mounting on a DIN rail

49877




Escutcheon (not compatible with feeding busbars)

For 1 device
For 2 devices

49878

49879


Connection accessories



Distribution connector 3 x 16 mm²


Set of 3

49860




Feeding busbar to supply 2 devices

49861




Feeding busbar to supply 3 devices

49862



Feeding busbar to supply 4 devices

49863




Incoming connector (25 to 95 mm²) for feeding busbars

Set of 3

49865

Electrical auxiliaries



Auxiliary changeover contact NO + NC


49885

ISFT160

Devices and accessories

ISFT160 3P fixed front-connected

Basic device for mounting on a backplate




M8 terminals

LV480801

2,5 to 95 mm² cable connectors (box clamp)

LV480802

Basic device for mounting on busbars with turnable hooks




ISFT160

LV480803

Accessories

Mounting accessories




Handle with electronic fuse monitor

LV480810

Support profile laterally attachable

LV480817



Terminal shields


LV480819

Connection accessories



Incoming connector

LV480818



Feeding busbars

for 2 devices


LV480811

for 3 devices


LV480812

for 4 devices


LV480813

Distribution connector 3 x 16 mm² for 1,5 to 50 mm² cable connectors

LV480814


Pressure plate for multiple-use terminal from 6 to 50mm²

LV480815

Pressure plate with contact prism for multiple-use terminal with Cu/Alu conductors from 6 to 70 mm²

LV480816

Electrical auxiliaries



Auxiliary changeover contact NO+NC

LV480755


Catalog numbers

ISFT250 to ISFT630

Devices and accessories


ISFT250 to ISFT630 3P fixed front-connected

Basic device for mounting on a backplate



ISFT250	LV480804
ISFT400	LV480806
ISFT630	LV480808


Basic device for mounting on busbars with turnable hooks




ISFT250	LV480805
ISFT400	LV480807

Accessories

Mounting accessories




Handle with electronic fuse monitor	ISFT250	LV480821
	ISFT400	LV480825
	ISFT630	LV480828




Support profile laterally attachable	LV480832
--------------------------------------	----------

Connection accessories




Pressure plate with contact prism for multiple-use terminal with Cu/Al conductors	from 70 to 150 mm ²	ISFT250	LV480822
	from 120 to 240 mm ²	ISFT400	LV480826
	from 150 to 300 mm ²	ISFT630	LV480829



ISFT250 box clamp from 35 to 150 mm ² 35...150 mm ² re/rm 50 to 150 mm ² se/sm	LV480823
---	----------




ISFT400 and ISFT 630 box clamp 95...300 mm ² re/rm 120 to 300 mm ² se/sm	LV480830
--	----------



Terminal shields	ISFT250	LV480824
	ISFT400	LV480827
	ISFT630	LV480831

Electrical auxiliaries



Auxiliary changeover contact NO + NC	LV480833
--------------------------------------	----------

D

ISFL160

Devices and accessories

ISFL160 1-pole switchable fixed front-connected

Basic device for mounting on busbars



Direct connection to 185mm busbars (M12)

LV480900

ISFL160 3-pole switchable fixed front-connected

Basic device for mounting on busbars



Direct hook-on connection to 60 mm busbars

Screws M8

LV480850

Terminals 95 mm²

LV480851

Direct connection to 100 mm busbars


Screws M8

LV480852

Terminals 95 mm²

LV480853

Conversion kit for connection to busbars (for ISFL160 direct connection)




Direct connection to 185 mm busbars

LV480854

Direct connection to 185 mm busbars for 2 ISFL160 devices

LV480855

Accessories




Sideframe door cut out - 850 mm

LV480868

Sidewise angle bracket for side frame (x4)

LV480869



Length adaptor

LV480870


Empty plastic box (46 x 46 mm)

LV480878



Bank panel cover

LV480871



Contact hooks for ISFL 1-pole switchable

Set of 3


LV480905

Connection (accessories for standard M8 terminals)

Lugs for 95 mm² copper cables

Set of 3

28951

Connectors for Cu/Al bare cables 1.5 x 95 mm²


Set of 3

LV480861


for flexible bars 12 x 6 mm

Set of 3


LV480862



Electrical auxiliaries



Auxiliary changeover contact NO + NC			LV480873
--------------------------------------	--	--	----------



1 current transformer for ISFL 1-pole switchable	150/5 A class 1 5 VA	Set of 1	LV480904
---	----------------------	----------	----------



Single block with 3 current transformer for ISFL 3-pole switchable	150/5 A class 1 1.5 VA	Set of 1	LV480881
	150/1 A class 1 2.5 VA	Set of 1	LV480882

Single block with current transformer for ISFL 3-pole switchable	150/5 A class 1 1.5 VA	Set of 1	LV480883
	150/1 A class 1 2.5 VA	Set of 1	LV480884




Fuse monitor for ISFL 3-pole switchable			LV480877
---	--	--	----------

ISFL250 to ISFL1250


Devices and accessories

ISFL250 to ISFL630 1-pole switchable

Basic device for mounting on busbars




Direct connection to 185 mm busbars (screw M12)	ISFL250	LV480901
	ISFL400	LV480902
	ISFL630	LV480903




Hooks for mounting without drilling	LV480859
-------------------------------------	----------

ISFL250 to ISFL630 3-pole switchable

Basic device for mounting on busbars




Direct connection to 185 mm busbars	ISFL250	LV480856
	ISFL400	LV480857
	ISFL630	LV480858
	ISFL1250	LV480875



Hooks for mounting without drilling	LV480859
-------------------------------------	----------

With fuse monitor




Fuse monitor (direct connection to 185 mm busbars)	ISFL250	LV480863
	ISFL400	LV480864
	ISFL630	LV480865
	ISFL1250	LV480876

Catalog numbers


ISFL250 to ISFL1250

Devices and accessories




Accessories

	Sideframe door cut out - 850 mm			LV480868
	Sidewise angle bracket for side frame	Set of 4		LV480869
	Empty plastic box (72 x 72 mm)			LV480879 ^[1]
	Empty plastic box (96 x 96 mm)			LV480880 ^[1]
	Blank panel cover			LV480872

Connection (accessories for standard M12 terminals)

	Connectors	For Cu/Al bare cable 1 x 35 to 300 mm ²	Set of 3	LV480867 ^[1]
		For Cu/Al bare cable 2 x 50 to 185 mm ²	Set of 3	49895 ^[1]
		For Cu/Al cable 4 x 240 mm ²	Set of 3	LV480890 ^[2]
	Screws with plastic support		Set of 3	LV480866 ^[1]
	Coupling kit ISFL250-630			LV480891 ^[1]

Electrical auxiliaries

	Auxiliary changeover contact NO + NC				LV480874
	Current transformer	150/5 class 1	2.5 VA	Set of 1	LV480885
		250/5 class 1	5 VA	Set of 1	LV480886
		400/5 class 1	5 VA	Set of 1	LV480887
		600/5 class 1	5 VA	Set of 1	LV480888
	Click-lock cable transformers			Set of 1	LV480889

^[1] Except for ISFL1250.


^[2] Only for ISFL1250.

GSC32 - GSC50 - GSC125

Devices

GSC32 - GSC50 - GSC125


Basic Device : Front or lateral control



Switch/Type of fuse


GSC32 / NFC
(10 x 38), 32 A

3P/3F




LV481503

4P/3F+N




LV481504



Switch/Type of fuse


GSC50 / NFC
(14 x 51), 50 A
GSC125 / NFC
(22 x 58), 125 A

3P/3F



LV481513



4P/4F



LV481514

LV481524

Direct handle with Test position



Front

32 A


GS1AH103

50 and 125 A

LV481701 ^[1]

Extended Rotary Handle IP 65

Front handle



Front Black Handle

Front Red/Yellow Handle

Front Black Handle + test position

Front Red/Yellow Handle + test position

32 and 50 A

GS2AH510

GS2AH520

GS2AHT510

GS2AHT520

125 A


GS2AH530

GS2AH540

GS2AHT530

GS2AHT540

Lateral handle



Lateral Black Handle

Lateral Red/Yellow Handle

32 and 50 A

GS2AH210

GS2AH220


125 A

GS2AH230

GS2AH240

Accessories

Shaft



200 mm shaft

320 mm shaft

400 mm shaft

32 and 50 A

GS2AE82

GS2AE8

GS2AE81


125 A

GS2AE22

GS2AE2

GS2AE21

Guide cone



32 to 1250 A

GS2AEH12

^[1] Available Q4 2020.


Catalog numbers

GSC32 - GSC50 - GSC125

Accessories

Accessories - GSC32 - GSC50 - GSC125

Connection




External neutral module

For GSC50

LV481900

For GSC125

LV481902



Internal neutral link

For GSC50


LV481911

For GSC125

LV481912

Electrical auxiliaries (Compatible with all GSC products)

Auxiliary contacts




1 NO contact with 2 accessories

GS1AM110

1 NC contact with 2 accessories

GS1AM101



Set of 5 NO contacts

ZBE101

Set of 5 NC contacts

ZBE102



Set of 10 accessories for auxiliary contact

LV481110

Cable connectors



For GSC125


3P (set of 3)

GS1AW33

4P (set of 4)

GS1AW34

Terminal shield



For GSC125

3P (set of 3)

GS1AP33

4P (set of 4)

GS1AP34

Note: FuPacT GS and its accessories are not compatible with the FuPacT INF former range.

Catalog numbers


GSD 63 to 1250

Devices


www.se.com

GSD63 - GSD125 - GSD160 - GSD250 - GSD400 - GSD630 - GSD800 - GSD1250

Basic Device : Front or lateral control




Switch/Type of fuse	3P/3F	4P/4F
GSD63/DIN 000 63 A	LV481403	LV481404
GSD125/DIN 00 125 A	LV481413	LV481414
GSD160/DIN 00 160 A	LV481423	LV481424
GSD250/DIN 1 250 A	LV481433	LV481434
GSD400/DIN 2 400 A	LV481443	LV481444




GSD630/DIN 3 630 A	LV481453	LV481454
GSD800/DIN 3 800 A	LV481463	LV481464
GSD1250/DIN 4 1250 A	LV481473	LV481474

Direct handle with Test position




	63 to 160 A	250 to 400 A	630 to 800 A	1250 A
Front	LV481701 ^[1]	LV481702 ^[1]	-	-

Extended Rotary Handle IP 65




Front handle	63 A	125 to 400 A	630 to 800 A	1250 A
Front Black Handle	GS2AH510	GS2AH530	GS2AH550	GS2AH570
Front Red/Yellow Handle	GS2AH520	GS2AH540	GS2AH560	GS2AH580
Front Black Handle + test position	GS2AHT510	GS2AHT530	-	-
Front Red/Yellow Handle + test position	GS2AHT520	GS2AHT540	-	-



Lateral handle	63 A	125 to 400 A	630 to 1250 A
Lateral Black Handle	GS2AH210	GS2AH230	GS2AH250
Lateral Red/Yellow Handle	GS2AH220	GS2AH240	GS2AH260


Accessories

Shaft



	63 to 400 A	630 to 1250 A
200 mm shaft	GS2AE22	GS2AE52
320 mm shaft	GS2AE2	GS2AE5
400 mm shaft	GS2AE21	GS2AE51

Guide cone



	63 to 1250 A
	GS2AEH12

^[1] Available Q4 2020.

Note: FuPacT GS and its accessories are not compatible with the FuPacT INF former range.



Catalog numbers

GSD 63 to 1250

Accessories



Accessories - GSD63 - GSD125 - GSD160 - GSD250 - GSD400 - GSD630 - GSD800 - GSD1250

Connection

	External neutral module	For GSD63	LV481901
		For GSD100 to GSD160	LV481902
		For GSD200 to GSD250	LV481904
		For GSD400	LV481905
		For GSD630 to GSD800	LV481906
		For GSD1250	LV481907
	Internal neutral link	For GSD63 to GSD160	LV481913
		For GSD250	LV481915
		For GSD400	LV481916
		For GSD630 to GSD800	LV481917
		For GSD1250	LV481918

Electrical auxiliaries (Compatible with all GSD products)


Auxiliary contacts

	1 NO contact with 2 accessories	GS1AM110
	1 NC contact with 2 accessories	GS1AM101
	Set of 5 NO contacts	ZBE101
	Set of 5 NC contacts	ZBE102
 x10	Set of 10 accessories for auxiliary contact	LV481110

Cable connectors

		3P (set of 3)	4P (set of 4)
	For GSD100 to GSD160	GS1AW33	GS1AW34
	For GSD200 to GSD250	GS1AW43	GS1AW44
	For GSD400	LV481203	LV481204

Terminal shield ^[1]

		3P (set of 3)	4P (set of 4)
	For GSD125 to GSD160	GS1AP33	GS1AP34
	For GSD250 to GSD400	GS1AP43	GS1AP44
	For GSD630 to GSD 800	GS2AP73	GS2AP64
	For GSD1250	GS2AP83	GS2AP84

[1] The use of terminal shields is mandatory at 690 V AC.

Note: FuPacT GS and its accessories are not compatible with the FuPacT INF former range.

Catalog numbers


GSB 32 to 1250

Devices


www.se.com

GSB32 - GSB63 - GSB100 - GSB160 - GSB200 - GSB250 - GSB400 - GSB630 - GSB800 - GSB1250


Basic Device : Front or lateral control



Switch/Type of fuse	3P/3F	4P/3F+N
GSB32 - BS A1 32A	LV481603	LV481604




Switch/Type of fuse	3P/3F	4P/4F
GSB63 - BS A2/A3 63A	LV481613	LV481614
GSB100 - BS A4 100A	LV481623	LV481624
GSB160 - BS A4 160A	LV481633	LV481634
GSB200 - BS B1/B2 200A	LV481643	LV481644
GSB250 - BS B1/B2/B3 250A	LV481653	LV481654
GSB400 - BS B1/B2/B3/B4 400A	LV481663	LV481664




GSB630 - BS C2 630A	LV481673	LV481674
GSB800 - BS C3 800A	LV481683	LV481684
GSB1250 - BS D1 1250A	LV481693	LV481694

Direct handle with Test position



	32 A	63 to 160 A	200 to 400 A
Front	GS1AH103	LV481701 ^[1]	LV481702 ^[1]

Extended Rotary Handle IP 65



Front handle	32 to 63 A	125 to 400 A	630 to 800 A	1250 A
Front Black Handle	GS2AH510	GS2AH530	GS2AH550	GS2AH570
Front Red/Yellow Handle	GS2AH520	GS2AH540	GS2AH560	GS2AH580
Front Black Handle + test position	GS2AHT510	GS2AHT530	-	-
Front Red/Yellow Handle + test position	GS2AHT520	GS2AHT540	-	-
Lateral handle	63 A	125 to 400 A	630 to 1250 A	
Lateral Black Handle	GS2AH210	GS2AH230	GS2AH250	
Lateral Red/Yellow Handle	GS2AH220	GS2AH240	GS2AH260	

^[1] Available Q4 2020.

Note: FuPacT GS and its accessories are not compatible with the FuPacT INF former range.


Catalog numbers

GSB 32 to 1250

Accessories

Accessories

Shaft



DB436399.ai

	32 A	63 to 400 A	630 to 1250 A
200 mm shaft	GS2AE82	GS2AE22	GS2AE52
320 mm shaft	GS2AE8	GS2AE2	GS2AE5
400 mm shaft	GS2AE81	GS2AE21	GS2AE51

Guide cone




DB436400.ai

	63 to 1250 A
	GS2AEH12

Accessories - GSB32 - GSB63 - GSB100 - GSB160 - GSB200 - GSB250 - GSB400 - GSB630 - GSB800 - GSB1250

Connection




DB436414.ai

External neutral module	For GSB63	LV481901
	For GSB100	LV481902
	For GSB160	LV481903
	For GSB200 - GSB250	LV481904
	For GSB400	LV481905
	For GSB630 - GSB800	LV481906
	For GSB1250	LV481907


Electrical auxiliaries (Compatible with all GSB products)

Auxiliary contacts



DB436403.ai

1 NO contact with 2 accessories	GS1AM110
1 NC contact with 2 accessories	GS1AM101



DB436402.ai

Set of 5 NO contacts	ZBE101
Set of 5 NC contacts	ZBE102



DB436404.ai

Set of 10 accessories for auxiliary contact	LV481110
---	----------


Cable connectors



DB436405.ai

	3P (set of 3)	4P (set of 4)
For GSB100 to GSB160	GS1AW33	GS1AW34
For GSB200 to GSB250	GS1AW43	GS1AW44
For GSB400	LV481203	LV481204

Terminal shield ^[1]



DB436406.ai

	3P (set of 3)	4P (set of 4)
For GSB125 to GSB160	GS1AP33	GS1AP34
For GSB200 to GSB400	GS1AP43	GS1AP44
For GSB630 to GSB 800	GS2AP73	GS2AP64
For GSB1250	GS2AP83	GS2AP84




[1] The use of terminal shields is mandatory at 690 V AC.

Note: FuPacT GS and its accessories are not compatible with the FuPacT INF former range.




FuPacT protection components

Cartridge fuses type aM

For protection of equipment with current peaks



Fuse type	Maximum rated voltage	Rating	Set of	Fuses without striker	
				Unit reference	Weight
	V	A			kg
Cylindrical 10 x 38	~ 500	20	10	DF2CA20	0.010
	~ 400	25	10	DF2CA25	0.010
		32	10	DF2CA32	0.010
Cylindrical 14 x 51	~ 690	20	10	DF2EA20	0.020
		25	10	DF2EA25	0.020
	~ 500	32	10	DF2EA32	0.020
		40	10	DF2EA40	0.020
		50	10	DF2EA50	0.020
Cylindrical 22 x 58	~ 690	20	10	DF2FA20	0.045
		25	10	DF2FA25	0.045
		32	10	DF2FA32	0.045
		40	10	DF2FA40	0.045
		50	10	DF2FA50	0.045
		63	10	DF2FA63	0.045
		80	10	DF2FA80	0.045
	~ 500	100	10	DF2FA100	0.045
		125	10	DF2FA125	0.045



Fuse type	Maximum rated voltage	Rating	Set of	Fuses without striker	
				Unit reference	Weight
	V	A			kg
Blade NH 000	~ 690	25	3	DF2FGA25	0.160
		32	3	DF2FGA32	0.160
		40	3	DF2FGA40	0.160
		50	3	DF2FGA50	0.160
		63	3	DF2FGA63	0.160
Blade NH 00	~ 690	80	3	DF2FGA80	0.160
		100	3	DF2FGA100	0.160
		125	3	DF2FGA125	0.160
Blade NH 0	~ 690	50	3	DF2GA1051	0.230
		63	3	DF2GA1061	0.230
		80	3	DF2GA1081	0.230
		100	3	DF2GA1101	0.230
		125	3	DF2GA1121	0.230
		160	3	DF2GA1161	0.230
	~ 500	200	3	DF2GA1201	0.230
	~ 690	160	3	DF2HA1161	0.400
Blade NH 1		200	3	DF2HA1201	0.400
		250	3	DF2HA1251	0.400
	~ 500	315	3	DF2HA1311	0.400
	~ 690	250	3	DF2JA1251	0.560
Blade NH 2		315	3	DF2JA1311	0.560
		400	3	DF2JA1401	0.560
	~ 500	500	3	DF2JA1501	0.560
Blade NH 3	~ 690	400	1	DF2KA1401	0.850
		500	1	DF2KA1501	0.850
	~ 500	630	1	DF2KA1631	0.850

[1] Set of 3.

FuPacT protection components

Cartridge fuses type gG

For protection of circuits without significant current peaks



DF2 CN●●




DF2 EN●●




DF2 FN●●

Fuse type	Maximum rated voltage	Rating	Set of	Fuses without striker	Weight
	V	A		Unit reference	kg
Cylindrical 10 x 38	~ 500	20	10	DF2CN20	0.010
	~ 400	25	10	DF2CN25	0.010
		32	10	DF2CN32	0.010
Cylindrical 14 x 51	~ 690	20	10	DF2EN20	0.020
		25	10	DF2EN25	0.020
	~ 500	32	10	DF2EN32	0.020
		40	10	DF2EN40	0.020
		50	10	DF2EN50	0.020
Cylindrical 22 x 58	~ 690	20	10	DF2FN20	0.045
		25	10	DF2FN25	0.045
		32	10	DF2FN32	0.045
		40	10	DF2FN40	0.045
		50	10	DF2FN50	0.045
		63	10	DF2FN63	0.045
		80	10	DF2FN80	0.045
	~ 500	100	10	DF2FN100	0.045




DF2 GN●●●●

DB425717.eps



DF4 GN●●●●

DB43863.eps



DF2 JN●●●●

DB425719.eps

Fuse type	Maximum rated voltage	Rating	Set of	Fuses without striker	Weight
	V	A		Unit reference	kg
Blade NH 000	~ 690	25	3	DF2FGN25	0.160
		32	3	DF2FGN32	0.160
		40	3	DF2FGN40	0.160
		50	3	DF2FGN50	0.160
		63	3	DF2FGN63	0.160
		80	3	DF2FGN80	0.160
	> 500	100	9	DF2FGN100	0.160
Blade NH 00	~ 690	125	3	DF2FGN125	0.160
	~ 500	160	3	DF2FGN160	0.160
Blade NH 0	~ 690	50	3	DF2GN1051	0.230
		63	3	DF2GN1061	0.230
		80	3	DF2GN1081	0.230
		100	3	DF2GN1101	0.230
		125	3	DF2GN1121	0.230
		160	3	DF2GN1161	0.230
	~ 500	125	3	-	-
Blade NH 1	~ 690	160	3	-	-
	~ 500	160	3	-	-
	~ 500	250	3	-	-
Blade NH 2	~ 690	250	3	DF2JN1251	0.560
		315	3	DF2JN1311	0.560
	~ 500	400	3	DF2JN1401	0.560
Blade NH 3	~ 690	500	3	-	-
	~ 500	500	1	DF2KN1501	0.850
		630	1	DF2KN1631	0.850

[1] Set of 3.