

Control and signaling units Ø 30

Harmony 9001K & 9001SK range

Pushbuttons, switches and pilot lights

with double insulated bezel

Complete units 9001SK, with screw clamp terminals

PG1230/1



9001SKR1GH13

109212



9001SKR3RH6

9001K_CPF19057



9001SKR2GH5

109214



9001SKR24BH13

PF1009/8



9001SKR16H13

Pushbuttons, spring return

Shape of head	Type of push	Type of contact			Color	Reference	Weight kg/lb
		NO	NC	CO			
	Flush	1	–	–	Black	9001SKR1BH5	0.086/0.190
		–	–	–	Green	9001SKR1GH5	0.086/0.190
		–	–	1	Black	9001SKR1BH13	0.086/0.190
		–	–	–	Green	9001SKR1GH13	0.086/0.190
		–	–	–	Red	9001SKR1RH13	0.086/0.190
	Projecting	–	–	–	Multi-color	9001SKR1UH13 (1)	0.086/0.190
		1	–	–	Multi-color	9001SKR1UH5 (1)	0.086/0.190
		–	1	–	Red	9001SKR3RH6	0.070/0.154
		–	–	1	Multi-color	9001SKR3UH13 (1)	0.070/0.154
		1	–	–	Multi-color	9001SKR3UH5 (1)	0.070/0.154
	Recessed (high guard)	1	–	–	Green	9001SKR2GH5	0.090/0.198
		–	–	1	Multi-color	9001SKR2UH13 (1)	0.090/0.198
		1	–	–	Multi-color	9001SKR2UH5 (1)	0.090/0.198

Mushroom head pushbuttons

Shape of head	Type of push	Diameter mm/in.	Type of contact			Color	Reference	Weight kg/lb
			NC I. break	NC	CO			
	Spring return	Ø 35/1.38	–	–	1	Black	9001SKR24BH13	0.095/0.209
		Ø 35/1.38	–	1	–	Red	9001SKR24RH13	0.095/0.209
		Snap in Knob	–	–	–	Red	9001SKR4RH6	0.095/0.209
		Ø 57/2.24	–	–	1	Black	9001SKR25BH13	0.102/0.225
		Ø 57/2.24	–	1	–	Red	9001SKR25RH13	0.102/0.225
	3 positions: Push-pull (maintained centre position)	Ø 41/1.61	1	1	–	Black	9001SKR8BH25	0.159/0.351
		Ø 41/1.61	–	–	–	Red	9001SKR8RH25	0.159/0.351
	2 maintained positions: Push-pull	Ø 35/1.38	–	1	–	Red	9001SKR9R20H6	0.159/0.351
		Ø 41/1.61	–	–	1	Black	9001SKR9BH13	0.159/0.351
		Ø 41/1.61	–	–	–	Red	9001SKR9RH13	0.159/0.351
		Ø 41/1.61	–	1	–	Red	9001SKR9RH6	0.159/0.351
		Ø 57/2.24	–	1	–	Red	9001SKR9R21H6	0.164/0.362
	2 positions Turn to release Trigger action (3)	Ø 40/1.58	1	1	–	Red	9001SKR16H13	0.141/0.312
		Ø 40/1.58	2	2	–	Red	9001SKR16H2	0.141/0.312
		Ø 40/1.58	–	–	–	Red	9001SKR16 (2)	0.141/0.312

(1) Supplied with 7 different colored caps: black, green, red, yellow, blue, white and orange, ready for clipping-in.

(2) Supplied without contact block. To order contact blocks, see [page 24](#).(3) Mushroom head Emergency stop trigger action and mechanical latching pushbuttons conform to standards EN/IEC 60204-1 and EN/ISO 13850, Machinery Directive 2006/42/EC, and EN/IEC 60947-5-5 when used with Emergency Stop legend plate 9001KN8330 or 9001KN9330, see [page 26](#).