

Control and signaling units Ø 30

Harmony 9001K & 9001SK range

Pushbuttons, switches and pilot lights

with double insulated bezel

Complete units 9001SK, with screw clamp terminal

108217



9001SKS43FB

Long
handle,
black

Selector switches (For information on contact actuation sequence, please refer to our site www.schneider-electric.com)						
Shape of head	Mount on side	Contact block (order separately)	Contact status 1 - closed 0 - open	Number and type of positions	Reference	Weight kg/lb
	1 or 2	9001KA2 		2 stay put 	9001SKS11FB	0.059/0.130
	1 or 2	9001KA2 		2 spring return from right to left 	9001SKS34FB	0.059/0.130
	1 or 2	9001KA1 		3 stay put 	9001SKS43FB	0.059/0.130
	1 or 2	9001KA1 		3 spring return from left to center 	9001SKS63FB	0.059/0.130
	1 or 2	9001KA1 		3 spring return to center 	9001SKS53FB	0.059/0.130
	Side 1	9001KA1 		4 stay put 	9001SKS88FB	0.059/0.130
	Side 2	9001KA1 				

Illuminated pushbuttons, spring return, flush push (super bright LED included)

Shape of head	Supply	Type of contact	Supply voltage V	Color	Reference	Weight kg/lb
	BA 9s base mounted		24 ~	Red	9001SK1L35LRR	0.181/0.399
				Green	9001SK1L35LGG	0.181/0.399
				Amber	9001SK1L35LYA	0.181/0.399
			48 ~	Red	9001SK1L36LRR	0.181/0.399
				Green	9001SK1L36LGG	0.181/0.399
				Amber	9001SK1L36LYA	0.181/0.399
			120 ~	Red	9001SK1L38LRR	0.181/0.399
				Green	9001SK1L38LGG	0.181/0.399
				Amber	9001SK1L38LYA	0.181/0.399

108221



9001SK1L35LGG

