Control and signaling units
Harmony XB4 metal
Multiple-headed pushbuttons, spring return

User assembly of other units, using:
Body-contact assemblies: see page 76
Combined sub-assemblies: see page 82


569134
XB4BL73415


569136
ZB4BA7121


569138
ZB4BL7341


569140
XB4BW73731●5


569142
ZB4BW7A1721


569150
ZB4BW7A3741

Double-headed pushbuttons *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Description	Type of contact NO	Type of contact NC	Color and marking of caps *(2)*	Reference	Weight kg/*lb*
Complete units						
	2 pushes (1 flush Black + 1 projecting Red)	1	1	White "I" on Green background White "0" on Red background	**XB4BL73415**	0.116/*0.256*
Heads only						
	2 flush Black pushes			White and Black background, unmarked	**ZB4BA7120**	0.056/*0.123*
				Black "I" on White background White "0" on Black background	**ZB4BA7121**	0.056/*0.123*
				Green and Red background, unmarked	**ZB4BA7340**	0.056/*0.123*
				White "I" on Green background White "0" on Red background	**ZB4BA7341**	0.056/*0.123*
				Without cap *(3)*	**ZB4BA79**	0.056/*0.123*
	1 flush Black push 1 projecting Red push			Green and Red background, unmarked	**ZB4BL7340**	0.056/*0.123*
				White "I" on Green background White "0" on Red background	**ZB4BL7341**	0.056/*0.123*

Double-headed pushbuttons + 1 white central pilot light block *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Description	Type of contact NO	Type of contact NC	Color and marking of caps *(2)*	Pilot light voltage V	Reference	Weight kg/*lb*
Complete units							
Protected LED	**1 flush Black push 1 projecting Red push 1 White central pilot light block**	1	1	White "I" on Green background White "0" on Red background	24	**XB4BW73731B5**	0.130/*0.287*
					120	**XB4BW73731G5**	0.130/*0.287*
					240	**XB4BW73731M5**	0.130/*0.287*
Heads only *(5)*							
Protected LED	**2 flush Black pushes 1 clear central pilot light** *(4)*			White and Black background, unmarked		**ZB4BW7A1720**	0.056/*0.123*
				Black "I" on White background White "0" on Black background		**ZB4BW7A1721**	0.056/*0.123*
				Green and Red background, unmarked		**ZB4BW7A3740**	0.056/*0.123*
				White "I" on Green background White "0" on Red background		**ZB4BW7A3741**	0.056/*0.123*
				Black "⬆" on White background White "⇩" on Black background		**ZB4BW7A1724**	0.056/*0.123*
				Black "+" on White background Black "–" on White background		**ZB4BW7A1715**	0.056/*0.123*
				Without cap *(3)*		**ZB4BW7A9**	0.056/*0.123*
Protected LED	**1 flush Black push 1 projecting Red push 1 clear central pilot light** *(4)*			Green and Red background, unmarked		**ZB4BW7L3740**	0.056/*0.123*
				White "I" on Green background White "0" on Red background		**ZB4BW7L3741**	0.056/*0.123*

Heads with black metal bezel

To order, add the suffix **7** to the references selected above. Example: **ZB4BA7120** becomes **ZB4BA71207**.

(1) Recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 24.
(2) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(3) Caps to be ordered separately: see page opposite.
(4) Color of centrally positioned pilot light determined by the color of the LED incorporated in the body sub-assembly.
(5) Only for use with bodies comprising a light source with integral LED.

Presentation:
page 10

Control and signaling units
Harmony XB4 metal
Multiple-headed pushbuttons, spring return

User assembly of other units, using:
Body-contact assemblies: see page 76
Combined sub-assemblies: see page 82

Triple-headed pushbuttons (1) (2)
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Description	Type of contact NO	NC	NO	Color and marking of caps (3)	Reference	Weight kg/*lb*
Complete units							
	**2 flush Black pushes + 1 central projecting Red push marked "Stop" in White**	1	1	1	White "I" on Green background White "II" on Green background	**XB4BA731327**	0.128/*0.282*
					Black "➡" on White background White "⇦" on Black background	**XB4BA711237**	0.128/*0.282*
Heads only							
	**2 flush Black pushes + 1 central projecting Red push marked "Stop" in White**				White "I" on Green background White "II" on Green background	**ZB4BA73132**	0.056/*0.123*
					White "⇦" on Green background White "⇨" on Green background	**ZB4BA73133**	0.056/*0.123*
					White "⇧" on Green background White "⇩" on Green background	**ZB4BA73134**	0.056/*0.123*
					White "+" on Green background White "–" on Green background	**ZB4BA73135**	0.056/*0.123*
					Black "+" on White background Black "–" on White background	**ZB4BA71115**	0.056/*0.123*
					Black "➡" on White background White "⇦" on black background	**ZB4BA71123**	0.056/*0.123*
					Black "⇧" on White background White "⇩" on Black background	**ZB4BA71124**	0.056/*0.123*
					White "⇧" on Black background White "⇩" on Black background	**ZB4BA72124**	0.056/*0.123*
					Without cap (4)	**ZB4BA791**	0.056/*0.123*

569144


XB4BA731327

569146


ZB4BA73133

569148


ZB4BA71124

Specific accessories for multiple-headed pushbuttons

Description	Background color	Marking	Sold in lots of	Reference	Weight kg/*lb*
Caps only for clip-on mounting (5) on: - ZB4BA79 double-headed pushbuttons - ZB4BW7A9 double-headed pushbuttons + central pilot light block - ZB4BA791 triple-headed pushbuttons	White	Unmarked	10	**ZBA71**	0.010/*0.022*
		"I" Black	10	**ZBA7131**	0.010/*0.022*
		"➡" Black	10	**ZBA7134**	0.010/*0.022*
		"+" Black	10	**ZBA7138**	0.010/*0.022*
	Black	Unmarked	10	**ZBA72**	0.010/*0.022*
		"O" White	10	**ZBA7232**	0.010/*0.022*
		"+" White	10	**ZBA7233**	0.010/*0.022*
		"⇨" White	10	**ZBA7235**	0.010/*0.022*
		"I" White	10	**ZBA7237**	0.010/*0.022*
	Green	Unmarked	10	**ZBA73**	0.010/*0.022*
		"I" White	10	**ZBA7331**	0.010/*0.022*
		"+" White	10	**ZBA7333**	0.010/*0.022*
		"⇧" White	10	**ZBA7335**	0.010/*0.022*
		"II" White	10	**ZBA7336**	0.010/*0.022*
	Red	Unmarked	10	**ZBA74**	0.010/*0.022*
		"O" White	10	**ZBA7432**	0.010/*0.022*
	Yellow	Unmarked	10	**ZBA75**	0.010/*0.022*
	Blue	Unmarked	10	**ZBA76**	0.010/*0.022*
Clear silicone boots (6)	For 2 flush pushes	–	10	**ZBA708**	0.055/*0.121*
	For 3 pushes	–	10	**ZBA709**	0.055/*0.121*
	For 1 flush push + 1 projecting push	–	10	**ZBA710**	0.055/*0.121*

540585

ZBA7235

569178

ZBA7432

540598

ZBA709

Heads with black metal bezel

To order, add the suffix **7** to the references selected above.
Example: **ZB4BA73132** becomes **ZB4BA731327**.

(1) Recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 24.
(2) Not compatible with high power switching contacts and contacts for printed circuit board.
(3) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(4) Caps to be ordered separately: see accessories on this page.
(5) Can be clipped-in at 90° steps, through 360°.
(6) Can be replaced without dismantling the head.