
Control and signaling units

Harmony XB4, metal

Illuminated selector switches with standard handle, with integral LED


Assembly of other products using:
Combined sub-assemblies: see page 76
Accessories: see page 90

PF106192





XB4BK123B5

PF106193



XB4BK134B5

Illuminated selector switches with standard handle, with integral LED *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Type of contact NO	Type of contact NC	Positions Number Type	Supply voltage V	Color of handle	Reference	Weight kg/*lb*
Complete units								
	**Standard handle**	1	1	2-position Stay put  90°	24 ⎓ (50/60 Hz)	Green	**XB4BK123B5** (ZB4BW0B35 + ZB4BK1233)	0.101/*0.223*
						Red	**XB4BK124B5** (ZB4BW0B45 + ZB4BK1243)	0.101/*0.223*
						Orange	**XB4BK125B5** (ZB4BW0B55 + ZB4BK1253)	0.101/*0.223*
					110...120 ∼ (50/60 Hz)	Green	**XB4BK123G5** (ZB4BW0G35 + ZB4BK1233)	0.101/*0.223*
						Red	**XB4BK124G5** (ZB4BW0G45 + ZB4BK1243)	0.101/*0.223*
						Orange	**XB4BK125G5** (ZB4BW0G55 + ZB4BK1253)	0.101/*0.223*
					230...240 ∼ (50/60 Hz)	Green	**XB4BK123M5** (ZB4BW0M35 + ZB4BK1233)	0.101/*0.223*
						Red	**XB4BK124M5** (ZB4BW0M45 + ZB4BK1243)	0.101/*0.223*
						Orange	**XB4BK125M5** (ZB4BW0M55 + ZB4BK1253)	0.101/*0.223*
		1	1	3-position Stay put  ± 45°	24 ⎓ (50/60 Hz)	Green	**XB4BK133B5** (ZB4BW0B35 + ZB4BK1333)	0.101/*0.223*
						Red	**XB4BK134B5** (ZB4BW0B45 + ZB4BK1343)	0.101/*0.223*
						Orange	**XB4BK135B5** (ZB4BW0B55 + ZB4BK1353)	0.101/*0.223*
					110...120 ∼ (50/60 Hz)	Green	**XB4BK133G5** (ZB4BW0G35 + ZB4BK1333)	0.101/*0.223*
						Red	**XB4BK134G5** (ZB4BW0G45 + ZB4BK1343)	0.101/*0.223*
						Orange	**XB4BK135G5** (ZB4BW0G55 + ZB4BK1353)	0.101/*0.223*
					230...240 ∼ (50/60 Hz)	Green	**XB4BK133M5** (ZB4BW0M35 + ZB4BK1333)	0.101/*0.223*
						Red	**XB4BK134M5** (ZB4BW0M45 + ZB4BK1343)	0.101/*0.223*
						Orange	**XB4BK135M5** (ZB4BW0M55 + ZB4BK1353)	0.101/*0.223*

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 24.

Presentation:
page 10

Control and signaling units
Harmony XB4, metal
Illuminated selector switches with standard handle, with integral LED

Assembly of other products using:
Combined sub-assemblies: see page 76
Accessories: see page 90



ZB4BK1343

Illuminated selector switches with standard handle, with integral LED (continued) *(1)*

Shape of head	Type of operator	Positions		Color of handle	Reference	Weight kg/*lb*
		Number	Type			
Heads only *(2)*						
Protected LED	**Standard handle**	2-position 90°	Stay put	White	**ZB4BK1213**	0.036/*0.079*
				Green	**ZB4BK1233**	0.036/*0.079*
				Red	**ZB4BK1243**	0.036/*0.079*
				Orange	**ZB4BK1253**	0.036/*0.079*
				Yellow	**ZB4BK1283**	0.036/*0.079*
				Blue	**ZB4BK1263**	0.036/*0.079*
			Spring return from right to left	White	**ZB4BK1413**	0.037/*0.082*
				Green	**ZB4BK1433**	0.037/*0.082*
				Red	**ZB4BK1443**	0.037/*0.082*
				Orange	**ZB4BK1453**	0.037/*0.082*
				Yellow	**ZB4BK1483**	0.037/*0.082*
				Blue	**ZB4BK1463**	0.037/*0.082*
		3-position ± 45°	Stay put	White	**ZB4BK1313**	0.036/*0.079*
				Green	**ZB4BK1333**	0.036/*0.079*
				Red	**ZB4BK1343**	0.036/*0.079*
				Orange	**ZB4BK1353**	0.036/*0.079*
				Yellow	**ZB4BK1383**	0.036/*0.079*
				Blue	**ZB4BK1363**	0.036/*0.079*
			Spring return to center	White	**ZB4BK1513**	0.036/*0.079*
				Green	**ZB4BK1533**	0.036/*0.079*
				Red	**ZB4BK1543**	0.036/*0.079*
				Orange	**ZB4BK1553**	0.036/*0.079*
				Yellow	**ZB4BK1583**	0.036/*0.079*
				Blue	**ZB4BK1563**	0.036/*0.079*
			Spring return from right to center	White	**ZB4BK1813**	0.036/*0.079*
				Green	**ZB4BK1833**	0.036/*0.079*
				Red	**ZB4BK1843**	0.036/*0.079*
				Orange	**ZB4BK1853**	0.036/*0.079*
				Yellow	**ZB4BK1883**	0.036/*0.079*
				Blue	**ZB4BK1863**	0.036/*0.079*
			Spring return from left to center	White	**ZB4BK1713**	0.036/*0.079*
				Green	**ZB4BK1733**	0.036/*0.079*
				Red	**ZB4BK1743**	0.036/*0.079*
				Orange	**ZB4BK1753**	0.036/*0.079*
				Yellow	**ZB4BK1783**	0.036/*0.079*
				Blue	**ZB4BK1763**	0.036/*0.079*

Heads with black metal bezel

To order, add a **7** to the references selected from above.
Example: **ZB4BK1213** becomes **ZB4BK12137**.

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 24.
(2) For use with bodies comprising a light source with integral LED only.