Control and signaling units
Harmony XB4, metal
Pilot lights with integral LED

Assembly of other products using:
Body/light assemblies: see page 84
Accessories: see page 90

101179



XB4BVB5

Pilot lights with integral LED *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Supply voltage V	Color	Reference	Weight kg/*lb*
Complete units				
■ With plain lens				
Protected LED	24 ≂ (50/60 Hz)	White	**XB4BVB1** (ZB4BVB1 + ZB4BV013)	0.080/*0.176*
		Green	**XB4BVB3** (ZB4BVB3 + ZB4BV033)	0.080/*0.176*
		Red	**XB4BVB4** (ZB4BVB4 + ZB4BV043)	0.080/*0.176*
		Orange	**XB4BVB5** (ZB4BVB5 + ZB4BV053)	0.080/*0.176*
		Blue	**XB4BVB6** (ZB4BVB6 + ZB4BV063)	0.080/*0.176*
	110...120 ∿ (50/60 Hz)	White	**XB4BVG1** (ZB4BVG1 + ZB4BV013)	0.080/*0.176*
		Green	**XB4BVG3** (ZB4BVG3 + ZB4BV033)	0.080/*0.176*
		Red	**XB4BVG4** (ZB4BVG4 + ZB4BV043)	0.080/*0.176*
		Orange	**XB4BVG5** (ZB4BVG5 + ZB4BV053)	0.080/*0.176*
		Blue	**XB4BVG6** (ZB4BVG6 + ZB4BV063)	0.080/*0.176*
	230...240 ∿ (50/60 Hz)	White	**XB4BVM1** (ZB4BVM1 + ZB4BV013)	0.080/*0.176*
		Green	**XB4BVM3** (ZB4BVM3 + ZB4BV033)	0.080/*0.176*
		Red	**XB4BVM4** (ZB4BVM4 + ZB4BV043)	0.080/*0.176*
		Orange	**XB4BVM5** (ZB4BVM5 + ZB4BV053)	0.080/*0.176*
		Blue	**XB4BVM6** (ZB4BVM6 + ZB4BV063)	0.080/*0.176*

(1) To add customized markings on these references using the web customization tool, see page 5.

Presentation:
page 10

Schneider Electric

Control and signaling units
Harmony XB4, metal
Pilot lights with integral LED

Assembly of other products using:
Body/light assemblies: see page 84
Accessories: see page 90

101233



ZB4BV063

XB4_632_CPSCT16037



ZB4BV083

101234



ZB4BV043S

Pilot lights with integral LED
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Heads only *(1)*

Shape of head	For use with body comprising light source type	Color of lens	Reference	Weight kg/*lb*
■ With plain lens				
	Integral LED only	White	**ZB4BV013** *(2)*	0.026/*0.057*
		Green	**ZB4BV033** *(2)*	0.026/*0.057*
		Red	**ZB4BV043** *(2)*	0.026/*0.057*
		Orange	**ZB4BV053** *(2)*	0.026/*0.057*
		Yellow	**ZB4BV083** *(2)*	0.026/*0.057*
		Blue	**ZB4BV063** *(2)*	0.026/*0.057*
		5 colors *(3) (4)*	**ZB4BV003**	0.026/*0.057*
■ With plain lens, for insertion of legend *(4)*				
	Integral LED only	White	**ZB4BV013E**	0.026/*0.057*
		Green	**ZB4BV033E**	0.026/*0.057*
		Red	**ZB4BV043E**	0.026/*0.057*
		Orange	**ZB4BV053E**	0.026/*0.057*
		Yellow	**ZB4BV083E**	0.026/*0.057*
		Blue	**ZB4BV063E**	0.026/*0.057*
■ With grooved lens *(5) (2)*				
	Integral LED only	White	**ZB4BV013S**	0.026/*0.057*
		Green	**ZB4BV033S**	0.026/*0.057*
		Red	**ZB4BV043S**	0.026/*0.057*
		Orange	**ZB4BV053S**	0.026/*0.057*
		Yellow	**ZB4BV083S**	0.026/*0.057*
		Blue	**ZB4BV063S**	0.026/*0.057*

(1) For use with bodies comprising a light source with integral LED only.
(2) To add customized markings on these references using the web customization tool, see page 5.
(3) Head supplied with 5 different colored lenses (white, green, red, orange, and blue) not fitted, for insertion of legend.
(4) For legend ordering information, see page 99.
(5) For use in bright ambient light conditions (for example, outdoors in sunlight).

Presentation:
page 10

Control and signaling units
Harmony XB4, metal
Pilot lights with integral LED and with BA 9s base fitting

Assembly of other products using:
Body/light assemblies: see page 84
Accessories: see page 90

PF512544



XB4BV5B1

Pilot lights with integral LED and transformer (1.2 VA, 24 V secondary) *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Supply voltage V	Color	Reference	Weight kg/*lb*
Complete units - With plain lens				
	400 ∼ - 50 Hz *(2)*	White	**XB4BV5B1**	0.172/*0.379*
		Green	**XB4BV5B3**	0.172/*0.379*
		Red	**XB4BV5B4**	0.172/*0.379*
		Orange	**XB4BV5B5**	0.172/*0.379*
		Blue	**XB4BV5B6**	0.172/*0.379*

101178-68-Q




XB4BV64

Pilot lights with BA 9s base fitting, with plain or grooved lens *(1)*
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Supply voltage V	Color	Reference	Weight kg/*lb*
Complete units - With plain lens				
■ Direct supply, for BA 9s bulb, U ≤ 250 V, 2.4 W max (bulb not included)				
	≤ 250	White	**XB4BV61** (ZB4**B**V6 + ZB4**B**V01)	0.075/*0.165*
		Green	**XB4BV63** (ZB4**B**V6 + ZB4**B**V03)	0.075/*0.165*
		Red	**XB4BV64** (ZB4**B**V6 + ZB4**B**V04)	0.075/*0.165*
		Orange	**XB4BV65** (ZB4**B**V6 + ZB4**B**V05)	0.075/*0.165*
■ Via integral transformer, 1.2 VA, 6 V secondary, with BA 9s incandescent bulb (included)				
	110...120 ∼ - 50/60 Hz	White	**XB4BV31** (ZB4**B**V3 + ZB4**B**V01)	0.152/*0.335*
		Green	**XB4BV33** (ZB4**B**V3 + ZB4**B**V03)	0.152/*0.335*
		Red	**XB4BV34** (ZB4**B**V3 + ZB4**B**V04)	0.152/*0.335*
		Orange	**XB4BV35** (ZB4**B**V3 + ZB4**B**V05)	0.152/*0.335*
	230 ∼ - 50 Hz 220...240 ∼ - 60 Hz	White	**XB4BV41** (ZB4**B**V4 + ZB4**B**V01)	0.152/*0.335*
		Green	**XB4BV43** (ZB4**B**V4 + ZB4**B**V03)	0.152/*0.335*
		Red	**XB4BV44** (ZB4**B**V4 + ZB4**B**V04)	0.152/*0.335*
		Orange	**XB4BV45** (ZB4**B**V4 + ZB4**B**V05)	0.152/*0.335*

PF512545-68-Q



XB4BV33

Heads only *(3)*

Shape of head	For use with body comprising light source type	Color of lens	Reference	Weight kg/*lb*
■ With plain lens				
	With BA 9s base fitting	White	**ZB4BV01**	0.027/*0.060*
		Green	**ZB4BV03**	0.027/*0.060*
		Red	**ZB4BV04**	0.027/*0.060*
		Orange	**ZB4BV05**	0.027/*0.060*
		Blue	**ZB4BV06**	0.027/*0.060*
		Clear	**ZB4BV07**	0.027/*0.060*
■ With grooved lens *(4)*				
	With BA 9s base fitting	White	**ZB4BV01S**	0.027/*0.060*
		Green	**ZB4BV03S**	0.027/*0.060*
		Red	**ZB4BV04S**	0.027/*0.060*
		Orange	**ZB4BV05S**	0.027/*0.060*
		Blue	**ZB4BV06S**	0.027/*0.060*
		Clear	**ZB4BV07S**	0.027/*0.060*

101234



ZB4BV04

PG113109-34-Q



ZB4BV06S

(1) To add customized markings on these references using the web customization tool, see page 5.
*(2) To order 440...460 V ∼ - 60 Hz tranformer blocks, replace "5" in the reference with "8". Example: **XB4BV5B1** becomes **XB4BV8B1**. To order 550...600 V ∼ - 60 Hz blocks, replace "5" with "9". Example: **XB4BV5B1** becomes **XB4BV9B1**.*
(3) For use with bodies comprising a light source with BA 9s base fitting (incandescent, neon, or LED) only.
(4) For use in bright ambient light conditions (for example, outdoors in sunlight).

Control and signaling units
Harmony XB4, metal
Push-to-test pilot light

Assembly of other products using:
Body/light assemblies: see page84
Accessories: see page 90



XB4BW21B5



XB4BW25G5

Push-to-test pilot light

Shape of head	Supply voltage V	Color	Reference	Weight kg/*lb*
Complete units - With plain lens				
	24 ≂ - 50/60 Hz	White	**XB4BW21B5**	0.090/*0.198*
	24 ≂ - 50/60 Hz	Green	**XB4BW23B5**	0.090/*0.198*
	24 ≂ - 50/60 Hz	Red	**XB4BW24B5**	0.090/*0.198*
	24 ≂ - 50/60 Hz	Orange	**XB4BW25B5**	0.090/*0.198*
	24 ≂ - 50/60 Hz	Yellow	**XB4BW28B5**	0.090/*0.198*
	24 ≂ - 50/60 Hz	Blue	**XB4BW26B5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	White	**XB4BW21G5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	Green	**XB4BW23G5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	Red	**XB4BW24G5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	Orange	**XB4BW25G5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	Yellow	**XB4BW28G5**	0.090/*0.198*
	110...120 ∿ - 50 - 60 Hz	Blue	**XB4BW26G5**	0.090/*0.198*