Control and signalling units Ø 22

Harmony® XB4 metal

Pushbuttons and switches for harsh environment

Multiple headed pushbuttons, spring return

Assembly of other products using body/contact assemblies: see page 16

Double-headed pushbuttons *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Reference	Weight kg
Complete units (IP 66 + IP 69K)						
	2 pushes (1 flush black + 1 projecting red)	1	1	White "I" on green background White "0" on red background	**XB4 BL73415**	0.116
Heads only (IP 66 + IP 69K)						
	2 flush black pushes			White background + black background, unmarked	**ZB4 BA7120**	0.056
				Black "I" on white background White "0" on black background	**ZB4 BA7121**	0.056
				Green background + red background, unmarked	**ZB4 BA7340**	0.056
				White "I" on green background White "0" on red background	**ZB4 BA7341**	0.056
				Without cap *(3)*	**ZB4 BA79**	0.056
	1 flush black push 1 projecting red push			Green background + red background, unmarked	**ZB4 BL7340**	0.056
				White "I" on green background White "0" on red background	**ZB4 BL7341**	0.056

DF569134



XB4 BL73415

DF569136



ZB4 BA7121

DF569138



ZB4 BL7341

Double-headed pushbuttons + 1 white central pilot light block *(1)*

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	Type of contact N/C	Colour and marking of caps *(2)*	Pilot light voltage V	Reference	Weight kg
Complete units (IP 66 + IP 69K)							
Protected LED	**1 flush black push 1 projecting red push 1 white central pilot light block**	1	1	White "I" on green background White "0" on red background	24	**XB4 BW73731B5**	0.130
					120	**XB4 BW73731G5**	0.130
					240	**XB4 BW73731M5**	0.130
Heads only (IP 66 + IP 69K) *(5)*							
Protected LED	**2 flush black pushes 1 clear central pilot light** *(4)*			White background + black background, unmarked		**ZB4 BW7A1720**	0.056
				Black "I" on white background White "0" on black background		**ZB4 BW7A1721**	0.056
				Green background + red background, unmarked		**ZB4 BW7A3740**	0.056
				White "I" on green background White "0" on red background		**ZB4 BW7A3741**	0.056
				Black "⬆" on white background White "⇩" on black background		**ZB4 BW7A1724**	0.056
				Black "+" on white background Black "–" on white background		**ZB4 BW7A1715**	0.056
				Without cap *(3)*		**ZB4 BW7A9**	0.056
Protected LED	**1 flush black push 1 projecting red push 1 clear central pilot light** *(4)*			Green background + red background, unmarked		**ZB4 BW7L3740**	0.056
				White "I" on green background White "0" on red background		**ZB4 BW7L3741**	0.056

DF569140



XB4 BW73731●5

DF569142



ZB4 BW7A1721

DF569150



ZB4 BW7A3741

Heads with black metal bezel

To order, add the suffix **7** to the references selected above. Example: **ZB4 BA7120** becomes **ZB4 BA71207**.

(1) Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, please consult our site www.schneider-electric.com.
(2) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(3) Caps to be ordered separately: see page opposite.
(4) Colour of centrally positioned pilot light determined by the colour of the LED incorporated in the body sub-assembly.
(5) Only for use with bodies comprising a light source with integral LED.

Control and signalling units Ø 22
Harmony® XB4 metal
Pushbuttons and switches for harsh environment
Multiple headed pushbuttons, spring return

Assembly of other products using body/contact assemblies: see page 16

Triple-headed pushbuttons *(1) (2)*
Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Description	Type of contact N/O	N/C	N/O	Colour and marking of caps *(3)*	Reference	Weight kg
Complete units (IP 66 + IP 69K)							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**	1	1	1	White "I" on green background White "II" on green background	**XB4 BA731327**	0.128
					Black "➡" on white background White "⇦" on black background	**XB4 BA711237**	0.128
Heads only (IP 66 + IP 69K)							
	**2 flush black pushes + 1 central projecting red push marked "Stop" in white**				White "I" on green background White "II" on green background	**ZB4 BA73132**	0.056
					White "⇦" on green background White "⇨" on green background	**ZB4 BA73133**	0.056
					White "⇧" on green background White "⇩" on green background	**ZB4 BA73134**	0.056
					White "+" on green background White "–" on green background	**ZB4 BA73135**	0.056
					Black "+" on white background Black "–" on white background	**ZB4 BA71115**	0.056
					Black "➡" on white background White "⇦" on black background	**ZB4 BA71123**	0.056
					Black "⬆" on white background White "⇩" on black background	**ZB4 BA71124**	0.056
					White "⇧" on black background White "⇩" on black background	**ZB4 BA72124**	0.056
					Without cap *(4)*	**ZB4 BA791**	0.056

DF569144


XB4 BA731327

DF569146


ZB4 BA73133

DF569148


ZB4 BA71124

Specific accessories for multiple-headed pushbuttons

Description	Background colour	Marking	Sold in lots of	Reference	Weight kg
Caps only for clip-on mounting *(5)* **on:** **- ZB4 BA79 double-headed pushbuttons** **- ZB4 BW7A9 double-headed pushbuttons + central pilot light block** **- ZB4 BA791 triple-headed pushbuttons**	White	Unmarked	10	**ZBA 71**	0.010
		"I" black	10	**ZBA 7131**	0.010
		"➡" black	10	**ZBA 7134**	0.010
		"+" black	10	**ZBA 7138**	0.010
	Black	Unmarked	10	**ZBA 72**	0.010
		"O" white	10	**ZBA 7232**	0.010
		"+" white	10	**ZBA 7233**	0.010
		"⇨" white	10	**ZBA 7235**	0.010
		"I" white	10	**ZBA 7237**	0.010
	Green	Unmarked	10	**ZBA 73**	0.010
		"I" white	10	**ZBA 7331**	0.010
		"+" white	10	**ZBA 7333**	0.010
		"⇧" white	10	**ZBA 7335**	0.010
		"II" white	10	**ZBA 7336**	0.010
	Red	Unmarked	10	**ZBA 74**	0.010
		"O" white	10	**ZBA 7432**	0.010
	Yellow	Unmarked	10	**ZBA 75**	0.010
	Blue	Unmarked	10	**ZBA 76**	0.010
Clear silicone boots *(6)*	For 2 flush pushes	–	10	**ZBA 708**	0.055
	For 3 pushes	–	10	**ZBA 709**	0.055
	For 1 flush push + 1 projecting push	–	10	**ZBA 710**	0.055

DF540585

ZBA 7235

DF569177

ZBA 7331

DF569178

ZBA 7432

DF540588

ZBA 709

Heads with black metal bezel

To order, add the suffix **7** to the references selected above.
Example: **ZB4 BA73132** becomes **ZB4 BA731327**.

(1) Recommended maximum number of contacts constituting the body (fixing collar + contact) associated with the head, please consult our site www.schneider-electric.com.
(2) Not compatible with high power switching contacts and contacts for printed circuit board.
(3) These caps are fitted by Schneider Electric and cannot be removed (risk of damage).
(4) Caps to be ordered separately: see accessories on this page.
(5) Can be clipped-in at 90° steps, through 360°.
(6) Can be replaced without dismantling the head.