Control and signalling units Ø 22

Harmony® XB5 plastic

Pushbuttons and switches for harsh environment

Spring return pushbuttons, unmarked

Assembly of other products using body/contact assemblies: see page 16


101287
XB5 AP51


110267
ZB5 AP4


PG113876
ZB5 AP6S


109499
ZB5 AP183


107360
ZBP 0

Pushbuttons with silicone booted head

Screw clamp terminal connections (Schneider Electric anti-retightening system)

Shape of head	Type of push	Type of contact N/O	Type of contact N/C	Colour of push	Reference	Weight kg
Complete units (IP 66 + IP 69K)						
	Booted, clear silicone (colour of push unobscured)	1	–	Black	**XB5 AP21** (ZB5 AZ101 + ZB5 AP2)	0.039
				Green	**XB5 AP31** (ZB5 AZ101 + ZB5 AP3)	0.039
				Yellow	**XB5 AP51** (ZB5 AZ101 + ZB5 AP5)	0.039
				Blue	**XB5 AP61** (ZB5 AZ101 + ZB5 AP6)	0.039
		–	1	Red	**XB5 AP42** (ZB5 AZ102 + ZB5 AP4)	0.039
Silicone booted heads only, with increased protection (IP 66 + IP 69K)						
Flush	**Clear boot** *(1)* For insertion of protected legend within head *(2)*			White	**ZB5 AP18**	0.023
				Green	**ZB5 AP38**	0.023
				Red	**ZB5 AP48**	0.023
				Yellow	**ZB5 AP58**	0.023
				Blue	**ZB5 AP68**	0.023
Projecting	**Clear boot** *(1)*			White	**ZB5 AP1**	0.014
				Black	**ZB5 AP2**	0.014
				Green	**ZB5 AP3**	0.014
				Red	**ZB5 AP4**	0.014
				Yellow	**ZB5 AP5**	0.014
				Blue	**ZB5 AP6**	0.014
Silicone booted heads only, standard for mounting with legend holder (IP 66)						
Flush	**Coloured boot**			White	**ZB5 AP1S**	0.021
				Black	**ZB5 AP2S**	0.021
				Green	**ZB5 AP3S**	0.021
				Red	**ZB5 AP4S**	0.021
				Yellow	**ZB5 AP5S**	0.021
				Blue	**ZB5 AP6S**	0.021
	Clear membrane For insertion of protected legend within head *(2)*			White	**ZB5 AP183**	0.010
				Green	**ZB5 AP383**	0.010
				Red	**ZB5 AP483**	0.010
				Yellow	**ZB5 AP583**	0.010
				Blue	**ZB5 AP683**	0.010

Transparent boots for pushbuttons

Description	For use with pushbutton types	Sold in lots of	Unit reference	Weight kg
Single boots *(1)*	Flush with circular head	10	**ZBP A**	0.002
	Projecting with circular head and push-push version	10	**ZBP 0**	0.002
	Flush or projecting with circular head for food industry applications	10	**ZBP 0A**	0.002

Coloured boots

Description	Colour	For use with	Sold in lots of	Unit reference	Weight kg
Coloured boots *(3)*	Black	ZB5 AP2S	10	**ZBP 012**	0.003
	Green	ZB5 AP3S	10	**ZBP 013**	0.003
	Red	ZB5 AP4S	10	**ZBP 014**	0.003
	Yellow	ZB5 AP5S	10	**ZBP 015**	0.003
	Blue	ZB5 AP6S	10	**ZBP 016**	0.003

Heads with black metal bezel

To order, add a figure **7** to the references selected from above.
Example: **ZB5 AP18** becomes **ZB5 AP187**.

(1) Permissible panel thickness 1 to 5 mm, cannot be used with legend holders.
(2) To order a legend for insertion within the head, please consult our site www.schneider-electric.com.
(3) Can be replaced without dismantling the head.