

Control and signaling units

Harmony XB5, plastic

Flush mounted illuminated pushbuttons, spring return,
with integral LED



Flush mounted illuminated pushbuttons with flush push for Ø 30 mm (continued) ⁽¹⁾				
Shape of head	Type of push	Color	Reference	Weight kg/lb
Heads only, circular ⁽²⁾ - With plain lens				
	Flush	White	ZB5FW313	0.017/0.037
		Green	ZB5FW333	0.017/0.037
		Red	ZB5FW343	0.017/0.037
		Orange	ZB5FW353	0.017/0.037
		Yellow	ZB5FW383	0.017/0.037
		Blue	ZB5FW363	0.017/0.037
	Flush with illuminated ring	White	ZB5FW913	0.016/0.035
		Green	ZB5FW933	0.016/0.035
		Red	ZB5FW943	0.016/0.035
		Orange	ZB5FW953	0.016/0.035
		Yellow	ZB5FW983	0.016/0.035
		Blue	ZB5FW963	0.016/0.035
	Flush for insertion of legend ⁽³⁾ (IP 69 K)	White	ZB5FA18	0.018/0.040
		Green	ZB5FA38	0.018/0.040
		Red	ZB5FA48	0.018/0.040
		Orange	ZB5FA58	0.018/0.040
		Blue	ZB5FA68	0.018/0.040

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

(2) Only for use with bodies comprising a light source with integral LED.

(3) For legend ordering information, see page 97.

Assembly of other products using:
Combined sub-assemblies: see page 80
Accessories: see page 86

Control and signaling units

Harmony XB5, plastic
Flush mounted illuminated pushbuttons, spring return,
with integral LED



Flush mounted illuminated pushbuttons with projecting push for Ø 30 mm ⁽¹⁾				
Shape of head	Type of push	Color	Reference	Weight kg/lb
Heads only, circular (2) - With plain lens				
	Projecting	White	ZB5FW113	0.018/0.040
		Green	ZB5FW133	0.018/0.040
		Red	ZB5FW143	0.018/0.040
		Orange	ZB5FW153	0.018/0.040
		Yellow	ZB5FW183	0.018/0.040
		Blue	ZB5FW163	0.018/0.040

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.