

Assembly of other products using:
Combined sub-assemblies: see page 80
Accessories: see page 86

Control and signaling units

Harmony XB5, plastic

Flush mounted illuminated selector switches
with standard handle, with integral LED

Flush mounted illuminated selector switches with standard handle, with integral LED for Ø 30 mm ⁽¹⁾

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Type of contact	Positions Number and Type	Supply voltage V	Color of handle	Reference	Weight kg/lb	
		NO NC						
Complete units								
Protectow LED	Standard handle	1	1	2-position 90° Stay put ↙	Green	XB5FK123B5 (ZB5AW0B35 + ZB5AK1233)	0.516/1.138	
					Red	XB5FK124B5 (ZB5AW0B45 + ZB5AK1243)	0.516/1.138	
					Orange	XB5FK125B5 (ZB5AW0B55 + ZB5AK1253)	0.516/1.138	
					110...120 ~ (50/60 Hz)	Green	XB5FK123G5 (ZB5AW0G35 + ZB5AK1233)	0.516/1.138
					Red	XB5FK124G5 (ZB5AW0G45 + ZB5AK1243)	0.516/1.138	
					Orange	XB5FK125G5 (ZB5AW0G55 + ZB5AK1253)	0.516/1.138	
					230...240 ~ (50/60 Hz)	Green	XB5FK123M5 (ZB5AW0M35 + ZB5AK1233)	0.516/1.138
					Red	XB5FK124M5 (ZB5AW0M45 + ZB5AK1243)	0.516/1.138	
					Orange	XB5FK125M5 (ZB5AW0M55 + ZB5AK1253)	0.516/1.138	
		1	1	3-position ± 45° Stay put ↙	Green	XB5FK133B5 (ZB5AW0B35 + ZB5AK1333)	0.516/1.138	
					Red	XB5FK134B5 (ZB5AW0B45 + ZB5AK1343)	0.516/1.138	
					Orange	XB5FK135B5 (ZB5AW0B55 + ZB5AK1353)	0.516/1.138	
					110...120 ~ (50/60 Hz)	Green	XB5FK133G5 (ZB5AW0G35 + ZB5AK1333)	0.516/1.138
					Red	XB5FK134G5 (ZB5AW0G45 + ZB5AK1343)	0.516/1.138	
					Orange	XB5FK135G5 (ZB5AW0G55 + ZB5AK1353)	0.516/1.138	
					230...240 ~ (50/60 Hz)	Green	XB5FK133M5 (ZB5AW0M35 + ZB5AK1333)	0.516/1.138
					Red	XB5FK134M5 (ZB5AW0M45 + ZB5AK1343)	0.516/1.138	
					Orange	XB5FK135M5 (ZB5AW0M55 + ZB5AK1353)	0.516/1.138	

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

Control and signaling units

Harmony XB5, plastic

Flush mounted illuminated selector switches
with standard handle, with integral LED



Flush mounted illuminated selector switches with standard handle, with integral LED for Ø 30 mm ⁽¹⁾⁽²⁾

Shape of head	Type of operator	Positions Number	Type		Color of handle	Reference	Weight kg/lb
Heads only							
	Standard handle	2-position 90°	Stay put		White	ZB5FK1213	0.030/0.066
					Green	ZB5FK1233	0.030/0.066
					Red	ZB5FK1243	0.030/0.066
					Orange	ZB5FK1253	0.030/0.066
					Yellow	ZB5FK1283	0.030/0.066
					Blue	ZB5FK1263	0.030/0.066
			Spring return from right to left		White	ZB5FK1413	0.030/0.066
					Green	ZB5FK1433	0.030/0.066
					Red	ZB5FK1443	0.030/0.066
					Orange	ZB5FK1453	0.030/0.066
					Yellow	ZB5FK1483	0.030/0.066
					Blue	ZB5FK1463	0.030/0.066
		3-position ± 45°	Stay put		White	ZB5FK1313	0.030/0.066
					Green	ZB5FK1333	0.030/0.066
					Red	ZB5FK1343	0.030/0.066
					Orange	ZB5FK1353	0.030/0.066
					Yellow	ZB5FK1383	0.030/0.066
					Blue	ZB5FK1363	0.030/0.066
			Spring return to center		White	ZB5FK1513	0.030/0.066
					Green	ZB5FK1533	0.030/0.066
					Red	ZB5FK1543	0.030/0.066
					Orange	ZB5FK1553	0.030/0.066
					Yellow	ZB5FK1583	0.030/0.066
					Blue	ZB5FK1563	0.030/0.066
		Spring return from right to center		White	ZB5FK1813	0.030/0.066	
				Green	ZB5FK1833	0.030/0.066	
				Red	ZB5FK1843	0.030/0.066	
				Orange	ZB5FK1853	0.030/0.066	
				Yellow	ZB5FK1883	0.030/0.066	
				Blue	ZB5FK1863	0.030/0.066	
		Spring return from left to center		White	ZB5FK1713	0.030/0.066	
				Green	ZB5FK1733	0.030/0.066	
Red	ZB5FK1743			0.030/0.066			
Orange	ZB5FK1753			0.030/0.066			
Yellow	ZB5FK1783			0.030/0.066			
Blue	ZB5FK1763			0.030/0.066			

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

(2) Only for use with bodies comprising a light source with integral LED.

