

Control and signaling units

Harmony XB5, plastic

Flush mounted pilot lights with integral LED



XB5FVB1



XB5FVG3

Flush mounted pilot lights with integral LED for Ø 30 mm

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Supply voltage V	Color	Reference	Weight kg/lb
Complete units (with plain lens)				
	24 ~ (50/60 Hz)	White	XB5FVB1 (ZB5AVB1 + ZB5FV013)	0.038/0.084
		Green	XB5FVB3 (ZB5AVB3 + ZB5FV033)	0.038/0.084
		Red	XB5FVB4 (ZB5AVB4 + ZB5FV043)	0.038/0.084
		Orange	XB5FVB5 (ZB5AVB5 + ZB5FV053)	0.038/0.084
		Blue	XB5FVB6 (ZB5AVB6 + ZB5FV063)	0.038/0.084
		Yellow	—	0.038/0.084
	110...120 ~ (50/60 Hz)	White	XB5FVG1 (ZB5AVG1 + ZB5FV013)	0.038/0.084
		Green	XB5FVG3 (ZB5AVG3 + ZB5FV033)	0.038/0.084
		Red	XB5FVG4 (ZB5AVG4 + ZB5FV043)	0.038/0.084
		Orange	XB5FVG5 (ZB5AVG5 + ZB5FV053)	0.038/0.084
		Blue	XB5FVG6 (ZB5AVG6 + ZB5FV063)	0.038/0.084
		Yellow	—	0.038/0.084
	230...240 ~ (50/60 Hz)	White	XB5FVM1 (ZB5AVM1 + ZB5FV013)	0.038/0.084
		Green	XB5FVM3 (ZB5AVM3 + ZB5FV033)	0.038/0.084
		Red	XB5FVM4 (ZB5AVM4 + ZB5FV043)	0.038/0.084
		Orange	XB5FVM5 (ZB5AVM5 + ZB5FV053)	0.038/0.084
		Blue	XB5FVM6 (ZB5AVM6 + ZB5FV063)	0.038/0.084
		Yellow	—	0.038/0.084

Assembly of other products using:
Light block sub-assemblies: see page 76
Accessories: see page 86



Flush mounted pilot lights with integral LED for Ø 30 mm (continued)
Screw clamp terminal connections (Schneider Electric anti-loosening system)

Heads only, circular (1)				
Shape of head	For use with body comprising light source type	Color of lens	Reference	Weight kg/lb
 ■ With plain lens	Integral LED only 	White	ZB5FV013	0.017/0.037
		Green	ZB5FV033	0.017/0.037
		Red	ZB5FV043	0.017/0.037
		Orange	ZB5FV053	0.017/0.037
		Yellow	ZB5FV083	0.017/0.037
		Blue	ZB5FV063	0.017/0.037

(1) Only for use with bodies comprising a light source with integral LED.