

Assembly of other products using:
Combined sub-assemblies: see page 80
Accessories: see page 86

Control and signaling units

Harmony XB5, plastic

Illuminated selector switches with standard handle,
with integral LED



XB5AK123B5



XB5AK124B5



XB5AK125B5

Illuminated selector switches with standard handle, with integral LED ⁽¹⁾

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Type of contact	Positions Number and Type	Supply voltage V	Color of handle	Reference	Weight kg/lb
		 NO  NC					
Complete units							
	Standard handle	1	1	2-position 90° Stay put ▽	24 ~ (50/60 Hz)	Green XB5AK123B5 (ZB5AW0B35 + ZB5AK1233)	0.516/1.138
						Red XB5AK124B5 (ZB5AW0B45 + ZB5AK1243)	0.516/1.138
						Orange XB5AK125B5 (ZB5AW0B55 + ZB5AK1253)	0.516/1.138
					110...120 ~ (50/60 Hz)	Green XB5AK123G5 (ZB5AW0G35 + ZB5AK1233)	0.516/1.138
						Red XB5AK124G5 (ZB5AW0G45 + ZB5AK1243)	0.516/1.138
						Orange XB5AK125G5 (ZB5AW0G55 + ZB5AK1253)	0.516/1.138
					230...240 ~ (50/60 Hz)	Green XB5AK123M5 (ZB5AW0M35 + ZB5AK1233)	0.516/1.138
						Red XB5AK124M5 (ZB5AW0M45 + ZB5AK1243)	0.516/1.138
						Orange XB5AK125M5 (ZB5AW0M55 + ZB5AK1253)	0.516/1.138
		1	1	3-position ± 45° Stay put ▽	24 ~ (50/60 Hz)	Green XB5AK133B5 (ZB5AW0B35 + ZB5AK1333)	0.516/1.138
						Red XB5AK134B5 (ZB5AW0B45 + ZB5AK1343)	0.516/1.138
						Orange XB5AK135B5 (ZB5AW0B55 + ZB5AK1353)	0.516/1.138
					110...120 ~ (50/60 Hz)	Green XB5AK133G5 (ZB5AW0G35 + ZB5AK1333)	0.516/1.138
						Red XB5AK134G5 (ZB5AW0G45 + ZB5AK1343)	0.516/1.138
						Orange XB5AK135G5 (ZB5AW0G55 + ZB5AK1353)	0.516/1.138
					230...240 ~ (50/60 Hz)	Green XB5AK133M5 (ZB5AW0M35 + ZB5AK1333)	0.516/1.138
						Red XB5AK134M5 (ZB5AW0M45 + ZB5AK1343)	0.516/1.138
						Orange XB5AK135M5 (ZB5AW0M55 + ZB5AK1353)	0.516/1.138

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

Assembly of other products using:
Combined sub-assemblies: see page 80
Accessories: see page 86

Control and signaling units

Harmony XB5, plastic

Illuminated selector switches with standard handle,
with integral LED



ZB5AK1263



ZB5AK1313



ZB5AK1783

Illuminated selector switches with standard handle, with integral LED (continued) (1)

Shape of head	Type of operator	Positions Number	Type		Color of handle	Reference	Weight kg/lb
Heads only (2)							
	Standard handle	2-position 90°	Stay put		White	ZB5AK1213	0.016/0.035
					Green	ZB5AK1233	0.016/0.035
					Red	ZB5AK1243	0.016/0.035
					Orange	ZB5AK1253	0.016/0.035
					Yellow	ZB5AK1283	0.016/0.035
					Blue	ZB5AK1263	0.016/0.035
			Spring return from right to left		White	ZB5AK1413	0.017/0.037
					Green	ZB5AK1433	0.017/0.037
					Red	ZB5AK1443	0.017/0.037
					Orange	ZB5AK1453	0.017/0.037
					Yellow	ZB5AK1483	0.017/0.037
					Blue	ZB5AK1463	0.017/0.037
		3-position ± 45°	Stay put		White	ZB5AK1313	0.016/0.035
					Green	ZB5AK1333	0.016/0.035
					Red	ZB5AK1343	0.016/0.035
					Orange	ZB5AK1353	0.016/0.035
					Yellow	ZB5AK1383	0.016/0.035
					Blue	ZB5AK1363	0.016/0.035
			Spring return to center		White	ZB5AK1513	0.016/0.035
					Green	ZB5AK1533	0.016/0.035
					Red	ZB5AK1543	0.016/0.035
					Orange	ZB5AK1553	0.016/0.035
					Yellow	ZB5AK1583	0.016/0.035
					Blue	ZB5AK1563	0.016/0.035
			Spring return from right to center		White	ZB5AK1813	0.016/0.035
					Green	ZB5AK1833	0.016/0.035
					Red	ZB5AK1843	0.016/0.035
					Orange	ZB5AK1853	0.016/0.035
					Yellow	ZB5AK1883	0.016/0.035
					Blue	ZB5AK1863	0.016/0.035
			Spring return from left to center		White	ZB5AK1713	0.016/0.035
					Green	ZB5AK1733	0.016/0.035
					Red	ZB5AK1743	0.016/0.035
					Orange	ZB5AK1753	0.016/0.035
					Yellow	ZB5AK1783	0.016/0.035
					Blue	ZB5AK1763	0.016/0.035

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

(2) Only for use with bodies comprising a light source with integral LED.