

Control and signaling units

Harmony XB5, plastic

Selector switches with standard handle



XB5AD33



ZB5AD2



ZB5AD204

Selector switches with standard handle ⁽¹⁾

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Type of contact		Positions		Reference	Weight kg/lb
		NO	NC	Number	Type		

Complete units

	Standard handle, black	1	—	2-position 90°	Stay put	✓	XB5AD21 (ZB5AZ101 + ZB5AD2)	0.043/0.095
		1	—		Spring return from right to left	↶	XB5AD41 (ZB5AZ101 + ZB5AD4)	0.046/0.101
		1	1		Stay put	✓	XB5AD25 (ZB5AZ105 + ZB5AD2)	0.043/0.095
		2	—	3-position ± 45°	Stay put	↕	XB5AD33 (ZB5AZ103 + ZB5AD3)	0.043/0.095
					Spring return to center	↕	XB5AD53 (ZB5AZ103 + ZB5AD5)	0.043/0.095

Heads only

	Standard handle, black			2-position 90°	Stay put	✓	ZB5AD2	0.017/0.037
					Spring return from right to left	↶	ZB5AD4	0.020/0.044
				3-position ± 45°	Stay put	↕	ZB5AD3	0.017/0.037
					Spring return to center	↕	ZB5AD5	0.017/0.037
					Spring return from left to center	↷	ZB5AD7	0.017/0.037
					Spring return from right to center	↶	ZB5AD8	0.017/0.037


Heads only with other colored handles

	Standard handle, white	Add suffix 01 to the reference, for example: ZB5AD201
	Standard handle, green	Add suffix 03 to the reference, for example: ZB5AD203
	Standard handle, red	Add suffix 04 to the reference, for example: ZB5AD204
	Standard handle, yellow	Add suffix 05 to the reference, for example: ZB5AD205
	Standard handle, blue	Add suffix 06 to the reference, for example: ZB5AD206

(1) For recommended maximum number of contacts and sequence of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

Control and signaling units
Harmony XB5, plastic
Selector switches with long handle

Assembly of other products using:
Body/contact assemblies: see page 74
Accessories: see page 86



ZB5AJ3



ZB5AJ

Selector switches with long handle (1)							
Screw clamp terminal connections (Schneider Electric anti-loosening system)							
Shape of head	Type of operator	Type of contact		Positions		Reference	Weight kg/lb
				Number	Type		
Complete units							
	Long handle, black	1	—	2-position 90°	Stay put	 XB5AJ21 (ZB5AZ101 + ZB5AJ2)	0.043/0.095
		2	—	3-position ± 45°	Stay put	 XB5AJ33 (ZB5AZ103 + ZB5AJ3)	0.043/0.095
					Spring return to center	 XB5AJ53 (ZB5AZ103 + ZB5AJ5)	0.043/0.095
Heads only							
	Long handle, black			2-position 90°	Stay put	 ZB5AJ2	0.017/0.037
					Spring return from right to left	 ZB5AJ4	0.020/0.044
				3-position ± 45°	Stay put	 ZB5AJ3	0.017/0.037
					Spring return to center	 ZB5AJ5	0.017/0.037
					Spring return from left to center	 ZB5AJ7	0.017/0.037
				Spring return from right to center	 ZB5AJ8	0.017/0.037	

(1) For recommended maximum number of contacts and sequence of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

Assembly of other products using:
Body/contact assemblies: see page 74
Accessories: see page 86

Control and signaling units

Harmony XB5, plastic

Key switches

Key no. 455, 8D1, 421E, 458A, 520E or 3131A



Key switches ⁽¹⁾

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Type of contact	Positions ⁽²⁾		Reference	Weight kg/lb
			Number	Type		
		NO				
		NC				

Complete units

	Key switch with key no. 455	1	—	2-position 90°	Stay put		XB5AG21 (ZB5AZ101 + ZB5AG2)	0.831/1.832
							XB5AG41 (ZB5AZ101 + ZB5AG4)	0.831/1.832
					Spring return to left		XB5AG61 (ZB5AZ101 + ZB5AG6)	0.870/1.918
		2	—	3-position ± 45°	Stay put		XB5AG03 (ZB5AZ103 + ZB5AG0)	0.831/1.832
							XB5AG33 (ZB5AZ103 + ZB5AG3)	0.831/1.832

Heads only

	Key switch with key no. 455 (3) (4)	2-position 90°	Stay put		ZB5AG2	0.057/0.126	
					ZB5AG02	0.057/0.126	
					ZB5AG4	0.057/0.126	
				Spring return from right to left		ZB5AG6	0.061/0.134
		3-position ± 45°	Stay put		ZB5AG0	0.057/0.126	
					ZB5AG3	0.057/0.126	
					ZB5AG5	0.057/0.126	
					ZB5AG9	0.057/0.126	
					ZB5AG09	0.057/0.126	
			Spring return	from left to center		ZB5AG1	0.057/0.126
				to center		ZB5AG7	0.057/0.126
				from right to center		ZB5AG8	0.057/0.126
					ZB5AG05	0.057/0.126	
					ZB5AG08	0.057/0.126	

(1) For recommended maximum number of contacts and sequence of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

(2) The symbol indicates key withdrawal position(s).

(3) Other key numbers:

- Key no. 421E: add suffix **12** to the reference.
- Key no. 458A: add suffix **10** to the reference.
- Key no. 520E: add suffix **14** to the reference.
- Key no. 3131A: add suffix **20** to the reference.

For example, for a switch head with key no. 421E, 2-position stay put with key withdrawal from the left-hand position, the reference becomes ZB5AG212.

(4) For specific keys with other numbers, please contact our Customer Care Center.

Control and signaling units

Harmony XB5, plastic

Key switches with key 8D1

Selector switches with knurled knob, toggle switches

Key switches (continued) (1)

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Shape of head	Type of operator	Positions (2)		Reference	Weight kg/lb
		Number	Type		
	Key switch with key no. 8D1	2-position 90°	Stay put		ZB5AG2D 0.057/0.126
					ZB5AG02D 0.057/0.126
					ZB5AG4D 0.057/0.126
		Spring return from right to left			ZB5AG6D 0.061/0.134
		3-position ± 45°	Stay put		ZB5AG0D 0.057/0.126
					ZB5AG3D 0.057/0.126
					ZB5AG5D 0.057/0.126
					ZB5AG9D 0.057/0.126
					ZB5AG09D 0.057/0.126
					ZB5AG03D 0.057/0.126
					ZB5AG04D 0.057/0.126
			Spring return from left to center		ZB5AG06D 0.057/0.126
					ZB5AG1D 0.057/0.126
					ZB5AG07D 0.057/0.126
			Spring return from right to center		ZB5AG8D 0.057/0.126
					ZB5AG08D 0.057/0.126
					ZB5AG05D 0.057/0.126
			Spring return to center		ZB5AG7D 0.057/0.126

Selector switches with knurled knob (1)

Shape of head	Type of operator	Positions		Reference	Weight kg/lb	
		Number	Type			
Heads only						
	Black knurled knob	2-position 90°	Stay put		ZB5AD29	0.020/0.044
			Spring return from right to left		ZB5AD49	0.024/0.053
		3-position ± 45°	Stay put		ZB5AD39	0.020/0.044
			Spring return to center		ZB5AD59	0.020/0.044
			Spring return from left to center		ZB5AD79	0.020/0.044
			Spring return from right to center		ZB5AD89	0.020/0.044



ZB5AD39

Toggle switches (1)

Shape of head	Type of operator	Positions		Reference	Weight kg/lb
		Number	Type		
Heads only					
	Black lever	2-position 90°	Stay put		ZB5AD28 0.023/0.051
			Spring return		ZB5AD48 0.023/0.051
	White lever	2-position 90°	Stay put		ZB5AD2801 0.023/0.051
	Red lever	2-position 90°	Stay put		ZB5AD2804 0.023/0.051
	Blue lever	2-position 90°	Stay put		ZB5AD2806 0.023/0.051



ZB5AD28

(1) For recommended maximum number of contacts and sequence of contacts constituting the body (fixing collar and contact) associated with the head, see page 20.

(2) The symbol  indicates key withdrawal position(s).