



Pilot lights

With integral LED

Shape of head	Type of light source (included)	Color of lens	Sold in lots of	Unit reference by supply voltage (1)			Weight kg/lb
				24 V ~	120 V ~	230 V ~	
	Integral LED	Green	10	XB7EV03BP	XB7EV03GP	XB7EV03MP	0.020/0.044
		Red	10	XB7EV04BP	XB7EV04GP	XB7EV04MP	0.020/0.044
		Yellow	10	XB7EV05BP	XB7EV05GP	XB7EV05MP	0.020/0.044
		Blue	10	XB7EV06BP	XB7EV06GP	XB7EV06MP	0.020/0.044
		Clear	10	XB7EV07BP	XB7EV07GP	XB7EV07MP	0.020/0.044
		Orange	10	XB7EV08BP	XB7EV08GP	XB7EV08MP	0.020/0.044



With BA 9s base fitting

Shape of head	Supply	Color of lens	Sold in lots of	Unit reference (1)		Weight kg/lb
				With bulb	Without bulb	
	With resistor, for 130 V, 2.6 W bulb Supply voltage: 230 V ~, 50-60 Hz	Green	10	XB7EV73P	XB7EV730P	0.020/0.044
		Red	10	XB7EV74P	XB7EV740P	0.020/0.044
		Yellow	10	XB7EV75P	XB7EV750P	0.020/0.044
		Blue	10	XB7EV76P	XB7EV760P	0.020/0.044
		Clear	10	XB7EV77P	XB7EV770P	0.020/0.044
		Orange	10	XB7EV78P	XB7EV780P	0.020/0.044
	Direct for BA 9s base fitting incandescent bulb Supply voltage: ≤ 250 V (2)	Green	10	—	XB7EV63P	0.020/0.044
		Red	10	—	XB7EV64P	0.020/0.044
		Yellow	10	—	XB7EV65P	0.020/0.044
		Blue	10	—	XB7EV66P	0.020/0.044
		Clear	10	—	XB7EV67P	0.020/0.044
		Orange	10	—	XB7EV68P	0.020/0.044

Selector switches and key switches

Shape of head	Type of operator	Type of contact		Number and type of positions (3)	Sold in lots of	Unit reference	Weight kg/lb
		NO	NC				
	Standard handle, black						
		1	—	2, stay put	10	XB7ND21	0.026/0.057
		1	1	2, stay put	10	XB7ND25	0.026/0.057
	Key (key n° 455)						
		2	—	3, stay put	10	XB7ND33	0.026/0.057
		1	—	2, key withdrawal in LH position	10	XB7NG21	0.050/0.110
	Key (key n° 455)						
		2	—	3, key withdrawal in centre position	10	XB7NG33	0.050/0.110

(1) For Faston connection version (1 x 6.35 mm/0.04 x 0.24 in. and 2 x 2.8 mm/0.08 x 0.11 in.), add the number "3" to the end of the reference.

Example: XB7EV07BP becomes XB7EV07BP3.

(2) Bulb characteristics for direct supply pilot lights: 250 V, 2.6 W.

(3) The symbol "K" indicates key withdrawal position.

