Signaling units
Rotating beacons
Harmony XVR
Ø 84, Ø 106, Ø 120, and Ø 130
(equipped with Super Bright LED)

PF525874



XVR08J06

PF525875



XVR10J05



XVR12J04

PF525877



XVR13J05

PF540658



XVR13B05L



XVRZR1



XVRZ081



XVRZR2



XVRZ082



XVRZR3

Complete, pre-cabled rotating beacons

Diameter Ø mm/*in.*	Sound option	IP degree of protection	Voltage V	Color	Reference	Weight kg/*lb*
84/*3.31*	Without buzzer	IP 23 (IP 65 with accessories)	≂ 12	Red	**XVR08J04**	0.300/*0.661*
				Orange	**XVR08J05**	0.300/*0.661*
				Green	**XVR08J03**	0.300/*0.661*
				Blue	**XVR08J06**	0.300/*0.661*
			≂ 24	Red	**XVR08B04**	0.300/*0.661*
				Orange	**XVR08B05**	0.300/*0.661*
				Green	**XVR08B03**	0.300/*0.661*
				Blue	**XVR08B06**	0.300/*0.661*
106/*4.17*	Without buzzer	IP 23 (IP 55 with accessories)	≂ 12	Red	**XVR10J04**	0.500/*1.102*
				Orange	**XVR10J05**	0.500/*1.102*
				Green	**XVR10J03**	0.500/*1.102*
				Blue	**XVR10J06**	0.500/*1.102*
			≂ 24	Red	**XVR10B04**	0.500/*1.102*
				Orange	**XVR10B05**	0.500/*1.102*
				Green	**XVR10B03**	0.500/*1.102*
				Blue	**XVR10B06**	0.500/*1.102*
120/*4.72*	Without buzzer	IP 23	≂ 12	Red	**XVR12J04**	0.500/*1.102*
				Orange	**XVR12J05**	0.500/*1.102*
				Green	**XVR12J03**	0.500/*1.102*
				Blue	**XVR12J06**	0.500/*1.102*
			≂ 24	Red	**XVR12B04**	0.500/*1.102*
				Orange	**XVR12B05**	0.500/*1.102*
				Green	**XVR12B03**	0.500/*1.102*
				Blue	**XVR12B06**	0.500/*1.102*
120/*4.72*	With buzzer, continuous or intermittent tone. Sound level at 1 m/*3.28 ft:* 50 to 90 dB	IP 23	≂ 12	Red	**XVR12J04S**	0.500/*1.102*
				Orange	**XVR12J05S**	0.500/*1.102*
				Green	**XVR12J03S**	0.500/*1.102*
				Blue	**XVR12J06S**	0.500/*1.102*
			≂ 24	Red	**XVR12B04S**	0.500/*1.102*
				Orange	**XVR12B05S**	0.500/*1.102*
				Green	**XVR12B03S**	0.500/*1.102*
				Blue	**XVR12B06S**	0.500/*1.102*
130/*5.12*	Without buzzer	IP 66 vibration resistance	⎓ 12	Red	**XVR13J04**	0.800/*1.764*
				Orange	**XVR13J05**	0.800/*1.764*
			⎓ 24	Red	**XVR13B04**	0.800/*1.764*
				Orange	**XVR13B05**	0.800/*1.764*
		IP 66 and IP 67	≂ 24	Red	**XVR13B04L**	0.820/*1808*
				Orange	**XVR13B05L**	0.820/*1808*
			∼ 120	Red	**XVR13G04L**	0.990/*2183*
				Orange	**XVR13G05L**	0.990/*2183*
			∼ 230	Red	**XVR13M04L**	0.990/*2183*
				Orange	**XVR13M05L**	0.990/*2183*

Accessories for rotating beacons

Description	To be used for/with	Diameter mm/*in.*	Height mm/*in.*	Reference	Weight kg/*lb*
Reflecting prism	Increasing light diffusion	84/*3.31*	–	**XVRZR1**	0.010/*0.022*
		106/*4.17*	–	**XVRZR2**	0.015/*0.033*
		120/*4.72*, 130/*5.12*	–	**XVRZR3**	0.020/*0.044*
Rubber base	IP 65 protection	84/*3.31*	–	**XVRZ081**	0.040/*0.088*
	IP 55 protection	106/*4.17*	–	**XVRZ082**	0.050/*0.110*
Metal angle bracket	Horizontal support	84/*3.31*, 100/*3.94*, 106/*4.17*, 120/*4.72*	–	**XVCZ23**	0.380/*0.084*
		130/*5.12*	–	**XVR012L**	1.300/*2.866*
Metal fixing plate	Horizontal support	106/*4.17*, 120/*4.72*	300/ *11.8*	**XVCZ13**	0.700/*1.543*

Signaling units
Rotating beacons
Harmony XVR
Ø 100
(multi-functional LED beacon)

PF141507A



XVR3B03

PF141505A



XVR3B04S

PF141506A



XVR3E06

PF141509A



XVR3Z001

Complete, pre-cabled motor-less rotating/flashing beacons

Diameter Ø mm/*in.*	Sound option	IP degree of protection	Voltage V	Color	Reference	Weight kg/*lb*
100/***3.94***	Without buzzer	IP 65 (upright) IP 23 (sideways, inverted)	⎓ 12-24	Green	**XVR3B03**	0.484/*1.067*
				Red	**XVR3B04**	0.484/*1.067*
				Orange	**XVR3B05**	0.484/*1.067*
				Blue	**XVR3B06**	0.484/*1.067*
			∿ 100-230	Green	**XVR3M03**	0.484/*1.067*
				Red	**XVR3M04**	0.484/*1.067*
				Orange	**XVR3M05**	0.484/*1.067*
				Blue	**XVR3M06**	0.484/*1.067*
100/***3.94***	With buzzer	IP 23 (upright, sideways, inverted)	⎓ 12-24	Green	**XVR3B03S**	0.538/*1.186*
				Red	**XVR3B04S**	0.538/*1.186*
				Orange	**XVR3B05S**	0.538/*1.186*
				Blue	**XVR3B06S**	0.538/*1.186*
			∿ 100-230	Green	**XVR3M03S**	0.538/*1.186*
				Red	**XVR3M04S**	0.538/*1.186*
				Orange	**XVR3M05S**	0.538/*1.186*
				Blue	**XVR3M06S**	0.538/*1.186*
100/***3.94***	Without buzzer	IP 65 (upright) IP 23 (sideways, inverted)	⎓ 48	Red	**XVR3E03**	0.484/*1.067*
				Orange	**XVR3E04**	0.484/*1.067*
				Green	**XVR3E05**	0.484/*1.067*
				Blue	**XVR3E06**	0.484/*1.067*

Accessories for motor-less rotating beacons

Description	To be used for/with	Reference	Weight kg/*lb*
External lens	Multi-functional LED beacon	**XVR3Z001**	0.083/*0.183*