

I/O System – 750 and 753 Series, Digital Input Modules

Contents

Function	2-Channel DI	4-Channel DI	8-Channel DI	16-Channel DI	8-Channel DIO	Description	Item Number			Page
							Standard	Extended Temperature	Pluggable	
5 VDC		■				4-Channel Digital Input; 5 VDC; 0.2 ms	750-414			164
5/12 VDC			■			8-Channel Digital Input; 5/12 VDC; 0.2 ms			753-434	164
24 VDC	■					2-Channel Digital Input; 24 VDC; 3 ms	750-400	750-400/025-000	753-400	165
	■					2-Channel Digital Input; 24 VDC; 3 ms; Acknowledgement; Diagnostics	750-418		753-418	165
	■					2-Channel Digital Input; 24 VDC; 3 ms; Diagnostics	750-421		753-421	166
		■				4-Channel Digital Input; 24 VDC; 3 ms	750-402	750-402/025-000	753-402	166
		■				4-Channel Digital Input; 24 VDC; 3 ms; 2-wire connection	750-432		753-432	167
		■				4-Channel Digital Input; 24 VDC; 3 ms; 3-wire connection	750-1420			167
			■			8-Channel Digital Input; 24 VDC; 3 ms	750-430*	750-430/025-000	753-430	168
			■			8-Channel Digital Input; 24 VDC; 3 ms; 2-wire connection	750-1415*			168
				■		16-Channel Digital Input; 24 VDC; 3 ms; Ribbon cable	750-1400			169
				■		16-Channel Digital Input; 24 VDC; 3 ms	750-1405*			169
					■	8-Channel Digital Input/Output; 24 VDC; 0.5 A; Ribbon cable	750-1502			170
					■	8-Channel Digital Input/Output; 24 VDC; 0.5 A	750-1506			170
	3 ms; High-side switching	■				2-Channel Digital Input; 24 VDC; 0.2 ms	750-401		753-401	171
		■				4-Channel Digital Input; 24 VDC; 0.2 ms	750-403		753-403	171
		■				4-Channel Digital Input; 24 VDC; 0.2 ms; 2-wire connection	750-433		753-433	172
		■				4-Channel Digital Input; 24 VDC; 0.2 ms; 3-wire connection	750-1421			172
			■			8-Channel Digital Input; 24 VDC; 0.2 ms	750-431*		753-431	173
			■			8-Channel Digital Input; 24 VDC; 0.2 ms; 2-wire connection	750-1416*			173
	0.2 ms; High-side switching			■		16-Channel Digital Input; 24 VDC; 0.2 ms	750-1406			173
		■				4-Channel Digital Input; 24 VDC; 3 ms; Low-side switching	750-408	750-408/025-000	753-408	174
		■				4-Channel Digital Input; 24 VDC; 3 ms; Low-side switching; 3-wire connection	750-1422			174
			■			8-Channel Digital Input; 24 VDC; 3 ms; Low-side switching	750-436		753-436	175
			■			8-Channel Digital Input; 24 VDC; 3 ms; Low-side switching; 2-wire connection	750-1417			175
				■		16-Channel Digital Input; 24 VDC; 3 ms; Low-side switching; Ribbon cable	750-1402			176
	3 ms; Low-side switching			■		16-Channel Digital Input; 24 VDC; 3 ms; Low-side switching	750-1407			176
		■				4-Channel Digital Input; 24 VDC; 0.2 ms; Low-side switching	750-409		753-409	177
		■				4-Channel Digital Input; 24 VDC; 0.2 ms; Low-side switching; 3-wire connection	750-1423			177
			■			8-Channel Digital Input; 24 VDC; 0.2 ms; Low-side switching	750-437		753-437	178
			■			8-Channel Digital Input; 24 VDC; 0.2 ms; Low-side switching; 2-wire connection	750-1418			178
		■				2-Channel Digital Input; 24 VDC; 3 ms; Proximity sensor	750-410		753-410	179
24 VAC/DC	■					2-Channel Digital Input; 24 VDC; 0.2 ms; Proximity sensor	750-411		753-411	179
	■					2-Channel Digital Input; NAMUR	750-425		753-425	180
	■					2-Channel Digital Input; Intruder detection	750-424		753-424	181
	■					4-Channel Digital Input; 24 VDC; Pulse extension	750-422		753-422	182
	■					4-Channel Digital Input; 24 VAC/DC; 20 ms	750-415		753-415	183
	■					4-Channel Digital Input; 24 VAC/DC; 50 ms	750-423		753-423	183
42 VAC/VDC	■					4-Channel Digital Input; 24 VAC/DC; 20 ms	750-428		753-428	184
48 VDC	■					2-Channel Digital Input; 48 VDC; 3 ms	750-412		753-412	185
60 VDC	■					2-Channel Digital Input; 60 VDC; 3 ms	*		753-429	186
110 VDC	■					2-Channel Digital Input; 110 VDC; High-side/low-side switching	750-427*		753-427	187
220 VDC	■					2-Channel Digital Input; 220 VDC	750-407*			187
120 VAC	■					2-Channel Digital Input; 120 VAC	750-406		753-406	188
120/230 VAC	■					4-Channel Digital Input; 120/230 VAC			753-440	189
230 VAC	■					2-Channel Digital Input; 230 VAC	750-405		753-405	188
PTC			■			8-Channel Digital Input; PTC	750-1425			189
Functional Safety							See Section 5.8			
Ex i							See Section 5.9			
*This module is also available as a 750 XTR Series variant.							See Section 6			