

I/O-System – 750 and 753 Series; Analog Input Modules

Contents

Function	1-Channel AI	2-Channel AI	4-Channel AI	8-Channel AI	Description	Item Number				Page
						Standard	/S5 or /S7 Customized Data Format	Extended Temperature	Pluggable	
0 ... 20 mA		■			2-Channel Analog Input; 0 ... 20 mA; Differential Input	750-452	750-452/000-200		753-452	214
		■			2-Channel Analog Input; 0 ... 20 mA; Differential Input	750-480			753-480	214
		■			2-Channel Analog Input; 0 ... 20 mA; Single-ended	750-465		750-465/025-000	753-465	215
		■			2-Channel Analog Input; 0 ... 20 mA; Single-ended 2-Channel Analog Input; 0 ... 20 mA; Single-ended; 60 Hz	750-470 750-470/005-000				215
		■			2-Channel Analog Input; 0 ... 20 mA; Single-ended; 16 bits 2-Channel Analog Input; 0 ... 20 mA; Single-ended; 16 bits; 60 Hz	750-472 750-472/005-000			753-472	216
			■		4-Channel Analog Input; 0 ... 20 mA; Single-ended	750-453*			753-453	216
4 ... 20 mA		■			2-Channel Analog Input; 4 ... 20 mA; Differential input 2-Channel Analog Input; 4 ... 20 mA; Differential input; Extended measurement range	750-454 750-454/000-003	750-454/000-200	750-454/025-000 750-454/025-003	753-454	217
		■			2-Channel Analog Input; 4 ... 20 mA; Differential input	750-492*			753-492	218
		■			2-Channel Analog Input; 4 ... 20 mA; Single-ended	750-466	750-466/000-200	750-466/025-000	753-466	219
		■			2-Channel Analog Input; 4 ... 20 mA; Single-ended 2-Channel Analog Input; 4 ... 20 mA; Single-ended; 60 Hz	750-473 750-473/005-000				220
		■			2-Channel Analog Input; 4 ... 20 mA; Single-ended; 16 bits 2-Channel Analog Input; 4 ... 20 mA; Single-ended; 16 bits; 60 Hz	750-474 750-474/005-000	750-474/000-200		753-474	221
		■			2-Channel Analog Input; 4 ... 20 mA HART	750-482 750-482/000-001	750-482/000-300	750-482/025-000	753-482	222
			■		4-Channel Analog Input; 4 ... 20 mA; Single-ended	750-455*		750-455/025-000	753-455	223
			■		4-Channel Analog Input; 4 ... 20 mA; Single-ended; 4 x 24 V	750-455/020-000				223
0/4 ... 20 mA			■		8-Channel Analog Input; 0/4 ... 20 mA; Single-ended	750-496				224
0 ... 1 A		■			2-Channel Analog Input; 0 ... 1 VAC/DC; Differential input	750-475			753-475	225
0 ... 5 A		■			2-Channel Analog Input; 0 ... 5 VAC/DC; Differential input	750-475/020-000				225
±10 V		■			2-Channel Analog Input; ±10 VDC; Differential input	750-456	750-456/000-200		753-456	226
		■			2-Channel Analog Input; ±10 VDC; Differential input 2-Channel Analog Input; ±10 VDC; Differential input; Synchronous	750-479 750-479/000-001			753-479	226
		■			2-Channel Analog Input; ±10 VDC; Single-ended; 16 bits	750-476	750-476/000-200		753-476	227
			■		4-Channel Analog Input; ±10 VDC; Single-ended	750-457*		750-457/025-000	753-457	227
0 ... 10 V		■			2-Channel Analog Input; 0 ... 10 VDC; Single-ended	750-467			753-467	228
		■			2-Channel Analog Input; 0 ... 10 VDC; Single-ended; 16 bits 2-Channel Analog Input; 0 ... 10 VDC; Single-ended; 16 bits; 60 Hz	750-478 750-478/005-000			753-478	228
			■		4-Channel Analog Input; 0 ... 10 VDC; Single-ended	750-468*		750-468/025-000		229
			■		4-Channel Analog Input; 0 ... 10 VDC; Single-ended	750-459			753-459	229
0 ... 10 V/±10 V			■		8-Channel Analog Input; 0 ... 10 VDC/±10 V; Single-ended	750-497				230
0 ... 10 VAC/DC		■			2-Channel Analog Input; 0 ... 10 VAC/DC; Differential input	750-477			753-477	231
0 ... 30 V		■			2-Channel Analog Input; 0 ... 30 VDC; Differential input	750-483*			753-483	231
Voltage/Current			■		4-Channel Analog Input; for voltage/current	750-471				232
Resistance Sensors		■			2-Channel Analog Input; for Pt100/RTD resistance sensors	750-461	750-461/000-200	750-461/025-000	753-461	234
		■			2-Channel Analog Input; for Pt100/RTD resistance sensors; Adjustable	750-461/003-000			753-461/003-000	234
		■			2-Channel Analog Input; for NTC 20k resistance sensors	750-461/020-000				235
		■	■		2/4-Channel Analog Input; Resistance measurement; Adjustable	750-464*				236
			■		4-Channel Analog Input; for NTC resistance sensors; Adjustable	750-464/020-000				236
			■		4-Channel Analog Input; Resistance measurement; Measurement range: -30 °C ... +150 °C	750-463				237
			■		4-Channel Analog Input; Resistance measurement; Adjustable	750-450				237
			■		8-Channel Analog Input; Resistance measurement; Adjustable	750-451		750-451/025-000		237
Thermocouples		■			2-Channel Analog Input; Thermocouple K; Diagnostics	750-469	750-469/000-200		753-469	238
		■			2-Channel Analog Input; Thermocouple K; Diagnostics; Adjustable	750-469/003-000*			753-469/003-000	238
		■			2-Channel Analog Input; Thermocouple J; Diagnostics	750-469/000-006				239
			■		8-Channel Analog Input; Thermocouple; Adjustable	750-458				239
Analog Specialty Functions	■				1-Channel Analog Input; Resistor bridges (strain gauge) 1-Channel Analog Input; Resistor bridges (strain gauge); 125 ms conversion time	750-491 750-491/000-001				240
		■			3-Phase Power Measurement; 480 VAC 1 A 3-Phase Power Measurement; 480 VAC 5 A	750-493 750-493/000-001		750-493/025-000		241
		■			3-Phase Power Measurement; 480 VAC 1 A 3-Phase Power Measurement; 480 VAC 5 A	750-494 750-494/000-001		750-494/025-000 750-494/025-001		242
		■			Power Measurement; 277 VAC/DC; External shunts	750-494/000-005				243
		■			3-Phase Power Measurement; 690 VAC 1 A 3-Phase Power Measurement; 690 VAC 5 A 3-Phase Power Measurement; 690 VAC Rogowski coils	750-495* 750-495/000-001* 750-495/000-002*				244
Ex i						See Section 5.9				
*This module is also available as a 750 XTR Series variant.						See Section 6				