

ONE-WAY

					ADAPTO Series	
					610.	
						
					Configuration adaptors from 3P+N+E to 3P+E	
					ONE-WAY ADAPTOR	
					IP44	
Supply	Current	Poles	Volt	Sockets	610.3746	
Plug IEC309 16A	16A	3P+N+E	400V	16A 3P+N+E 1	10	

- Used to supply 16A loads with 3P+E plugs from 16A 3P+N+E power supply sockets.

- The adaptor's 16A 3P+N+E plug is first plugged into the 16A 3P+N+E power supply socket and then the 16A 3P+E plug of the load to be supplied is plugged into the adaptor's 16A 3P+E socket.

- For temporary use only

2-WAY

					ADAPTO Series	
					600.	601.
						
					With appliance inlet	
					MULTI -WAY ADAPTOR	
					IP44	
					IP66	
Supply	Current	Poles	Volt	Sockets		
Appliance inlet IEC309 16A	16A	2P+E	230V	16A	600.1623	1/6
				16A 230V	600.1624	1/6
		3P+E	400V	16A	600.1626	1/6
				16A 230V	600.1626/I ¹	1/6
		3P+N+E	400V	16A	600.1629	1/6
				16A 230V	600.1627	1/6
		3P+N+E	400V	16A	601.1623	1/6
				16A 230V	601.1626	1/6

¹ One socket with reversed phases.

- 2-way adaptors

- Casing provided with lug for hanging from above (16A).



Industrial adaptors

ADAPTO Series

2-WAY

ADAPTO Series

604.

605.



Sockets

16A

32A

With cable and plug

MULTI-WAY ADAPTOR

Supply	Current	Poles	Volt	Sockets					Cable section	MULTI-WAY ADAPTOR	
				2P+E	3P+E	3P+N+E	3P+E	3P+N+E		IP44	IP66
Plug IEC309 16A	16A	2P+E	230V	2					3x2,5mm ²	604.1623/C 1/6	605.1623/C 1/6
Plug IEC309 16A		3P+E			2				4x4mm ²	604.1626/C 1/6 604.1626/I-C ^[1] 1/6	605.1626/C 1/6
Plug IEC309 16A		3P+N+E	400V	1	1				5x2,5mm ²	604.1629/C 1/6 604.1627/C 1/6	605.1629/C 1/6 605.1627/C 1/6
Plug IEC309 32A	32A	3P+E					2		4x4mm ²	604.3226/C ^[2] 1/6	605.3226/C ^[2] 1/6
Plug IEC309 32A		3P+N+E						2	5x4mm ²	604.3227/C ^[2] 1/6	605.3227/C ^[2] 1/6

[1] One socket with reversed phases.

[2] Zinc-plated steel carrying handle (32A).

- 2m rubber cable H07RN-F

- Equipped with PG21 cable gland, cable clamp and terminal block.

3-WAY

ADAPTO Series

606.



Sockets

16A 110V

16A

With appliance inlet

Supply	Current	Poles	Volt	Sockets			MULTI-WAY ADAPTOR	
				2P+E	3P+E		IP44	IP66/IP67
Appliance inlet IEC309 16A	16A	2P+E	230V		3		606.3005-062 1/6	606.3505-062 1/6
		3P+E				3	606.3005-063 1/6	606.3505-063 1/6
		3P+N+E	400V		2	1	606.3005-059 1/6	606.3505-059 1/6
Appliance inlet IEC309 16A 110V		2P+E	110V	3			606.3005-479 1/6	606.3505-479 1/6



2P+E 16A 110V



2P+E 16A



3P+E 16A



3P+N+E 16A



3P+E 32A



3P+N+E 32A

■ 3-WAY

ADAPTO Series											
606.											
											
With cable and plug											
MULTI -WAY ADAPTOR											
Sockets											
16A 110V 16A											
Supply	Current	Poles	Volt	2P+E		3P+E		Cable section	MULTI -WAY ADAPTOR		
							IP44		IP66/IP67		
Plug IEC309 16A				2P+E	110V		3			3x2,5mm ²	606.3015-062
Plug IEC309 16A	16A	3P+E	230V		3			606.3015-062	1/6	606.3515-062	1/6
Plug IEC309 16A		3P+N+E	400V			3	4x2,5mm ²	606.3015-063	1/6	606.3515-063	1/6
Plug IEC309 16A					2	1	5x2,5mm ²	606.3015-059	1/6	606.3515-059	1/6
Plug IEC309 16A 110V					3			606.3015-740	6		
Plug IEC309 16A 110V		2P+E	110V	3			3x2,5mm ²	606.3015-479	1/6		
- 2m rubber cable H07RN-F - Equipped with PG21 cable gland, cable clamp and terminal block.											

- 2m rubber cable H07RN-F
- Equipped with PG21 cable gland, cable clamp and terminal block.

■ 3-WAY and 5-WAY

ADAPTO Series													
603.													
													
Without cable and plug (x3)													
MULTI -WAY ADAPTOR													
Sockets													
16A													
Supply	Current	Poles	Volt	2P+E			3P+E			3P+N+E			
													
				Cable section									
Terminal block 16mm ²	16A	2P+E	230V	3									
Terminal block 16mm ²	16A	3P+E	400V		3								
Terminal block 16mm ²	16A	3P+N+E	400V	2	1								
Terminal block 16mm ²	16A	3P+N+E	400V	2		1							
Terminal block 16mm ²	16A	3P+N+E	400V			3							
							MULTI -WAY ADAPTOR						
							IP44			IP66			
							603.3005-062			1/10	603.3505-062		1/10
							603.3005-063			1/10	603.3505-063		1/10
							603.3005-059			1/10	603.3505-059		1/10
							603.3005-061			1/10	603.3505-061		1/10
							603.3005-064			1/10	603.3505-064		1/10

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.



3-WAY and 5-WAY

ADAPTO Series

603.



Sockets

16A

32A

Without cable and plug
(x5)

Supply	Current	Poles	Volt	Sockets						MULTI -WAY ADAPTOR	
				2P+E	3P+E	3P+N+E	3P+E	3P+N+E	3P+N+E	IP44	
Terminal block 16mm ²	16A	2P+E	230V	2	3					603.5005-358	1/10
Terminal block 16mm ²	16A	3P+N+E	400V	1	1		3			603.5005-359	1/10
Terminal block 16mm ²	16A	3P+N+E	400V	2		1		1	1	603.5005-427	1/10
Terminal block 16mm ²	16A	3P+N+E	400V	2		2	2			603.5005-415	1/10
Terminal block 16mm ²	16A	3P+N+E	400V	2				3		603.5005-360	1/10

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.

ADAPTO Series

602.



Sockets

16A

32A

With cable and plug (x3)

Supply	Current	Poles	Volt	2P+E		3P+E	3P+N+E		Cable section	MULTI -WAY ADAPTOR			
										IP44		IP66	
Plug IEC309 16A	16A	2P+E	230V	3					3x2,5mm²	602.3005-062	1/6	602.3505-062	1/6
Plug IEC309 16A	16A	3P+E	400V		3				4x2,5mm²	602.3005-063	1/6	602.3505-063	1/6
Plug IEC309 16A	16A	3P+N+E	400V	2	1				5x2,5mm²	602.3005-059	1/6	602.3505-059	1/6
Plug IEC309 16A	16A	3P+N+E	400V	2		1			5x2,5mm²	602.3005-061	1/6	602.3505-061	1/6
Plug IEC309 16A	16A	3P+N+E	400V			3			5x2,5mm²	602.3005-064	1/6	602.3505-064	1/6
Plug IEC309 32A	32A	3P+E	400V				3		4x4mm²			602.3505-443	1/6
Plug IEC309 32A	32A	3P+N+E	400V					3	5x4mm²	602.3005-215	1/6		

- Zinc-plated steel carrying handle.
- 2m rubber cable H07RN-F
- Equipped with PG21 cable gland, cable clamp and terminal block.



ITALIAN STANDARD
P30 2P+E 16A
Shuttered socket CEI 23-50



ITALIAN STANDARD
P17/11 2P+E 16A
Shuttered socket CEI 23-50



2P+E 16A



3P+E 16A



3P+N+E 16A



3P+E 32A



3P+N+E 32A

3-WAY and 5-WAY

ADAPTO Series

602.



Sockets

16A

With cable and plug (x5)

Supply	Current	Poles	Volt	Sockets					Cable section	MULTI -WAY ADAPTOR	
				2P+E	3P+E	3P+N+E				IP44	
Plug IEC309 16A	16A	2P+E	230V	2	3				3x2,5mm ²	602.5005-358	1/6
Plug IEC309 16A	16A	3P+N+E	400V	1	1	3			5x2,5mm ²	602.5005-359	1/6
Plug IEC309 16A	16A	3P+N+E	400V	2			3		5x2,5mm ²	602.5005-360	1/6

- Zinc-plated steel carrying handle.
- 2m rubber cable H07RN-F
- Equipped with PG21 cable gland, cable clamp and terminal block.

3-WAY with protection devices >> Protection device: MCB

ADAPTO Series

623.



Sockets

Without cable and plug

no.	Sockets			General	Max power	MULTI -WAY ADAPTOR	
	2P+E	3P+E				IP44	IP66
3	1	2		MCB 2P 16A	3 KW	623.3000-056	1
3		3		MCB 2P 16A	3 KW	623.3000-062	1
3			3	MCB 3P 16A	9 KW	623.3000-063	1

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.

2.2



■ 3-WAY with protection devices >> Protection device: MCB

ADAPTO Series

625.



Sockets

Elevated installation

		16A		General	Max power	MULTI -WAY ADAPTOR	
		2P+E	3P+E			IP66	
no.						Supply by terminal block	
3	1		2	MCB 4P 16A	9 KW	625.3500-060	1
3	2	1		MCB 4P 16A	9 KW	625.3500-059	1
3	3			MCB 2P 16A	3 KW	625.3500-062	1
3			3	MCB 3P 16A	9 KW	625.3500-063	1

- Tubular stand to be ordered separately
- Equipped with PG21 cable gland, cable clamp and terminal block.

■ 3-WAY with protection devices >> Protection devices: MCB+RCD

ADAPTO Series

623.



Sockets

Without cable and plug

		16A		General	Max power	MULTI -WAY ADAPTOR	
		2P+E	3P+E			IP44	
no.						Direct supply to main switch	
3	1	2		MCB 2P 16A RCD 2P 25A 0,03A	3 KW	623.3006-054	1
3		3		MCB 2P 16A RCD 2P 25A 0,03A	3 KW	623.3006-062	1
3			3	RCBO 4P 16A 0,03A	9 KW	623.3006-063	1

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.



ITALIAN STANDARD
P17/11 2P+E 16A
Shuttered socket CEI 23-50



2P+E 16A



3P+E 16A



ITALIAN STANDARD
P30 2P+E 16A
Shuttered socket CEI 23-50



3P+N+E 16A

	625.
--	------



Elevated installation

					MULTI -WAY ADAPTOR	
					IP66	
					Supply by terminal block	
no.			General	Max power		
3	1	2	RCBO 4P 16A 0,03A	9 KW	625.3506-060	1
3	2	1	RCBO 4P 16A 0,03A	9 KW	625.3506-059	1
3	3		MCB 2P 16A RCD 2P 25A 0,03A	3 KW	625.3506-062	1

- Tubular stand to be ordered separately
- Equipped with PG21 cable gland, cable clamp and terminal block.

	ADAPTO Series
	623.



Without cable and plug

Current	Poles	Volt	16A					MULTI-WAY ADAPTOR		
			2P+E		3P+E	3P+N+E	IP44		IP66	
								Terminal block 16mm²		
16A	2P+E	230V	2	2				623.4005-010	1	
16A	2P+E	230V			4			623.4005-012	1	623.4505-012 1
16A	3P+N+E	400V			2	2		623.4005-003	1	623.4505-003 1
16A	3P+N+E	400V			2		2	623.4005-006	1	623.4505-006 1

- Zinc-plated steel carrying handle.
- Equipped with PG21 cable gland, cable clamp and terminal block.

Industrial adaptors
ADAPTO Series

4-WAY

ADAPTO Series
625.



Sockets

Elevated installation

Current	Poles	Volt	16A		MULTI-WAY ADAPTOR	
			2P+E	3P+E	IP66	
					Terminal block 16mm ²	
16A	2P+E	230V	4		625.4505-012	1
16A	3P+N+E	400V	2	2	625.4505-003	1

- Tubular stand to be ordered separately
- Equipped with PG21 cable gland, cable clamp and terminal block.



Elevated installation
Handle and cable gland not supplied for elevated-installation versions. The cable inlet is from below, where the adaptor is fastened to the stand.



2P+E 16A



3P+E 16A

Accessories

ENCLOSURES ACCESSORIES

	654.	692.	
			
Description	Mounting bracket for compressed air	Tubular stand	Adaptors coupling kit
PLATE FOR COMP. AIR MOSE	654.005010		
TUBULAR STAND		692.43401	
ADAPTOR COUPLING KIT			692.4342121/5

- 1 3-way and 4-way adaptors can be coupled together as shown in the drawing
- 2 The kit includes all the screws, nuts, washers and seals required to couple together 3-way and 4-way adaptors.

2.2

