

ISOLATORS-EX Series



ALUMINIUM SWITCHES DISCONNECTORS - IP65



Current	Poles	Cable inlets	Dimensions (mm)		GENERAL USE	EMERGENCY CONTROL
20A	2	2xM25 + 1xM20 (high)	105x150x82	1/12	590.XHGE2002	590.XHEM2002
	3		105x150x82	1/12	590.XHGE2003	590.XHEM2003
	4		105x150x82	1/12	590.XHGE2004	590.XHEM2004
32A	2	2xM25 + 1xM20 (high)	105x150x82	1/12	590.XHGE3202	590.XHEM3202
	3		105x150x82	1/12	590.XHGE3203	590.XHEM3203
	4		105x150x82	1/12	590.XHGE3204	590.XHEM3204
40A	2	2xM25 1xM20 (high)	105x150x82	1/12	590.XHGE4002	590.XHEM4002
	3		105x150x82	1/12	590.XHGE4003	590.XHEM4003
	4		105x150x82	1/12	590.XHGE4004	590.XHEM4004
63A	2	2xM32 + 1xM20 (high)	150x210x107	1/5	590.XHGE6302	590.XHEM6302
	3		150x210x107	1/5	590.XHGE6303	590.XHEM6303
	4		150x210x107	1/5	590.XHGE6304	590.XHEM6304

- 1xM20 (top): on request

Package/Bulk Pack.

THERMOPLASTIC SWITCHES DISCONNECTORS - IP66



Current	Poles	Cable inlets	Dimensions (mm)		GENERAL USE	EMERGENCY CONTROL
20A	2	2xM25 + 1xM20	115x190x128	1/12	590.XGE2002	590.XEM2002
	3		115x190x128	1/12	590.XGE2003	590.XEM2003
	4		115x190x128	1/12	590.XGE2004	590.XEM2004
32A	2	2xM32 + 1xM20	115x190x128	1/12	590.XGE3202	590.XEM3202
	3		115x190x128	1/12	590.XGE3203	590.XEM3203
	4		115x190x128	1/12	590.XGE3204	590.XEM3204
40A	2	2xM32 + 1xM20	115x190x128	1/12	590.XGE4002	590.XEM4002
	3		115x190x128	1/12	590.XGE4003	590.XEM4003
	4		115x190x128	1/12	590.XGE4004	590.XEM4004

Package/Bulk Pack.

- Auxiliary contacts:

NC 16A-32A: 590.PL004001

NC 63A: 590.PL004003

NO 16A-32A: 590.PL004002

NO 63A: 590.PL004004

See table page 115.

Padlockable handle in two positions (ON/OFF).
OFF position = 3 padlocks
ON position = 1 padlock