

Switched interlocked sockets outlets

ADVANCE2 Series

■ Rated operating voltage >50V >> Standard version

ADVANCE 2 Series

560.



Without fuse carrier IP44

INTERLOCKED SOCKET

IP44

106x240mm

M25X1,5

Poles	Hz	Volt	Colour	h	16A		32A	
2P+E	50Hz 60Hz	100-130V		4h	560.1670	1/12	560.3270	1/12
		200-250V		6h	560.1683	1/12	560.3283	1/12
		380-415V		9h	560.1678	1/12	560.3278	1/12
		480-500V		7h	560.16836	1/12	560.32836	1/12
		TST>50V		12h	560.16833	1/12	560.32833	1/12
	>300-500Hz	>50V		2h	560.16832 ^[1]	1/12	560.32832 ^[1]	1/12
	DC	>50-250V		3h	560.16834 ^[2]	1/12	560.32834 ^[2]	1/12
		>250V		8h	560.16838 ^[2]	1/12	560.32838 ^[2]	1/12
	3P+E	100-130V		4h	560.1672	1/12	560.3272	1/12
		200-250V		9h	560.1674	1/12	560.3274	1/12
		380-415V		6h	560.1686	1/12	560.3286	1/12
		380V 50Hz / 440V 60Hz		3h	560.16864	1/12	560.32864	1/12
		480-500V		7h	560.16866	1/12	560.32866	1/12
		600-690V		5h	560.16867 ^[3]	1/12	560.32867 ^[3]	1/12
		440-460V		11h	560.16865	1/12	560.32865	1/12
3P+N+E	100-300Hz	>50V		10h	560.16861 ^[1]	1/12	560.32861 ^[1]	1/12
	>300-500Hz	>50V		2h	560.16862 ^[1]	1/12	560.32862 ^[1]	1/12
	50Hz 60Hz	100-130V		4h	560.1679	1/12	560.3279	1/12
		208-250V		9h	560.1675	1/12	560.3275	1/12
		346-415V		6h	560.1687	1/12	560.3287	1/12
		380V 50Hz / 440V 60Hz		3h	560.16874	1/12	560.32874	1/12
		480-500V		7h	560.16876	1/12	560.32876	1/12
		600-690V		5h	560.16877 ^[3]	1/12	560.32877 ^[3]	1/12
		440-460V		11h	560.16875	1/12	560.32875	1/12
	>300-500Hz	>50V		2h	560.16872 ^[1]	1/12	560.32872 ^[1]	1/12

[1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.

[2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

[3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

- Supplied with stainless steel fixing screws.
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included

Rated operating voltage >50V >> Standard version

ADVANCE 2 Series

561.



Without fuse carrier
IP66/IP67

					INTERLOCKED SOCKET					
					IP66/IP67					
					106x240mm			136x390mm		
					M25X1,5			M40X1,5		
Poles	Hz	Volt	Colour	h	16A		32A		63A	
2P+E	50Hz 60Hz	100-130V		4h	561.1670	1/12	561.3270	1/12	561.6370 ^[4]	1/4
		200-250V		6h	561.1683	1/12	561.3283	1/12	561.6383 ^[4]	1/4
		380-415V		9h	561.1678	1/12	561.3278	1/12	561.6378 ^[4]	1/4
		480-500V		7h	561.16836	1/12	561.32836	1/12	561.63836 ^[4]	1/4
		TST>50V		12h	561.16833	1/12	561.32833	1/12	561.63833 ^[4]	1/4
	DC	>50V		2h	561.16832 ^[1]	1/12	561.32832 ^[1]	1/12		
		>50-250V		3h	561.16834 ^[2]	1/12	561.32834 ^[2]	1/12	561.63834 ^{[2][4]}	1/4
		>250V		8h	561.16838 ^[2]	1/12	561.32838 ^[2]	1/12	561.63838 ^{[2][4]}	1/4
3P+E	50Hz 60Hz	100-130V		4h	561.1672	1/12	561.3272	1/12	561.6372 ^[4]	1/4
		200-250V		9h	561.1674	1/12	561.3274	1/12	561.6374 ^[4]	1/4
		380-415V		6h	561.1686	1/12	561.3286	1/12	561.6386 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	561.16864	1/12	561.32864	1/12		
		480-500V		7h	561.16866	1/12	561.32866	1/12	561.63866 ^[4]	1/4
	60Hz	600-690V		5h	561.16867 ^[3]	1/12	561.32867 ^[3]	1/12	561.63867 ^{[3][4]}	1/4
		440-460V		11h	561.16865	1/12	561.32865	1/12	561.63865 ^[4]	1/4
		>50V		10h	561.16861 ^[1]	1/12	561.32861 ^[1]	1/12		
3P+N+E	50Hz 60Hz	>50V		2h	561.16862 ^[1]	1/12	561.32862 ^[1]	1/12		
		100-130V		4h	561.1679	1/12	561.3279	1/12	561.6379 ^[4]	1/4
		208-250V		9h	561.1675	1/12	561.3275	1/12	561.6375 ^[4]	1/4
		346-415V		6h	561.1687	1/12	561.3287	1/12	561.6387 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	561.16874	1/12	561.32874	1/12		
	60Hz	480-500V		7h	561.16876	1/12	561.32876	1/12	561.63876 ^[4]	1/4
		600-690V		5h	561.16877 ^[3]	1/12	561.32877 ^[3]	1/12	561.63877 ^{[3][4]}	1/4
		440-460V		11h	561.16875	1/12	561.32875	1/12	561.63875 ^[4]	1/4
	>300-500Hz	>50V		2h	561.16872 ^[1]	1/12	561.32872 ^[1]	1/12		

- [1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.
- [2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.
- [3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.
- [4] [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)
 - Supplied with stainless steel fixing screws.
 - Open threaded cable entry
 - Cable gland included
 - Threaded cap/cable sleeve included



Switched interlocked sockets outlets

ADVANCE2 Series

■ Rated operating voltage >50V >> Standard version [FUSE]

ADVANCE 2 Series

562.



With fuse carrier IP44

INTERLOCKED SOCKET

IP44

106x240mm

M25X1,5

Poles	Hz	Volt	Colour	h	16A		32A	
2P+E	50Hz 60Hz	100-130V		4h	562.1670	1/12	562.3270	1/12
		200-250V		6h	562.1683	1/12	562.3283	1/12
		380-415V		9h	562.1678	1/12	562.3278	1/12
		480-500V		7h	562.16836	1/12	562.32836	1/12
		TST>50V		12h	562.16833	1/12	562.32833	1/12
	DC	>300-500Hz		2h	562.16832 ^[1]	1/12	562.32832 ^[1]	1/12
		>50-250V		3h	562.16834 ^[2]	1/12	562.32834 ^[2]	1/12
		>250V		8h	562.16838 ^[2]	1/12	562.32838 ^[2]	1/12
	3P+E	100-130V		4h	562.1672	1/12	562.3272	1/12
		200-250V		9h	562.1674	1/12	562.3274	1/12
		380-415V		6h	562.1686	1/12	562.3286	1/12
		380V 50Hz / 440V 60Hz		3h	562.16864	1/12	562.32864	1/12
		480-500V		7h	562.16866	1/12	562.32866	1/12
		600-690V		5h	562.16867 ^[3]	1/12	562.32867 ^[3]	1/12
		60Hz		11h	562.16865	1/12	562.32865	1/12
3P+N+E	100-300Hz	>50V		10h	562.16861 ^[1]	1/12	562.32861 ^[1]	1/12
	>300-500Hz	>50V		2h	562.16862 ^[1]	1/12	562.32862 ^[1]	1/12
	50Hz 60Hz	100-130V		4h	562.1679	1/12	562.3279	1/12
		208-250V		9h	562.1675	1/12	562.3275	1/12
		346-415V		6h	562.1687	1/12	562.3287	1/12
		380V 50Hz / 440V 60Hz		3h	562.16874	1/12	562.32874	1/12
		480-500V		7h	562.16876	1/12	562.32876	1/12
		600-690V		5h	562.16877 ^[3]	1/12	562.32877 ^[3]	1/12
		60Hz		11h	562.16875	1/12	562.32875	1/12
	>300-500Hz	>50V		2h	562.16872 ^[1]	1/12	562.32872 ^[1]	1/12

[1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.

[2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

[3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

- Supplied with stainless steel fixing screws.
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included
- Fuses not supplied

Switched interlocked sockets outlets

ADVANCE2 Series



Rated operating voltage >50V >> Standard version [FUSE]

ADVANCE 2 Series

563.



With fuse carrier IP66/
IP67

					INTERLOCKED SOCKET								
					IP66/IP67								
					106x240mm			136x390mm					
					M25X1,5			M40X1,5					
Poles	Hz	Volt	Colour	h	16A		32A		63A				
2P+E	50Hz 60Hz	100-130V		4h	563.1670	1/12	563.3270	1/12	563.6370		1/4		
		200-250V		6h	563.1683	1/12	563.3283	1/12	563.6383		1/4		
		380-415V		9h	563.1678	1/12	563.3278	1/12	563.6378	 	1/4		
		480-500V		7h	563.16836	1/12	563.32836	1/12					
		TST>50V		12h	563.16833	1/12	563.32833	1/12	563.63833		1/4		
	DC	>300-500Hz	>50V		2h	563.16832		1/12	563.32832		1/12		
		>50-250V		3h	563.16834		1/12	563.32834		1/12	563.63834	 	1/4
				8h	563.16838		1/12	563.32838		1/12	563.63838	 	1/4
3P+E	50Hz 60Hz	100-130V		4h	563.1672	1/12	563.3272	1/12	563.6372		1/4		
		200-250V		9h	563.1674	1/12	563.3274	1/12	563.6374		1/4		
		380-415V		6h	563.1686	1/12	563.3286	1/12	563.6386	 	1/4		
		380V 50Hz / 440V 60Hz		3h	563.16864	1/12	563.32864	1/12					
		480-500V		7h	563.16866	1/12	563.32866	1/12					
	60Hz	600-690V		5h	563.16867		1/12	563.32867		1/12			
		440-460V		11h	563.16865	1/12	563.32865	1/12					
				100-300Hz	>50V		10h	563.16861		1/12	563.32861		1/12
>300-500Hz			2h	563.16862		1/12	563.32862		1/12				
3P+N+E	50Hz 60Hz	100-130V		4h	563.1679	1/12	563.3279	1/12	563.6379		1/4		
		208-250V		9h	563.1675	1/12	563.3275	1/12	563.6375		1/4		
		346-415V		6h	563.1687	1/12	563.3287	1/12	563.6387	 	1/4		
		380V 50Hz / 440V 60Hz		3h	563.16874	1/12	563.32874	1/12					
		480-500V		7h	563.16876	1/12	563.32876	1/12					
	60Hz	600-690V		5h	563.16877		1/12	563.32877		1/12			
		440-460V		11h	563.16875	1/12	563.32875	1/12					
				>300-500Hz	>50V		2h	563.16872		1/12	563.32872		1/12

- [1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.
 - [2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.
 - [3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.
 - [4] [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)
 - [5] 400V only
- Supplied with stainless steel fixing screws.
 - Open threaded cable entry
 - Cable gland included
 - Threaded cap/cable sleeve included
 - Fuses not supplied

1.3



Switched interlocked sockets outlets

ADVANCE2 Series

■ Rated operating voltage >50V >> Standard version [DIN]

ADVANCE 2 Series

567.



With DIN rail (6 modules) IP44

INTERLOCKED SOCKET

IP44

136x390mm

M25X1,5

Poles	Hz	Volt	Colour	h	16A		32A	
2P+E	50Hz 60Hz	100-130V		4h	567.1670	1/4	567.3270	1/4
		200-250V		6h	567.1683	1/4	567.3283	1/4
		380-415V		9h	567.1678	1/4	567.3278	1/4
		480-500V		7h	567.16836	1/4	567.32836	1/4
		TST>50V		12h	567.16833	1/4	567.32833	1/4
	DC	>300-500Hz		2h	567.16832 ^[1]	1/4	567.32832 ^[1]	1/4
		>50-250V		3h	567.16834 ^[2]	1/4	567.32834 ^[2]	1/4
		>250V		8h	567.16838 ^[2]	1/4	567.32838 ^[2]	1/4
	3P+E	100-130V		4h	567.1672	1/4	567.3272	1/4
		200-250V		9h	567.1674	1/4	567.3274	1/4
		380-415V		6h	567.1686	1/4	567.3286	1/4
		380V 50Hz / 440V 60Hz		3h	567.16864	1/4	567.32864	1/4
		480-500V		7h	567.16866	1/4	567.32866	1/4
		600-690V		5h	567.16867 ^[3]	1/4	567.32867 ^[3]	1/4
		60Hz		11h	567.16865	1/4	567.32865	1/4
3P+N+E	100-300Hz	>50V		10h	567.16861 ^[1]	1/4	567.32861 ^[1]	1/4
	>300-500Hz	>50V		2h	567.16862 ^[1]	1/4	567.32862 ^[1]	1/4
	50Hz 60Hz	100-130V		4h	567.1679	1/4	567.3279	1/4
		208-250V		9h	567.1675	1/4	567.3275	1/4
		346-415V		6h	567.1687	1/4	567.3287	1/4
		380V 50Hz / 440V 60Hz		3h	567.16874	1/4	567.32874	1/4
		480-500V		7h	567.16876	1/4	567.32876	1/4
	60Hz	600-690V		5h	567.16877 ^[3]	1/4	567.32877 ^[3]	1/4
		440-460V		11h	567.16875	1/4	567.32875	1/4
		>300-500Hz		2h	567.16872 ^[1]	1/4	567.32872 ^[1]	1/4

[1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.

[2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

[3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

- Supplied with stainless steel fixing screws.
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included
- [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)

Rated operating voltage >50V >> Standard version [DIN]

ADVANCE 2 Series										
568.										
										
With DIN rail (6 modules) IP66/IP67										
INTERLOCKED SOCKET										
IP66/IP67										
136x390mm										
M25X1,5										
M40X1,5										
Poles	Hz	Volt	Colour	h	16A		32A		63A	
2P+E	50Hz 60Hz	100-130V		4h	568.1670	1/4	568.3270	1/4	568.6370	1/4
		200-250V		6h	568.1683	1/4	568.3283	1/4	568.6383	1/4
		380-415V		9h	568.1678	1/4	568.3278	1/4	568.6378 ^[4]	1/4
		480-500V		7h	568.16836	1/4	568.32836	1/4		
		TST>50V		12h	568.16833	1/4	568.32833	1/4	568.63833	1/4
	>300-500Hz	>50V		2h	568.16832 ^[1]	1/4	568.32832 ^[1]	1/4		
	DC	>50-250V		3h	568.16834 ^[2]	1/4	568.32834 ^[2]	1/4	568.63834 ^[2]	1/4
		>250V		8h	568.16838 ^[2]	1/4	568.32838 ^[2]	1/4	568.63838 ^[2]	1/4
3P+E	50Hz 60Hz	100-130V		4h	568.1672	1/4	568.3272	1/4	568.6372	1/4
		200-250V		9h	568.1674	1/4	568.3274	1/4	568.6374	1/4
		380-415V		6h	568.1686	1/4	568.3286	1/4	568.6386 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	568.16864	1/4	568.32864	1/4		
		480-500V		7h	568.16866	1/4	568.32866	1/4		
	60Hz	600-690V		5h	568.16867 ^[3]	1/4	568.32867 ^[3]	1/4		
		440-460V		11h	568.16865	1/4	568.32865	1/4		
		100-300Hz	>50V		10h	568.16861 ^[1]	1/4	568.32861 ^[1]	1/4	
>300-500Hz	>50V		2h	568.16862 ^[1]	1/4	568.32862 ^[1]	1/4			
3P+N+E	50Hz 60Hz	100-130V		4h	568.1679	1/4	568.3279	1/4	568.6379	1/4
		208-250V		9h	568.1675	1/4	568.3275	1/4	568.6375	1/4
		346-415V		6h	568.1687	1/4	568.3287	1/4	568.6387 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	568.16874	1/4	568.32874	1/4		
		480-500V		7h	568.16876	1/4	568.32876	1/4		
	60Hz	600-690V		5h	568.16877 ^[3]	1/4	568.32877 ^[3]	1/4		
		440-460V		11h	568.16875	1/4	568.32875	1/4		
		>300-500Hz	>50V		2h	568.16872 ^[1]	1/4	568.32872 ^[1]	1/4	

^[1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.

^[2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

^[3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

^[4] 400V only

- Supplied with stainless steel fixing screws.
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included
- [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)



Switched interlocked sockets outlets

ADVANCE2 Series

■ Rated operating voltage >50V >> HD version [HEAVY DUTY]

ADVANCE 2 HD Series

564.



With fuse carrier IP66/
IP67

INTERLOCKED SOCKET

IP66/IP67

106x240mm

136x390mm

M25X1,5

M40X1,5

Poles	Hz	Volt	Colour	h	16A	32A	63A
2P+E	50Hz 60Hz	100-130V	Yellow	4h	564.1670	564.3270	564.6370 ^[4]
		200-250V	Blue	6h	564.1683	564.3283	564.6383 ^[4]
		380-415V	Red	9h	564.1678	564.3278	564.6378 ^{[5][4]}
		480-500V	Black	7h	564.16836	564.32836	
		TST>50V	Grey	12h	564.16833	564.32833	564.63833 ^[4]
	DC	>300-500Hz	Green	2h	564.16832 ^[1]	564.32832 ^[1]	564.63832 ^{[1][4]}
		>50-250V	Grey	3h	564.16834 ^[2]	564.32834 ^[2]	564.63834 ^{[2][4]}
		>250V	Grey	8h	564.16838 ^[2]	564.32838 ^[2]	564.63838 ^{[2][4]}
3P+E	50Hz 60Hz	100-130V	Yellow	4h	564.1672	564.3272	564.6372 ^[4]
		200-250V	Blue	9h	564.1674	564.3274	564.6374 ^[4]
		380-415V	Red	6h	564.1686	564.3286	564.6386 ^{[5][4]}
		380V 50Hz / 440V 60Hz		3h	564.16864	564.32864	
		480-500V	Black	7h	564.16866	564.32866	
	60Hz	600-690V		5h	564.16867 ^[3]	564.32867 ^[3]	
		440-460V	Red	11h	564.16865	564.32865	
		100-300Hz		10h	564.16861 ^[1]	564.32861 ^[1]	
		>300-500Hz	Green	2h	564.16862 ^[1]	564.32862 ^[1]	
3P+N+E	50Hz 60Hz	100-130V	Yellow	4h	564.1679	564.3279	564.6379 ^[4]
		208-250V	Blue	9h	564.1675	564.3275	564.6375 ^[4]
		346-415V	Red	6h	564.1687	564.3287	564.6387 ^{[5][4]}
		380V 50Hz / 440V 60Hz		3h	564.16874	564.32874	
		480-500V	Black	7h	564.16876	564.32876	
	60Hz	600-690V		5h	564.16877 ^[3]	564.32877 ^[3]	
		440-460V	Red	11h	564.16875	564.32875	
		>300-500Hz	Green	2h	564.16872 ^[1]	564.32872 ^[1]	

Heavy Duty products are especially suited to greivous working conditions and are also resistant to highly salty environments

- [1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.
- [2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.
- [3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.
- [4] [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)
- [5] 400V only
 - Supplied with stainless steel fixing screws.
 - Open threaded cable entry
 - Cable gland included
 - Threaded cap/cable sleeve included

Rated operating voltage >50V >> HD version [HEAVY DUTY]

ADVANCE 2 HD Series

569.



With DIN rail (6 modules) IP66/IP67

INTERLOCKED SOCKET

IP66/IP67

136x390mm

Poles	Hz	Volt	Colour	h	M25X1,5		M40X1,5			
					16A	32A	63A			
2P+E	50Hz 60Hz	100-130V		4h	569.1670	1/4	569.3270	1/4	569.6370	1/4
		200-250V		6h	569.1683	1/4	569.3283	1/4	569.6383	1/4
		380-415V		9h	569.1678	1/4	569.3278	1/4	569.6378 ^[4]	1/4
		480-500V		7h	569.16836	1/4	569.32836	1/4		
		TST>50V		12h	569.16833	1/4	569.32833	1/4	569.63833	1/4
	>300-500Hz	>50V		2h	569.16832 ^[1]	1/4	569.32832 ^[1]	1/4	569.63832 ^[1]	1/4
	DC	>50-250V		3h	569.16834 ^[2]	1/4	569.32834 ^[2]	1/4	569.63834 ^[2]	1/4
		>250V		8h	569.16838 ^[2]	1/4	569.32838 ^[2]	1/4	569.63838 ^[2]	1/4
3P+E	50Hz 60Hz	100-130V		4h	569.1672	1/4	569.3272	1/4	569.6372	1/4
		200-250V		9h	569.1674	1/4	569.3274	1/4	569.6374	1/4
		380-415V		6h	569.1686	1/4	569.3286	1/4	569.6386 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	569.16864	1/4	569.32864	1/4		
		480-500V		7h	569.16866	1/4	569.32866	1/4		
	60Hz	600-690V		5h	569.16867 ^[3]	1/4	569.32867 ^[3]	1/4		
		440-460V		11h	569.16865	1/4	569.32865	1/4		
	>300-500Hz	>50V		10h	569.16861 ^[1]	1/4	569.32861 ^[1]	1/4		
3P+N+E	>300-500Hz		2h	569.16862 ^[1]	1/4	569.32862 ^[1]	1/4			
	50Hz 60Hz	100-130V		4h	569.1679	1/4	569.3279	1/4	569.6379	1/4
		208-250V		9h	569.1675	1/4	569.3275	1/4	569.6375	1/4
		346-415V		6h	569.1687	1/4	569.3287	1/4	569.6387 ^[4]	1/4
		380V 50Hz / 440V 60Hz		3h	569.16874	1/4	569.32874	1/4		
		480-500V		7h	569.16876	1/4	569.32876	1/4		
	60Hz	600-690V		5h	569.16877 ^[3]	1/4	569.32877 ^[3]	1/4		
		440-460V		11h	569.16875	1/4	569.32875	1/4		
>300-500Hz	>50V		2h	569.16872 ^[1]	1/4	569.32872 ^[1]	1/4			

Heavy Duty products are especially suited to previous working conditions and are also resistant to highly salty environments

- [1] The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging above 100 Hz; contact Scame Technical Service for further information.
- [2] When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.
- [3] Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.
- [4] 400V only
 - Supplied with stainless steel fixing screws.
 - Open threaded cable entry
 - Cable gland included
 - Threaded cap/cable sleeve included
 - [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)



Switched interlocked sockets outlets

ADVANCE2 Series

■ Rated operating voltage <50V

ADVANCE 2 Series

565.



Version with safety transformer

INTERLOCKED SOCKET

IP44

IP66/IP67

106x240mm

136x390mm

106x240mm

136x390mm

Current Poles Volt Colour

M25X1,5

16A	2P	24V		565.2416	1/10	565.2516 ^{[1][2]}	1/4	565.2416/S	1/10	565.2516/S ^{[1][2]}	1/4
-----	----	-----	--	----------	------	----------------------------	-----	------------	------	------------------------------	-----

SELV transformer 220/24V~ 150VA (continuous duty).

[1] [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)

[2] Provided protections: primary circuit (2A), secondary circuit (6A), fuses included.

- Supplied with stainless steel fixing screws.
- When plug is inserted a micro-switch is activated and closes the circuit
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included

ADVANCE 2 HD Series

566.



Version with safety transformer (HD - Heavy Duty)

INTERLOCKED SOCKET

IP44

IP66/IP67

106x240mm

136x390mm

106x240mm

136x390mm

Current Poles Volt Colour

M25X1,5

16A	2P	24V		566.2416	1/10	566.2516 ^{[1][2]}	1/4	566.2416/S	1/10	566.2516/S ^{[1][2]}	1/4
-----	----	-----	--	----------	------	----------------------------	-----	------------	------	------------------------------	-----

Heavy Duty products are especially suited to greivous working conditions and are also resistant to highly salty environments

SELV transformer 220/24V~ 150VA (continuous duty).

[1] [LARGE] Possibility to enter from the bottom (smooth walls with drilling point mark)

[2] Provided protections: primary circuit (2A), secondary circuit (6A), fuses included.

- Supplied with stainless steel fixing screws.
- When plug is inserted a micro-switch is activated and closes the circuit
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included

Switched interlocked sockets outlets

ADVANCE2 Series



Rated operating voltage <50V

ADVANCE 2 Series

565.



Version with DIN rail (6 modules)

					INTERLOCKED SOCKET			
					IP44		IP66/IP67	
					106x240mm			
					M25X1,5			
Current	Poles	Volt	Colour	h				
16A	2P	20-25V			565.2420	1/10	565.2420/S	1/10
		40-50V		12h	565.2421	1/10	565.2421/S	1/10
20-25V				565.2432	1/10	565.2432/S	1/10	
32A		40-50V		12h	565.2433	1/10	565.2433/S	1/10

- Supplied with stainless steel fixing screws.
- When plug is inserted a micro-switch is activated and closes the circuit
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included

ADVANCE 2 HD Series

566.



Version with DIN rail (6 modules) (HD - Heavy Duty)

					INTERLOCKED SOCKET			
					IP44		IP66/IP67	
					106x240mm			
					M25X1,5			
Current	Poles	Volt	Colour	h				
16A	2P	20-25V		12h	566.2420	1/10	566.2420/S	1/10
		40-50V			566.2421	1/10	566.2421/S	1/10
32A		20-25V		566.2432	1/10	566.2432/S	1/10	
40-50V			12h	566.2433	1/10	566.2433/S	1/10	

Heavy Duty products are especially suited to previous working conditions and are also resistant to highly salty environments

- Supplied with stainless steel fixing screws.
- When plug is inserted a micro-switch is activated and closes the circuit
- Open threaded cable entry
- Cable gland included
- Threaded cap/cable sleeve included

1.3




Switched interlocked sockets outlets

ADVANCE2 System

Standard version >> Compact module 106

ADVANCE 2 System

576.



Description	Version	IP	Notes	Dimension	Power	Modular bases	Enclosures
CONSUMER UNIT			10 DIN	212x150x110mm	14W		
			4 DIN	106x150x110mm	8W		
JUNCTION BOX 106	CUT-OUT SINGLE	IP66	16/32A	106x150x105mm			576.4301 ^[1] 12
	ONE-MODULE BLANK						
	TWO-MODULE BLANK			212x150x105mm			
MODULAR BASE 106			16-32A	106x434x18mm		576.4300 12	

^[1] Metric break-through cable entry

^[2] Power dissipation calculated in conformity with CEI 23-49 italian standards

Standard version >> Large module 136

ADVANCE 2 System

576.



Description	Version	IP	Notes	Dimension	Power	Modular bases	Enclosures
CONSUMER UNIT			13 DIN	272x150x110mm	17W		
			6 DIN	136x150x110mm	9W		
JUNCTION BOX 136	CUT-OUT SINGLE	IP66	16/32A	136x150x105mm			576.4321 ^[1] 12
	ONE-MODULE BLANK						
	TWO-MODULE BLANK			272x150x105mm			
MODULAR BASE 136			16-32-63A	136x584x18mm		576.4340 6	
ENCLOSURE FOR SWITCH		IP66	ADVANCE2	136x150x105mm			

^[1] Metric break-through cable entry

^[2] For fitting with Y1 switch size panel mounting version (R) and relevant front operators handleless (IP65).

^[3] Power dissipation calculated in conformity with CEI 23-49 italian standards

ADVANCE 2 System
576.



Consumer units

Enclosures

Consumer units

576.4302 2 1 6

576.4303 1 12

576.4304 1 6

576.4305 2 1 6

ADVANCE 2 System
576.



Consumer units

Enclosures

Consumer units

Enclosures

576.4322 3 1 6

576.4323 1 12

576.4324 1 6

576.4325 3 1 6

576.4390 2 1 6



Switched interlocked sockets outlets

ADVANCE2 System

HD version >> Compact module 106 HD - Heavy Duty

ADVANCE 2 HD System

578.



Description	Version	IP	Notes	Dimension	Power	Modular bases	Enclosures
CONSUMER UNIT			10 DIN	212x150x110mm	14W		
			4 DIN	106x150x110mm	8W		
JUNCTION BOX 106	ONE-MODULE BLANK	IP66		106x150x105mm			578.4301 ^[1] 12
	TWO-MODULE BLANK						
MODULAR BASE 106			16-32A	106x434x18mm		578.4300 12	

Heavy Duty products are especially suited to greivous working conditions and are also resistant to highly salty environments

[1] Metric break-through cable entry

[2] Power dissipation calculated in conformity with CEI 23-49 italian standards

HD version >> Large module 136 HD - Heavy Duty

ADVANCE 2 HD System

578.



Description	Version	IP	Notes	Dimension	Power	Modular bases	Enclosures
CONSUMER UNIT			13 DIN	272x150x110mm	17W		
			6 DIN	136x150x110mm	9W		
JUNCTION BOX 136	ONE-MODULE BLANK	IP66		136x150x105mm			578.4321 ^[1] 12
	TWO-MODULE BLANK			272x150x105mm			
MODULAR BASE 136			16-32-63A	136x584x18mm		578.4340 6	

Heavy Duty products are especially suited to greivous working conditions and are also resistant to highly salty environments

[1] Metric break-through cable entry

[2] Power dissipation calculated in conformity with CEI 23-49 italian standards

ADVANCE 2 HD System
578.



Consumer units



Enclosures



Consumer units

578.4302 2 1 6

578.4304 1 6

578.4305 2 1 6

ADVANCE 2 HD System
578.



Consumer units



Enclosures



Consumer units

578.4322 2 1 6

578.4324 1 6

578.4325 2 1 6

1.3

Switched interlocked sockets outlets

ADVANCE2 System

Modular system for combination units - IP66

ENCLOSURES ACCESSORIES

654.



Description

Kit accessories

TRIANGULAR LOCK KIT

654.0079

1/10

TOP22 Series

590.



Description

Colour

Switch size

Contact blocks

NC CONTACT		Y1	590.PL004001 ¹	10/60
		Y2	590.PL004003 ¹	10
NO CONTACT		Y1	590.PL004002 ²	10/60
		Y2	590.PL004004 ²	10

¹ NC=Normally closed

² NO=Normally open

- Snap catch