

References						
Designation	Use Applications	Description	Cable length m (ft)	Unitreference	Sold in lots of (1)	Weight kg/ lb
Measurement accessories						
Temperature control						
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Gray - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCRN52015	8	0.144/0.320
				TM1STNTCRN5201P	100	0.144/0.320
			3 (9.84)	TM1STNTCRN52030	5	0.180/0.400
				TM1STNTCRN5203P	50	0.180/0.400
			5 (16.40)	TM1STNTCRN52050	4	0.228/0.500
				TM1STNTCRN5205P	25	0.228/0.500
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 67 - Gray - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCRN61515	8	0.104/0.230
				TM1STNTCRN6151P	100	0.104/0.230
			3 (9.84)	TM1STNTCRN61530	5	0.125/0.280
				TM1STNTCRN6153P	50	0.125/0.280
			5 (16.40)	TM1STNTCRN61550	4	0.164/0.360
				TM1STNTCRN6155P	25	0.164/0.360
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- FAST - IP 67 - Gray - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCSF44015	8	0.144/0.320
				TM1STNTCSF4401P	100	0.144/0.320
			3 (9.84)	TM1STNTCSF44030	5	0.175/0.390
				TM1STNTCSF4403P	50	0.175/0.390
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Gray - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCSN62015	8	0.144/0.320
				TM1STNTCSN6201P	100	0.144/0.320
			3 (9.84)	TM1STNTCSN62030	5	0.175/0.390
				TM1STNTCSN6203P	50	0.175/0.390
			5 (16.40)	TM1STNTCSN62050	4	0.232/0.510
				TM1STNTCSN6205P	25	0.232/0.510
NTC probes with a strap 	Pipe ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Gray - Equipped with 2 conductor cables for controller side - Equipped with strap	1.5 (4.92)	TM1STNTCTN62015	8	0.152/0.340
				TM1STNTCTN6201P	100	0.152/0.340
			3 (9.84)	TM1STNTCTN62030	5	0.180/0.400
				TM1STNTCTN6203P	50	0.180/0.400
PT1000 probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Green - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STPTTSN62015	8	0.144/0.320
				TM1STPTTSN6201P	100	0.144/0.320
			3 (9.84)	TM1STPTTSN62030	5	0.175/0.390
				TM1STPTTSN6203P	50	0.175/0.390
PT1000 probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Green - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STPTTSN52015	8	0.136/0.300
				TM1STPTTSN5201P	100	0.136/0.300
			3 (9.84)	TM1STPTTSN52030	5	0.175/0.390
				TM1STPTTSN5203P	50	0.175/0.390
			5 (16.40)	TM1STPTTSN52050	4	0.232/0.510
				TM1STPTTSN5205P	25	0.232/0.510

(1) The given value is the number of products delivered for one ordered reference.

References				
Designation	Use Applications	Description	Reference	Weight kg/ lb
Measurement accessories				
Temperature control				
NTC probe	Outside air ■ Temperature control: -50...100 °C (-58...212 °F)	- IP 65 - Wall mounting - NTC 10kOhm /25°C	TM1STNTCW69755	0.050/ 0.110
				
NTC probe	Inside air (room) ■ Temperature control: -25...40 °C (-13...104 °F)	- IP 30 - Indoor wall mounting - NTC 10kOhm /25°C	TM1STNTCWN75750	0.050/ 0.110
				
Humidity control				
Humidity probe	Multi-purpose ■ Humidity control: 0...100%	- IP 65 - Wall mounting - 4-20 mA	TM1SHC4	0.140/ 0.308
				
Humidity & temperature control				
Humidity & temperature probes	Multi-purpose ■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)	- IP 65 - Wall mounting - 4-20 mA, NTC 10kOhm /25°C	TM1SHTCN4	0.140/ 0.308
				
	Multi-purpose ■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)	- IP 65 - Wall mounting - 2x 4-20 mA	TM1SHTCC4	0.140/ 0.308
	Multi-purpose ■ Humidity control: 0...100% ■ Temperature control: -40...60 °C (-40...140 °F)	- IP 65 - Wall mounting - 2x Modbus ports embedded (RS-485 / Modbus RTU)	TM1SHTM4	0.140/ 0.308