

■ OPTIMA-TOP Series >> Surface mounting appliance inlets

					OPTIMA-TOP Series	
					240.	
						
					 Mantle terminals	
					APPLIANCE INLET	
					IP44/IP54	
					M40X1,5	
					63A	
2P+E	50Hz 60Hz	100-130V		4h	240.6390T	4
		200-250V		6h	240.6393T	4
		380-415V		9h	240.6398T	4
		480-500V		7h	240.63936T	
		TST>50V		12h	240.63933T	
	>300-500Hz	>50V		2h	240.63932T	
		DC	>50-250V		3h	240.63934T
			>250V		8h	240.63938T
3P+E	50Hz 60Hz	100-130V		4h	240.6391T	4
		200-250V		9h	240.6394T	4
		380-415V		6h	240.6396T	4
		380V 50Hz / 440V 60Hz		3h	240.63964T	
		440-460V		11h	240.63965T	
		480-500V		7h	240.63966T	
	>300-500Hz	600-690V		5h	240.63967T	
		>50V		10h	240.63961T	
3P+N+E	50Hz 60Hz	>50V		2h	240.63962T	
		100-130V		4h	240.6392T	4
		208-250V		9h	240.6395T	4
		346-415V		6h	240.6397T	4
		380V 50Hz / 440V 60Hz		3h	240.63974T	
		480-500V		7h	240.63976T	
	>300-500Hz	600-690V		5h	240.63977T	
		440-460V		11h	240.63975T	
	>50V		2h	240.63972T		

- Cable gland included

1.1



Plugs and inlets for industrial applications

Surface mounting appliance inlets - IP66/IP67/IP69

■ OPTIMA-TOP Series >> Surface mounting appliance inlets

OPTIMA-TOP Series

245.



Mantle terminals

APPLIANCE INLET

IP66/IP67

M40X1,5

63A

M63X1,5

125A

Poles	Hz	Volt	Colour	h			
2P+E	50Hz 60Hz	100-130V		4h	245.6390T	4	245.12590T 1/4
		200-250V		6h	245.6393T	4	245.12593T 1/4
		380-415V		9h	245.6398T	4	245.12598T 1/4
		480-500V		7h	245.63936T		245.125936T
		TST>50V		12h	245.63933T		245.125933T
	>300-500Hz	>50V		2h	245.63932T		245.125932T
		>50-250V		3h	245.63934T		245.125934T
	DC	>250V		8h	245.63938T		245.125938T
3P+E	50Hz 60Hz	100-130V		4h	245.6391T	4	245.12591T 1/4
		200-250V		9h	245.6394T	4	245.12594T 1/4
		380-415V		6h	245.6396T	4	245.12596T 1/4
		380V 50Hz / 440V 60Hz		3h	245.63964T		245.125964T
		480-500V		7h	245.63966T		245.125966T
	60Hz	600-690V		5h	245.63967T		245.125967T
		440-460V		11h	245.63965T		245.125965T
	100-300Hz	>50V		10h	245.63961T		245.125961T
	>300-500Hz	>50V		2h	245.63962T		245.125962T
3P+N+E	50Hz 60Hz	100-130V		4h	245.6392T	4	245.12592T 1/4
		208-250V		9h	245.6395T	4	245.12595T 1/4
		346-415V		6h	245.6397T	4	245.12597T 1/4
		380V 50Hz / 440V 60Hz		3h	245.63974T		245.125974T
		480-500V		7h	245.63976T	4	245.125976T
	60Hz	600-690V		5h	245.63977T		245.125977T
		440-460V		11h	245.63975T		245.125975T
	>300-500Hz	>50V		2h	245.63972T		245.125972T

- Cable gland included



Terminals
Mantle terminals (EASY-PLUG)

ACCESSORIES

570.



Description	Current	Poles	Cover for IP66/IP67/IP69 plugs	
PLUG CAP	16A 20A	2P+E	570.90163	10/100
		3P+E	570.90164	10/100
		3P+N+E	570.90165	10/100
	30A 32A		570.90325	10/100
		2/3P+E	570.90324	10/100
	60A 63A	ALL	570.9063	10
	100A 125A		570.9125	10

1.1

