

PF140700C



RUMC21BD

PF140725B



RUMC21F7

PF140708C



RUMC32BD

PF140735



RUMF32F7

References

Relays for standard applications, with lockable test button and without LED (sold in lots of 10)

Pins	Control circuit voltage	Number and type of contacts - Thermal current (Ith)			
		2 CO - 10 A	Weight	3 CO - 10 A	Weight
	V	Unit reference	kg/lb	Unit reference	kg/lb
Cylindrical	12	RUMC21JD	0.086/0.190	RUMC31JD	0.086/0.190
	24	RUMC21BD	0.086/0.190	RUMC31BD	0.086/0.190
	48	RUMC21ED	0.086/0.190	RUMC31ED	0.086/0.190
	60	—	—	RUMC31ND	0.086/0.190
	110	RUMC21FD	0.086/0.190	RUMC31FD	0.086/0.190
	125	—	—	RUMC31GD	0.086/0.190
	220	—	—	RUMC31MD	0.086/0.190
	~ 24	RUMC21B7	0.086/0.190	RUMC31B7	0.086/0.190
	~ 48	RUMC21E7	0.086/0.190	RUMC31E7	0.086/0.190
	~ 120	RUMC21F7	0.086/0.190	RUMC31F7	0.086/0.190
	~ 230	RUMC21P7	0.086/0.190	RUMC31P7	0.086/0.190
Flat (Faston type)	12	RUMF21JD	0.086/0.190	RUMF31JD	0.086/0.190
	24	RUMF21BD	0.086/0.190	RUMF31BD	0.086/0.190
	48	RUMF21ED	0.086/0.190	RUMF31ED	0.086/0.190
	110	RUMF21FD	0.086/0.190	RUMF31FD	0.086/0.190
	~ 24	RUMF21B7	0.086/0.190	RUMF31B7	0.086/0.190
	~ 48	RUMF21E7	0.086/0.190	RUMF31E7	0.086/0.190
	~ 120	RUMF21F7	0.086/0.190	RUMF31F7	0.086/0.190
	~ 230	RUMF21P7	0.086/0.190	RUMF31P7	0.086/0.190

Relays for standard applications, with lockable test button and LED (sold in lots of 10)

Cylindrical	12	RUMC22JD	0.086/0.190	RUMC32JD	0.086/0.190
	24	RUMC22BD	0.086/0.190	RUMC32BD	0.086/0.190
	48	RUMC22ED	0.086/0.190	RUMC32ED	0.086/0.190
	60	—	—	RUMC32ND	0.086/0.190
	110	RUMC22FD	0.086/0.190	RUMC32FD	0.086/0.190
	125	—	—	RUMC32GD	0.086/0.190
	~ 24	RUMC22B7	0.086/0.190	RUMC32B7	0.086/0.190
	~ 48	RUMC22E7	0.086/0.190	RUMC32E7	0.086/0.190
	~ 120	RUMC22F7	0.086/0.190	RUMC32F7	0.086/0.190
	~ 230	RUMC22P7	0.086/0.190	RUMC32P7	0.086/0.190
Flat (Faston type)	12	RUMF22JD	0.086/0.190	RUMF32JD	0.086/0.190
	24	RUMF22BD	0.086/0.190	RUMF32BD	0.086/0.190
	48	RUMF22ED	0.086/0.190	RUMF32ED	0.086/0.190
	110	RUMF22FD	0.086/0.190	RUMF32FD	0.086/0.190
	~ 24	RUMF22B7	0.086/0.190	RUMF32B7	0.086/0.190
	~ 48	RUMF22E7	0.086/0.190	RUMF32E7	0.086/0.190
	~ 120	RUMF22F7	0.086/0.190	RUMF32F7	0.086/0.190
	~ 230	RUMF22P7	0.086/0.190	RUMF32P7	0.086/0.190

2

PF140733B

RUZSC3M +
Relay RUMC3...

PF106027



RUW241P7

PF516229



RUW101MW

References (continued)

Sockets

Contact terminal arrangement	Connection	Relay type	Sold in lots of	Unit reference	Weight kg/lb
Mixed	Screw connector	RUMC2...	10	RUZC2M	0.054/0.119
		RUMC3...	10	RUZC3M	0.054/0.119
Separate	Screw connector	RUMC2...	10	RUZSC2M	0.095/0.209
		RUMC3...	10	RUZSC3M	0.100/0.220
		RUMF2...	10	RUZSF3M	0.095/0.209
		RUMF3...			

Protection modules

Description	For use with	Voltage	Sold in lots of	Unit reference	Weight kg/lb
		V			
Diode	All RUM sockets	~ 6...250	10	RUW240BD	0.004/0.009
RC circuit	All RUM sockets	~ 110...240	10	RUW241P7	0.004/0.009
Varistor	All RUM sockets	~ / ~ 24	10	RUW242B7	0.004/0.009
		~ / ~ 240	10	RUW242P7	0.004/0.009

Timer module

Description	For use with	Voltage	Reference	Weight kg/lb
		V		
Multifunction	All RUM sockets	~ / ~ 24... 240	RUW101MW	0.020/0.044

Timing relays

Description	For use with	Reference	Weight kg/lb
2 timed CO contacts (single-function or multifunction)	RUZC...M sockets	RE48A... (1)	—

(1) Please refer to "Zelio Time timing relays" catalog.