

Size (A)	32	63	63	100
----------	----	----	----	-----

Electrical specifications

Voltage	120 - 127 / 220 - 240 / 254 V ($\pm 10\%$)	208 - 220 / 380 - 415 / 440 V ($\pm 10\%$)
Number of phases	ph+N or ph-ph (+ PE)	3ph+N or 3ph (+ PE)
Frequency	50 Hz or 60 Hz (configurable $\pm 5\%$)	
Number of poles switching	2-pole switching	3 or 4-pole switching
Neutral system	Compatible with all earthing systems	
Maintenance bypass	Interlocked and secured	
Overload	150% for 2 minutes - 110% for 60 minutes	

Efficiency

Admissible power factor	No restrictions
-------------------------	-----------------

Environment

Operating ambient temperature	0 - 40 °C	
Relative humidity	95%	
Maximum altitude	1000 m a.s.l. without derating	
Cooling	Forced ventilation	
Acoustic level at 1 m (ISO 3746)	< 45 dB(A)	< 60 dB(A)

Mechanical specifications

Dimensions W x D x H ⁽¹⁾	483 x 747 x 89 mm (19" x 747 x 2U)*	483 x 648 x 400 mm (19" x 648 x 9U)*
Weight	26 kg	58 kg
Degree of protection	IP30	

Standards

Performance and safety	IEC 62310, IEC 60529, AS 62310, AS 60529	
EMC	C2 category (IEC 62310-2, AS 62310.2)	
Protection class	CB or PC class	
Product declaration	CE, RCM (E2376)	

(1) Depth does not include handles (+40 mm).