

Size (A)	200	300	400	600	800	1000	1250	1400	1600	1800
----------	-----	-----	-----	-----	-----	------	------	------	------	------

Electrical specifications

Voltage	208 - 220 / 380 - 415 / 440 V ($\pm 10\%$)
Number of phases	3ph+N or 3ph (+ PE)
Frequency	50 Hz or 60 Hz (configurable $\pm 5\%$)
Number of poles switching	3 or 4-pole switching
Neutral system	Compatible with all earthing systems
Maintenance bypass	Interlocked and secured
Overload	150% for 2 minutes - 110% for 60 minutes
Efficiency	99%
Admissible power factor	No restrictions

Environment

Operating ambient temperature	0 - 40°C
Relative humidity	95 %
Maximum altitude	1000 m a.s.l. without derating
Cooling	Forced ventilation
Acoustic level at 1 m (ISO 3746)	< 60 dBA

Mechanical specifications

Dimensions W x D x H ⁽¹⁾	400 x 586 x 765 mm	600 x 586 x 765 mm	800 x 586 x 765 mm	1000 x 950 x 1930 mm	910 x 815 x 1955 mm
Weight	70 kg	105 kg	130 kg	495 kg	750 kg
Degree of protection	IP20				

Standards

Performance and safety	IEC 62310, IEC 60529, AS 62310, AS 60529
EMC	C2 category (IEC 62310-2, AS 62310.2)
Protection class	CB or PC class
Product declaration	CE, RCM (E2376)

(1) Depth does not include handles (+40 mm).