


STK-M | metric thread

Accessories

Blind plug for metric threads

Temperature: -30°C ... +100°C

Material: polyamide, fibre-glass reinforced



FLEXA No.	Thread type	Colour	C [mm]	Ø B [mm]	Weight [kg/100]	PU [pcs.]
10551001212	M12x1, 5	Black	6,0	15,0	0,110	100
10551001216	M16x1, 5	Black	6,0	20,0	0,190	100
10551001220	M20x1, 5	Black	6,0	24,0	0,260	100
10551001225	M25x1, 5	Black	8,0	30,0	0,410	100
10551001232	M32x1, 5	Black	8,0	37,0	0,690	100
10551001240	M40x1, 5	Black	8,0	46,0	1,000	50
10551001250	M50x1, 5	Black	10,0	56,0	1,520	50
10551001012	M12x1, 5	Light grey	6,0	15,0	0,110	100
10551001016	M16x1, 5	Light grey	6,0	20,0	0,190	100
10551001020	M20x1, 5	Light grey	6,0	24,0	0,260	100
10551001025	M25x1, 5	Light grey	8,0	30,0	0,410	100
10551001032	M32x1, 5	Light grey	8,0	37,0	0,690	100
10551001040	M40x1, 5	Light grey	8,0	46,0	1,000	50
10551001050	M50x1, 5	Light grey	10,0	56,0	1,520	50

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.