

TRANSFORMERS

Single-phase control and isolation transformers

- acc. to EN 61558
- touch protected acc. to EN 60529 (IP20)
- isolation class T 60/B

Approvals:  

MET

Input voltage 230 V AC ±5 %
Output voltage 230 V AC



MET

Input voltage 400 V AC ±5 %
Output voltage 230 V AC

MET

Input voltage 240/415 V AC
Output voltage 110/240 V AC

Ordering data	Art.-No.	Art.-No.	Art.-No.
Nominal power rating	spring clamp/screw terminals	spring clamp/screw terminals	spring clamp/screw terminals
500 VA	6686020	6686021	6686025
630 VA	6686030	6686031	6686035
800 VA	6686040	6686041	6686045
1000 VA	6686050	6686051	6686055
1500 VA	6686060	6686061	
Technical data			
Input voltage	230 V AC ±5 %	400 V AC ±5 %	240/415 V AC
Output voltage	230 V AC	230 V AC	110/240 V AC

Single-phase control and isolation transformers

- acc. to EN 61558
- touch protected acc. to EN 60529 (IP20)
- isolation class T 60/B

Approvals:  

MET

Input voltage 230 V AC ±5 %
Output voltage 230 V AC



MET

Input voltage 400 V AC ±5 %
Output voltage 230 V AC

Ordering data	Art.-No.	Art.-No.	
Nominal power rating	spring clamp/screw terminals	spring clamp/screw terminals	
2000 VA	6686070	6686071	
3000 VA	6686090	6686091	
4000 VA	6686110	6686111	
5000 VA	6686130	6686131	
Technical data			
Input voltage	230 V AC ±5 %	400 V AC ±5 %	
Output voltage	230 V AC	230 V AC	

Notes	For screw-type terminal connection, the item number changes from 6686... to 86... (i.e. the prefix 66 is dropped).
-------	--

TRANSFORMERS

Single-phase safety transformers

– acc. to EN 61558

– touch protected acc. to
EN 60529 (IP20)

– isolation class T 60/B

Approvals: **cULus** **GL**

MET

Input voltage 230 V AC $\pm 5\%$
Output voltage 24 V AC SELV



MET

Input voltage 400 V AC $\pm 5\%$
Output voltage 24 V AC SELV

Ordering data		Art.-No.	Art.-No.
Nominal power rating			
500 VA		86023	86024
630 VA		86033	86034
800 VA		86043	86044
1000 VA		86053	86054
Technical data			
Input voltage	230 V AC $\pm 5\%$	400 V AC $\pm 5\%$	
Output voltage	24 V AC SELV		

Notes