


Data Sheet | Item Number: 2687-2144

Power supply; Eco 2; 1-phase; 24 VDC output voltage; 5 A output current; DC OK contact

<https://www.wago.com/2687-2144>



Features:

- Signal output, optical status indication
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Connection technology with push-in termination and tool-free lever operation
- Electrically isolated output voltage (SELV/PELV) per EN 61010/UL 61010
- Marker slot (2789-1233, not included) for WAGO marking cards (WMB) and WAGO marking strips



Technical data

Input		Output	
Phases	1	Nominal output voltage $U_{o\,nom}$	24 VDC (SELV)
Nominal input voltage $U_{i\,nom}$	1 x 100 ... 240 VAC	Output voltage range	23 ... 28 VDC (adjustable)
Input voltage range	1 x 90 ... 264 VAC	Default Setting	DC 24 V
Nominal mains frequency range	50 ... 60 Hz; 0 Hz	Nominal output current $I_{o\,nom}$	5 A (24 VDC)
Input current I_i	≤ 0.8 A (230 VAC; nominal load); ≤ 1.5 A (100 VAC; nominal load)	Nominal output power	120 W
Inrush current	≤ 20 A (after 1 ms)	Deviation	≤ 1 %
Power factor correction (PFC)	Active	Residual ripple	≤ 75 mV (peak-to-peak)
Mains failure hold-up time	≥ 20 ms (230 VAC)	Overload behavior	Constant power up to 125 %; shutdown and automatic restart in the event of a short circuit

Signaling and communication	
Signaling	Optical status indication (overload) Optical status indication (DC OK) Digital signal output (DO)

Efficiency/power losses	
Power loss P_i	≤ 3 W (no load); ≤ 12 W (nominal load)
Efficiency (typ.)	90 %

Circuit protection	
Internal fuse	T 3.15 A / 250 VAC
Backup fusing (recommended)	16 A (for USA/Canada: 15 A)

Safety and protection	
Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	0.5 kVDC
Isolation voltage (sec.-signal)	0.5 kVDC
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III (≤ 2000 m a.s.l.); II (> 2000 m a.s.l.)
Pollution degree	2
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 1,000,000$ h (per IEC 61709)

Connection data

Connection 1	
Connection type	Input/output/signaling
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 2604 Series
Solid conductor	0.2 ... 4 mm² / 24 ... 12 AWG
Fine-stranded conductor	0.2 ... 4 mm² / 24 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	0.25 ... 2.5 mm²
Fine-stranded conductor; with uninsulated ferrule	0.25 ... 2.5 mm²
Strip length	9 ... 11 mm / 0.35 ... 0.43 inches



Physical data		
Width		38 mm / 1.496 inches
Height		130 mm / 5.118 inches
Depth from upper-edge of DIN-rail		130 mm / 5.118 inches

Mechanical data		
Mounting type		DIN-35 rail

Material data		
Fire load		0 MJ
Weight		620 g

Environmental requirements		
Ambient temperature (operation)		-25 ... +70 °C (device starts at -40 °C (type-tested))
Ambient temperature (storage)		-40 ... +85 °C
Relative humidity		5 ... 96 % (no condensation permissible)
Derating		-2.5 %/K, > 55 °C; -10 %/V, > 24 V
Climatic category		3K3 (per EN 60721)
Operating altitude (max.)		5000 m

Standards and specifications		
Conformity marking		CE
Standards/specifications		EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201 SEMI F47

Commercial data		
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		CN
GTIN		4066966401080
Customs tariff number		85044083900

Product classification		
UNSPSC		39121004
ETIM 9.0		EC002540
ETIM 8.0		EC002540
ECCN		NO US CLASSIFICATION



Environmental Product Compliance	
CAS-No.	1303-86-2 1317-36-8 7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Diboron trioxide Lead Lead monoxide
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	88b095ec-76a2-44ba-bc4f-8af04d3aa869
SCIP notification number (Belgium)	1f36d4b5-c2bd-4fa4-9ba7-fab4560274ea
SCIP notification number (Bulgaria)	ece2741c-94c2-4643-8455-4af30ed67835
SCIP notification number (Czech Republic)	cd95343d-b393-43cf-80b0-cccb5257bbfd
SCIP notification number (Denmark)	8de2a84b-c12a-4761-91dd-b119773534c8
SCIP notification number (Finland)	37dca7ef-68a8-4237-96ee-ffc69fca1b79
SCIP notification number (France)	be625ff9-61f8-44cb-a1b4-9c91e7ab498f
SCIP notification number (Germany)	0f1a79bc-42ce-497c-93aa-169b84dec80a
SCIP notification number (Hungary)	c75d9660-e9e0-4f6a-8094-a02f7eb002c5
SCIP notification number (Italy)	4058ebcb-e5d3-4e13-8a2c-bb034a513773
SCIP notification number (Netherlands)	e09550f1-21a2-4612-b815-cd116bb56de2
SCIP notification number (Poland)	42928b5b-13e1-44dc-bfe4-9af43f5d13b6
SCIP notification number (Romania)	42dd0d9d-70ff-4898-aa20-05f92774b9fb
SCIP notification number (Sweden)	d048877f-4660-48fa-8533-a6cfed8010d2

Approvals / Certificates

General approvals

Declarations of conformity and manufacturer's declarations

EAC EAC 		
Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03080
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 61010-2-201	UL-US-2218925-0_UL-CA-2218432-0

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Approvals for hazardous areas		
		
Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	E198726



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2687-2144

Download icon

Documentation

Manual

Power supply; Eco 2; 1-phase; 24 VDC output voltage; 5 A output current

V 1.1.1
19.03.2024

pdf
4627.56 KB

Download icon

Bid Text

2687-2144

xml
7.26 KB

Download icon

2687-2144

docx
29.77 KB

Download icon

Instruction Leaflet

Power supply; Eco 2

V 1.3.0
08.11.2022

pdf
2307.76 KB

Download icon

CAD/CAE-Data

CAD data

2D/3D Models
2687-2144

Download icon

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marker carrier



Item No.: 2789-1233

Marker carrier; for WMB or marking strips;
Length: 33 mm