


Emergency stop rope pull switches



Choose : **1** > **2** > **3** > **4** > **Reference**

Body and cable length Function Contact Connection

XY2CJ		Threaded cable entries - anchoring point	NC+NO	2NC	2NC+NO
Metal 20 meters cable length 30 meters cable length 30 meters cable length		Pg13.5 - straight	XY2CJS15 (1)	XY2CJS17 (1)	XY2CJS19 (1) (2)
		Pg13.5 - right side	XY2CJR15 (1)	XY2CJR17 (1)	XY2CJR19 (1) (2)
		Pg13.5 - left side	XY2CJL15 (1)	XY2CJL17 (1)	XY2CJL19 (1) (2)

(1) For ISO M20, just add "H29" to the part number (example: XY2CJS15 becomes XY2CJS15H29)

(2) For 1/2" NPT, just add "H7" to the part number (example: XY2CJS19 becomes XY2CJS19H7)

XY2CH		Tapped cable entries	NC+NO	2NC	2NC+NO
Metal 30 meters cable length Reset by booted pushbutton;		Pg13.5	XY2CH13250 (3)	XY2CH13270 (3)	XY2CH13290 (3)
		ISO M20	XY2CH13250H29	XY2CH13270H29	XY2CH13290H29
		1/2" NPT	XY2CH13250H7	XY2CH13270H7	XY2CH13290H7

(3) Also available with pilot light

XY2CE		Plain hole cable entries	NC+NO	2NC	2NC+2NO
Metal 70 meters cable length Reset by booted pushbutton; Anchor point on right side. Reset by booted pushbutton; Anchor point on left side.		Pg13.5	XY2CE1A250	XY2CE1A270	XY2CE1A290 (4)
		1/2" NPT	XY2CE1A250H7	XY2CE1A270H7	XY2CE1A290H7
		Pg13.5	XY2CE2A250	XY2CE2A270	XY2CE2A290 (4)
		1/2" NPT	XY2CE2A250H7	XY2CE2A270H7	XY2CE2A290H7

(4) Also available with pilot light

XY2CED		Plain hole cable entries	2 NC + 2 NO slow break
Metal >=2 x 35 meters cable length and <=2 x 100 meters cable length Reset by booted pushbutton Reset by key release (N° 455) pushbutton		Pg13.5	XY2CEDA290 (5)
		1/2" NPT	XY2CEDA290H7
		Pg13.5	XY2CEDA590 (5)

(5) Also available with pilot light

An adjustment shim and 2 end springs are supplied with **XY2CED** switches.

Accessories	XY2CJ	XY2CH	XY2CE	XY2CED
Mounting kit	XY2CZ9425 (5)	XY2CZ9330 (6)	XY2CZ9570 (7)	XY2CZ96200 (8)

(5) Kit contents: 1 galvanised cable L:30.5 (Ø 3.2 mm), quick tensioner, cable supports, and end spring.

(6) Kit contents: 1 galvanised cable L: 30.5 m (Ø 3.2 mm) and end spring.

(7) Kit contents: 1 galvanised cable L: 70.5 m (Ø 5 mm), turnbuckle, cable supports, cable end protectors and end spring.

(8) Kit contents: 2 galvanised cables L: 100.5m (D 5mm) and quick tensioners.