


Safety light curtains

Choose :



XUSL Type 4		Finger detection (resolution 14 mm)	Hand detection (resolution 30 mm)	Body detection (detection thru 2-3 or 4 beams)
Finger, hand and body detection (5)		Sensing distance 0...3m or 1...6m selectable		
PLe/Cat4 - SIL3		Sensing distance 0...4m or 0...12m selectable		
		Automatic or manual start/restart		
		External Device Monitoring (EDM)		
Height protected (mm)				
160	XUSL4E14F016N	XUSL4E30H016N		
260		XUSL4E30H026N		
310	XUSL4E14F031N	XUSL4E30H031N		
460	XUSL4E14F046N	XUSL4E30H046N		
510 - 2 beams				XUSL4E2BB051N
610	XUSL4E14F061N	XUSL4E30H061N		
760	XUSL4E14F076N	XUSL4E30H076N		
810 - 3 beams				XUSL4E3BB081N
910	XUSL4E14F091N	XUSL4E30H091N		
910 - 4 beams				XUSL4E4BB091N
1060	XUSL4E14F106N	XUSL4E30H106N		
1210	XUSL4E14F121N	XUSL4E30H121N		
1360	XUSL4E14F136N	XUSL4E30H136N		
1510	XUSL4E14F151N	XUSL4E30H151N		
1660	XUSL4E14F166N	XUSL4E30H166N		
1810	XUSL4E14F181N	XUSL4E30H181N		
XUSL4M				
510 - 2 beams				Integrated muting (1) (4)
810 - 3 beams				XUSL4MA2BB051N (2)
910 - 4 beams				XUSL4MB2BB051N (3)
				XUSL4MA3BB081N (2)
				XUSL4MB3BB081N (3)
				XUSL4MA4BB091N (2)
				XUSL4MB4BB091N (3)

- (1) Possible association with pre-built/pre-adjusted muting arms XUSZAS* (single beam muting sensors) and XUSZAM* multi-beam muting sensors).
- (2) Hardware and Software configuration (with SoMute software), partial muting and integrated muting lamp
- (3) Hardware configuration only
- (4) For hand detection, some models are available in 30mm and 40mm resolutions, in different protected heights
- (5) IP69K special models with ECOLAB conformity are available for XUSL4E and XUSL2E

XUSL Type 2		Hand detection (resolution 30 mm)	Body detection (thru 2-3 or 4 beams)
Hand and body detection (5)		Sensing distance 0...4m or 0...12m selectable	
PLc/Cat2 - SIL1		Automatic or manual start/restart	
		External Device Monitoring (EDM)	
		Height protected (mm)	
160	XUSL2E30H016N		
260	XUSL2E30H026N		
310	XUSL2E30H031N		
460	XUSL2E30H046N		
510 - 2 beams			XUSL2E2BB051N
610	XUSL2E30H061N		
760	XUSL2E30H076N		
810 - 3 beams			XUSL2E3BB081N
910	XUSL2E30H091N		
910 - 4 beams			XUSL2E4BB091N
1060	XUSL2E30H106N		
1210	XUSL2E30H121N		
1360	XUSL2E30H136N		
1510	XUSL2E30H151N		
1660	XUSL2E30H166N		
1810	XUSL2E30H181N		

Accessories		For use with...	
Pre-wired connectors		XUSL2E*/4E*/4M*	XUSL2E*/4E*
		M12 connector 5 pins - Female	
		Transmitter	
	Length	Straight	90°
	2 m	XZCP1164L2	XZCP1264L2
	5 m	XZCP1164L5	XZCP1264L5
	10 m	XZCP1164L10	XZCP1264L10
	15 m	XZCP1164L15	XZCP1264L15
	25 m	XZCP1164L25	XZCP1264L25
		For use with XUSL2E* / 4E*	
		M12 connector 8 pins - Female	
		Receiver	
	Length	Straight	90°
	2 m	XZCP29P11L2	XZCP53P11L2
	5 m	XZCP29P11L5	XZCP53P11L5
	10 m	XZCP29P11L10	XZCP53P11L10
	15 m	XZCP29P11L15	XZCP53P11L15
	25 m	XZCP29P11L25	XZCP53P11L25
		For use with XUSL4M*	
		M12 connector 12 pins - Female	
		Receiver	
	Length	Straight	
	5 m	XZCP57V12L5	
	10 m	XZCP57V12L10	
	15 m	XZCP57V12L15	