


Double-Deck Terminal Block 2.5 (4 "f-st") mm²; 870 Series

Technical Data

0.08 ... 2.5 (4 "f-st") mm ² ①	28 ... 12 AWG
500 V/6 kV/3 ②	300 V, 20 A, ③
I _N 24 A	
Terminal block width: 5 mm / 0.197 inch	
6 ... 7 mm / 0.24 ... 0.28 inch	



Double-deck terminal block; Through/through terminal block; Gray housing

	Item No.	Pack. Unit
○ L/L	870-501	50
○ N/L	870-502	50
○ L/N	870-503	50

Double-deck terminal block; Through/through terminal block; Blue housing


● N/N	870-504 ④	50
-------	-----------	----

Double-deck terminal block; Through/through terminal block; Light gray housing

○ L/L ⑤	870-961 ④	50
---------	-----------	----

Other terminal blocks with the same profile:

Diode	870-540/281-410	Page 436
LED	870-543/281-434	Page 436



Double-deck terminal block; 4-conductor through terminal block; internally commoned; Violet conductor entry; Gray housing


	Item No.	Pack. Unit
○ L	870-508	50

Double-deck terminal block; 4-conductor through terminal block; internally commoned; Violet conductor entry; Blue housing

● N	870-509 ④	50
-----	-----------	----

Technical Data

0.08 ... 2.5 (4 "f-st") mm ² ①	28 ... 12 AWG
500 V/6 kV/3 ②	
I _N 24 A	
Terminal block width: 5 mm / 0.197 inch	
6 ... 7 mm / 0.24 ... 0.28 inch	




Double-deck terminal block; Ground conductor/through terminal block; Gray housing

	Item No.	Pack. Unit
○ GND/N	870-517	50
○ GND/L	870-527	50

Double-deck terminal block; Ground conductor/through terminal block; Light gray housing

○ GND/L ⑥	870-967/999-950 ④	50
-----------	-------------------	----



Double-deck terminal block; 4-conductor ground terminal block; internally commoned; Green-yellow housing

	Item No.	Pack. Unit
● GND	870-507	50

- ① Max. insulation diameter: 4.4 mm
 - ② 500 V = rated voltage
6 kV = rated impulse voltage
3 = pollution degree (see Section 14)
 - ③ Terminal blocks with a blue insulated housing are suitable for Ex i applications.
 - ④ Suitable for Ex e II applications
0.2 ... 2.5 (4 "f-st") mm² / 24 ... 12 AWG
440 V; 22 A (see Section 14)
Using one or more push-in type jumper bars, the maximum rated voltage is reduced to 275 V and the rated current to 13.5 A.
- See application notes for:
Insulation stop, see page 346
Group marker carrier, page 435
- Approvals and corresponding ratings, visit www.wago.com

Accessories; 870 Series

Appropriate marking systems:
Mini-WSB/Mini-WSB Inline/WMB/WMB Inline

End and intermediate plate; 2 mm thick

orange	870-519	100 (25)
gray	870-518	100 (25)

Ex e/Ex i separator; orange; 3 mm thick

125.5 mm	209-192	50 (25)
----------	---------	---------

Insulation stop; 0.08 ... 0.2 mm² "s" (0.14 mm² "f-st"); 5 pcs/strip

white	280-470	200 (25)
-------	---------	----------

Insulation stop; 0.25 ... 0.5 mm²; 5 pcs/strip

light gray	280-471	200 (25)
------------	---------	----------

Insulation stop; 0.75 ... 1 mm²; 5 pcs/strip

dark gray	280-472	200 (25)
-----------	---------	----------

Protective warning marker; with black high-voltage symbol; for 5 terminal blocks

yellow	280-405	100 (25)
--------	---------	----------

Push-in type jumper bar; insulated; I_N 18 A; light gray

2-way	870-402	200 (25)
3-way	870-403	200 (25)
4-way	870-404	100 (25)
5-way	870-405	100 (25)
6-way	870-406	100 (25)
7-way	870-407	100 (25)
8-way	870-408	100 (25)
9-way	870-409	100 (25)
10-way	870-410	50 (25)


Push-in type jumper bar; insulated; I_N 18 A; light gray

1 to 3	870-433	200 (25)
1 to 4	870-434	200 (25)
1 to 5	870-435	100 (25)
1 to 6	870-436	100 (25)
1 to 7	870-437	100 (25)
1 to 8	870-438	100 (25)
1 to 9	870-439	100 (25)
1 to 10	870-440	50 (25)

7


3-Conductor Double-Deck Terminal Block 2.5 (4 "f-st") mm²; 870 Series

Technical Data	
0.08 ... 2.5 (4 "f-st") mm ² ①	28 ... 12 AWG
500 V/6 kV/3 ②	300 V, 20 A, ③
I _N 24 A	
Terminal block width: 5 mm / 0.197 inch	
6 ... 7 mm / 0.24 ... 0.28 inch	



3-conductor double-deck terminal block; Through/through terminal block; Gray housing		
	Item No.	Pack. Unit
○ L/L	870-531	50
○ N/L	870-532	50
○ L/N	870-533	50


3-conductor double-deck terminal block; Through/through terminal block; Blue housing		
● N/N	870-534 ③	50



3-conductor double-deck terminal block; 6-conductor through terminal block; internally commoned; Violet conductor entry; Gray housing		
	Item No.	Pack. Unit
○ L	870-538	50

3-conductor double-deck terminal block; 6-conductor through terminal block; internally commoned; Violet conductor entry; Blue housing		
● N	870-539 ③	50

Technical Data	
0.08 ... 2.5 (4 "f-st") mm ² ①	28 ... 12 AWG
500 V/6 kV/3 ②	
I _N 24 A	
Terminal block width: 5 mm / 0.197 inch	
6 ... 7 mm / 0.24 ... 0.28 inch	



3-conductor double-deck terminal block; Ground conductor/through terminal block; Gray housing		
	Item No.	Pack. Unit
○ GND/N	870-535	50
○ GND/L	870-536	50

3-conductor double-deck terminal block; 6-conductor ground terminal block; internally commoned; Green-yellow housing		
	Item No.	Pack. Unit
● GND	870-537	50

- ① Max. insulation diameter: 4.4 mm
 - ② 500 V = rated voltage
6 kV = rated impulse voltage
3 = pollution degree (see Section 14)
 - ③ Terminal blocks with a blue insulated housing are suitable for Ex i applications.
- See application notes for:
Insulation stop, see page 346
Group marker carrier, page 435
- Approvals and corresponding ratings, visit www.wago.com

Accessories; 870 Series
Appropriate marking systems:
Mini-WSB/Mini-WSB Inline/WMB/WMB Inline

End and intermediate plate; 2 mm thick			
orange	870-574	100 (25)	
gray	870-573	100 (25)	

Insulation stop; 0.08 ... 0.2 mm ² "s" (0.14 mm ² "f-st"); 5 pcs/strip			
white	280-470	200 (25)	

Insulation stop; 0.25 ... 0.5 mm ² ; 5 pcs/strip			
light gray	280-471	200 (25)	

Insulation stop; 0.75 ... 1 mm ² ; 5 pcs/strip			
dark gray	280-472	200 (25)	

Protective warning marker; with black high-voltage symbol; for 5 terminal blocks			
yellow	280-405	100 (25)	

Push-in type jumper bar; insulated; I _N 18 A; light gray			
2-way	870-402	200 (25)	
3-way	870-403	200 (25)	
4-way	870-404	100 (25)	
5-way	870-405	100 (25)	
6-way	870-406	100 (25)	
7-way	870-407	100 (25)	
8-way	870-408	100 (25)	
9-way	870-409	100 (25)	
10-way	870-410	50 (25)	

Push-in type jumper bar; insulated; I _N 18 A; light gray			
1 to 3	870-433	200 (25)	
1 to 4	870-434	200 (25)	
1 to 5	870-435	100 (25)	
1 to 6	870-436	100 (25)	
1 to 7	870-437	100 (25)	
1 to 8	870-438	100 (25)	
1 to 9	870-439	100 (25)	
1 to 10	870-440	50 (25)	

Marking strip; plain; 7.5 mm wide; 1 m long			
translucent	709-196	1	

Mini-WSB marking card; white; 10 strips with 10 markers/card; 5 mm wide markers			
plain	248-501	5	